



ORDERING INFORMATION

100X-BLK (BASE SYSTEM)	LRAD 100X battery powered portable long range communication system
100X-BLK-MAG	LRAD 100X base system with additional magnetic base and yoke to secure the LRAD to metallic surfaces, like vehicle roofs
100X-BLK-MAG-SYS	LRAD 100X base system with additional magnetic base, yoke, and wireless kit for remote operation out to 200 m
100X-BLK-STUD	LRAD 100X base system with additional yoke for mounting on tripod (tripod sold separately)

INCLUDED ACCESSORIES

MP3 Player	MP3 player to store, control, and broadcast audio messages and tones
Record on the Fly Mic	Microphone with record and playback feature for immediate playback
MP3 Auxiliary Cable	Allows connection to any audio device with a headphone jack
USB Cable	USB cable for downloading files to the MP3 player
Li-Fe-PO4 Battery	8-Hour Lithium Iron Phosphate rechargeable battery
Battery Charger	AC powered battery charger with LED battery charge status display
Hard Case	Watertight, dust proof, rugged enclosure for storage and transport

OPTIONAL ACCESSORIES

Wireless Kit	Wireless operation of LRAD systems over ranges up to 300 meters, 35mm phone jack connects to a standard MP3 audio device (UHF, US only). Lightweight hypercardioid headset microphone is included
HD Action Camera	During LRAD operation, record High Definition, date/time stamped video and audio with this compact, rugged digital camera
AC Power Supply	Can be powered by a standard AC source in place of the battery
Cigarette lighter/plug cable	Cigarette lighter/plug cable powers LRAD through 12 VDC cigarette lighter
Stud Mount	Mounting yoke kit for LRAD-100X, compatible for LRAD tripods (tripod not included)
Stud Kit	Stud weldment kit
Medium-Duty Tripod	Reusable hard case available for purchase
Table Mount Kit	Fixed mount for flat surfaces
Tactical Pack	Rugged backpack for operation of the LRAD 100X within the pack or on the move
Front Carry Pack	For mobile or stationary operation of the LRAD 100X
VAC Mount	Mounts LRAD 100X on most smooth or slightly curved nonporous surfaces

DIRECTIONALITY, POWER, RANGE & INTELLIGIBILITY

- › Powerful, intelligible voice communications up to 600 meters
- › **Speech Transmission Index** of 0.95 out of 1.0 in optimum conditions
- › Focused, directional broadcasts for targeted communication
- › Safely communicate beyond standoff distances
- › Create instant acoustic standoff perimeter
- › Deliver clearly heard and understood communications into buildings & vehicles

FEATURES

- › 8-hour rechargeable battery
- › Operate easily with gloves or Mopp gear
- › Optional power sources
- › Simple Operator Interface
- › Water resistant

MARKETS SERVED

- › Law Enforcement
- › Defense
- › Commercial Security
- › Critical Infrastructure Security
- › Maritime
- › Homeland Security
- › Fire Rescue & Incident Management
- › Border & Port Security
- › Emergency Warning
- › Mass Notification
- › Wildlife Preservation & Asset Protection

LRAD 100X

Lightweight, Portable, Long Range Communication

SELF-CONTAINED, PORTABLE COMMUNICATION SYSTEM

The LRAD 100X is a self-contained, portable communication system for on-scene and tactical communication.

With unparalleled vocal clarity and up to 30db louder than bullhorns, megaphones, and vehicle P.A. systems, the LRAD 100X is also four to six times louder than other acoustic hailers of comparable size and weight. LRAD's optimized driver and waveguide technology ensures every message is clearly broadcast, heard and understood, even above engine, crowd, siren, and background noise.

The LRAD warning tone commands attention to the voice messages that follow and provides a safer alternative to non-lethal and kinetic measures for changing behavior.



ACOUSTIC PERFORMANCE

Maximum Peak Output	140dB SPL @ 1 meter, C-weighted
Maximum Continuous Output	137db SPL @ 1 meter, A-weighted
Sound Projection	+/- 15° @ 1kHz/-3dB
Communication Ranges	Maximum range up to 600 meters in ideal conditions. Operational range up to 250 meters over 88dB of background noise. Ranges based on continuous output.

ENVIRONMENTAL PERFORMANCE

Hot Operating Temperature	MIL-STD-810G, Method 501.5, Procedure II, Design type Hot, 60°C
Cold Operating Temperature	MIL-STD-810G, Method 502.5, Procedure II, Design type Basic Cold, -33°C
Hot Storage Temperature	MIL-STD-810G, Method 501.5, Procedure I, 70°C
Cold Storage Temperature	MIL-STD-810G, Method 502.5, Procedure I, -40°C
Operating Humidity	MIL-STD 810G, Method 507.5, Procedure II – Aggravated Cycle
Rain	MIL-STD-810G, Method 506.5, Procedure I, Blowing rain
Salt Fog	MIL-STD-810G, Method 509.5
Shipboard Vibration	MIL-STD-167-1A
Shipboard Shock	MIL-S-901D, Class I, Shock grade B
Random Vibration	MIL-STD-810G, Method 516.6, Procedure I, (Functional shock)

MECHANICAL

Dimensions	14"W x 14" H x 6.5"D (35.6 x 35.6 x 16.5 cm)
Weight	15 lbs.(6.8 kg) with battery, accessories and cables
Construction	Injection molded, impact resistant polymer, 6061 Aluminum

ELECTRICAL REQUIREMENTS¹

Power Consumption	Typical Power consumption 85 Watts (With tone) Normal power consumption 20 Watts (With voice content)
Power Input	10.8 to 16.8 VDC, Included rechargeable 13.2VDC Li-Fe-PO battery for up to 2 hours of continuous operation at maximum volume on a full charge.

¹ BATTERY LIFE UP TO 2 HOURS OF CONTINUOUS OPERATION AT MAXIMUM TONE ON A FULL CHARGE. ADAPTERS AVAILABLE FOR AUTO CIGARETTE LIGHTER AND FOR 2590 RECHARGEABLE MILITARY BATTERY.

SAFETY²

MIL-STD-1474D

² DESIGNED TO MEET MIL-STD-1474D STANDARD WHICH ESTABLISHES ACOUSTICAL NOISE LIMITS AND PRESCRIBES TESTING REQUIREMENTS AND MEASUREMENT TECHNIQUES FOR DETERMINING CONFORMANCE TO THE NOISE LIMITS SPECIFIED THEREIN.

ELECTROMAGNETIC COMPATIBILITY (EMC)³

FCC Part 15 class A radiated emissions

³ DESIGNED TO MEET REQUIREMENTS FOR THE CONTROL OF ELECTROMAGNETIC INTERFERENCE CHARACTERISTICS OF SUBSYSTEMS AND EQUIPMENT.



Genasys - The Leader in Protective Communications

Genasys Protective Communications Solutions have a diverse range of applications, including predictive simulation to anticipate and understand the potential impact of emerging crises; emergency warning and mass notification for public safety; critical event management for commercial enterprises and government agencies; de-escalation for defense and law enforcement; as well as automatic detection of real-time threats. For more information, visit genasys.com.

SCAN FOR VIDEO



Genasys products are available for purchase through multiple channels including: DLA TLS SOE, GSA Advantage, Federal and State grants, FEMA Authorized Equipment List (AEL), and others. More information: sales@genasys.com

genasys.com

TEL: 858-676-1112 | +1 855 GENASYS | SALES@GENASYS.COM
16262 WEST BERNARDO DRIVE · SAN DIEGO, CA 92127 USA

SPECIFICATIONS SUBJECT TO CHANGE · ©2023 GENASYS INC.