

Symbolic Crosschecking of Floating-Point and SIMD Code

Peter Collingbourne, Cristian Cadar, Paul H J Kelly

Department of Computing, Imperial College London

4 November, 2010

Outline

- ▶ SIMD
- ▶ Symbolic Execution
- ▶ KLEE-FP
- ▶ Evaluation

SIMD

- ▶ Single Instruction Multiple Data
- ▶ A popular means of improving the performance of programs by exploiting data level parallelism
- ▶ SIMD vectorised code operates over one-dimensional arrays of data called vectors

```
_m128 c = _mm_mul_ps(a, b);
/* c = { a[0]*b[0], a[1]*b[1],
           a[2]*b[2], a[3]*b[3] } */
```

Symbolic Execution for SIMD

- ▶ Manually translating scalar code into an equivalent SIMD version is a difficult and error-prone task
- ▶ We propose a novel automatic technique for verifying that the SIMD version of a piece of code is equivalent to its (original) scalar version

Symbolic Execution


- ▶ Symbolic execution tests multiple paths through the program
- ▶ Determines the feasibility of a particular path by reasoning about all possible values using a constraint solver
- ▶ Can verify code correctness by verifying the absence of certain error types (such as array bounds errors or division by zero) on a per-path basis

Symbolic Execution – Operation

- ▶ Each variable may hold either a concrete or a symbolic value
- ▶ Symbolic value – an expression consisting of mathematical or boolean operations and symbols
- ▶ For example, an integer variable i may hold a value such as $x + 3$


Symbolic Execution – Example

```
unsigned int x;  
klee_make_symbolic(&x, sizeof(x), "x");  
assert(x > x - 1);  
if (x > x - 1)  
    ;  
else  
    abort();
```



Symbolic Execution – Example

```
unsigned int x;
klee_make_symbolic(&x, sizeof(x), "x");
assert(x > x - 1);
if (x > x - 1)
    ;
else
    abort();
```



Symbolic Execution – Example

```
unsigned int x;
klee_make_symbolic(&x, sizeof(x), "x");
assert(x > x - 1);
if (x > x - 1)
    ;
else
    abort();
```

x	x
$x > x - 1$	

x	x
$\neg(x > x - 1)$	

Symbolic Execution – Example

```
unsigned int x;
klee_make_symbolic(&x, sizeof(x), "x");
assert(x > x - 1);
if (x > x - 1)
;
else
    abort();
```

x	x
$x > x - 1$	

x	x
$\neg(x > x - 1)$	


Symbolic Execution – Example

```
unsigned int x;  
klee_make_symbolic(&x, sizeof(x), "x");  
if (x > 0) {  
    assert(x > x - 1);  
    if (x > x - 1)  
        ;  
    else  
        abort();  
}
```

x	⊥
---	---

Symbolic Execution – Example

```
unsigned int x;
klee_make_symbolic(&x, sizeof(x), "x");
if (x > 0) {
    assert(x > x - 1);
    if (x > x - 1)
        ;
    else
        abort();
}
```



Symbolic Execution – Example

```
unsigned int x;
klee_make_symbolic(&x, sizeof(x), "x");
if (x > 0) {
    assert(x > x - 1);
    if (x > x - 1)
        ;
    else
        abort();
}
```

x	x
$x > 0$	

x	x
$\neg(x > 0)$	

Symbolic Execution – Example

```
unsigned int x;
```

```
klee_make_symbolic(&x, sizeof(x), "x");
```

```
if (x > 0) {
```

```
    assert(x > x - 1);
```

```
    if (x > x - 1)
```

```
        ;
```

```
    else
```

```
        abort();
```

```
}
```

x	x
$x > 0$	
$x > x - 1$	

x	x
$x > 0$	
$\neg(x > x - 1)$	

x	x
$\neg(x > 0)$	

Issues

- ▶ SIMD vectorised code frequently makes intensive use of floating point arithmetic
- ▶ The current generation of symbolic execution tools lack or have poor support for floating point and SIMD

Technique

- ▶ For the purposes of this work, we need to test *equality*, not inequality
- ▶ The requirements for equality of two floating point values are harder to satisfy than for integers
- ▶ Usually, the two numbers need to be built up in the same way to be sure of equality
- ▶ This suits us just fine for verification purposes

KLEE

- ▶ Tool for symbolic testing of C and C++ code [Cadar, Dunbar, Engler, OSDI 2008]
- ▶ Based on the LLVM compiler framework
- ▶ `svn co http://llvm.org/svn/llvm-project/klee/trunk klee`
- ▶ Supports integer constraints only; symbolic FP not allowed

KLEE-FP: our modified version of KLEE

- ▶ Our improvements to KLEE:
 - ▶ Symbolic construction of floating-point operations
 - ▶ A set of expression matching and canonicalization rules for establishing FP equality
 - ▶ Support for SIMD instructions `insertelement`,
`extractelement`, `shufflevector`
 - ▶ Semantics for a substantial portion of Intel SSE instruction set
- ▶ Related contributions to LLVM:
 - ▶ Atomic intrinsic lowering
 - ▶ An aggressive variant of phi-node folding
- ▶ Selected modifications contributed upstream to KLEE/LLVM
- ▶ `git clone git://git.pcc.me.uk/~peter/klee-fp.git`

Scalar/SIMD Implementation


```
void zlimit(int simd, float *src, float *dst,
            size_t size) {
    if (simd) {
        __m128 zero4 = _mm_set1_ps(0.f);
        while (size >= 4) {
            __m128 srcv = _mm_loadu_ps(src);
            __m128 cmpv = _mm_cmpgt_ps(srcv, zero4);
            __m128 dstv = _mm_and_ps(cmpv, srcv);
            _mm_storeu_ps(dst, dstv);
            src += 4; dst += 4; size -= 4;
        }
    }
    while (size) {
        *dst = *src > 0.f ? *src : 0.f;
        src++; dst++; size--;
    }
}
```

Scalar/SIMD Implementation

```
void zlimit(int simd, float *src, float *dst,
            size_t size) {
    if (simd) {
        __m128 zero4 = _mm_set1_ps(0.f);
        while (size >= 4) {
            __m128 srcv = _mm_loadu_ps(src);
            __m128 cmpv = _mm_cmpgt_ps(srcv, zero4);
            __m128 dstv = _mm_and_ps(cmpv, srcv);
            _mm_storeu_ps(dst, dstv);
            src += 4; dst += 4; size -= 4;
        }
    }
    while (size) {
        *dst = *src > 0.f ? *src : 0.f;
        src++; dst++; size--;
    }
}
```


Scalar/SIMD Implementation

```
__m128 zero4 = _mm_set1_ps(0.f);
while (size >= 4) {
    __m128 srcv = _mm_loadu_ps(src);
    __m128 cmpv = _mm_cmpgt_ps(srcv, zero4);
    __m128 dstv = _mm_and_ps(cmpv, srcv);
    _mm_storeu_ps(dst, dstv);
    src += 4; dst += 4; size -= 4;
}
```



Scalar/SIMD Implementation

```
__m128 zero4 = _mm_set1_ps(0.f);
while (size >= 4) {
    __m128 srcv = _mm_loadu_ps(src);
    __m128 cmpv = _mm_cmpgt_ps(srcv, zero4);
    __m128 dstv = _mm_and_ps(cmpv, srcv);
    _mm_storeu_ps(dst, dstv);
    src += 4; dst += 4; size -= 4;
}
```




Scalar/SIMD Implementation


```
void zlimit(int simd, float *src, float *dst,
            size_t size) {
    if (simd) {
        __m128 zero4 = _mm_set1_ps(0.f);
        while (size >= 4) {
            __m128 srcv = _mm_loadu_ps(src);
            __m128 cmpv = _mm_cmpgt_ps(srcv, zero4);
            __m128 dstv = _mm_and_ps(cmpv, srcv);
            _mm_storeu_ps(dst, dstv);
            src += 4; dst += 4; size -= 4;
        }
    }
    while (size) {
        *dst = *src > 0.f ? *src : 0.f;
        src++; dst++; size--;
    }
}
```

Scalar/SIMD Implementation

```
while (size) {  
    *dst = *src > 0.f ? *src : 0.f;  
    src++; dst++; size--;  
}
```



Scalar/SIMD Implementation




$$\text{And}(\text{SExt}(P^1), X) \rightarrow \text{Select}(P^1, X, 0)$$

Cross-checking SIMD Code

```
int main(void) {
    float src[64], dstv[64], dsts[64];
    uint32_t *dstvi = (uint32_t *)dstv;
    uint32_t *dstsi = (uint32_t *)dsts;
    unsigned i;
    klee_make_symbolic(src, sizeof(src), "src");
    zlimit(0, src, dsts, 64);
    zlimit(1, src, dstv, 64);
    for (i = 0; i < 64; ++i)
        assert(dstvi[i] == dstsi[i]);
}
```


Checking Equality

$$\begin{aligned}& \neg(I2F(x << 1) +_f 2.0 *_f I2F(0 - x)) \\&= I2F(x \times 2) +_f 2.0 *_f I2F(\sim x + 1)) \\&\rightarrow \neg(x << 1 = x \times 2 \wedge 0 - x = \sim x + 1)\end{aligned}$$



Checking Equality

$$\begin{aligned}& \neg(I2F(x << 1) +_f 2.0 *_f I2F(0 - x)) \\&= I2F(x \times 2) +_f 2.0 *_f I2F(\sim x + 1)) \\&\rightarrow \neg(x << 1 = x \times 2 \wedge 0 - x = \sim x + 1)\end{aligned}$$



Floating Point Operations

- ▶ New nodes:

FAdd

FSub

FMul

FDiv

FRem

FPToSI

FPToUI

SIToFP

UIToFP

FPExt

FPTrunc

FCmp

- ▶ Outcome sets:

$$\mathbf{O} = \{<, =, >, \text{UNO}\}$$

Shorthand	CmpInst::Predicate	FCmp operation	Meaning
$\text{F0eq}(X, Y)$	$\text{FCMP_OEQ} = 0\ 0\ 0\ 1$	$\text{FCmp}(X, Y, \{=\})$	Ordered =
$\text{F0lt}(X, Y)$	$\text{FCMP_OLT} = 0\ 1\ 0\ 0$	$\text{FCmp}(X, Y, \{<\})$	Ordered <
$\text{F0le}(X, Y)$	$\text{FCMP_OLE} = 0\ 1\ 0\ 1$	$\text{FCmp}(X, Y, \{<, =\})$	Ordered \leq
$\text{FUno}(X, Y)$	$\text{FCMP_UNO} = 1\ 0\ 0\ 0$	$\text{FCmp}(X, Y, \{\text{UNO}\})$	Unordered test

Expression Transformation Rules

- ▶ 18 rules, including:

$$\text{And}(\text{FCmp}(X, Y, O_1), \text{FCmp}(X, Y, O_2)) \rightarrow \text{FCmp}(X, Y, O_1 \cap O_2)$$
$$\text{Or}(\text{FCmp}(X, Y, O_1), \text{FCmp}(X, Y, O_2)) \rightarrow \text{FCmp}(X, Y, O_1 \cup O_2)$$
$$\text{Eq}(\text{FCmp}(X, Y, O), \text{false}) \rightarrow \text{FCmp}(X, Y, \mathbf{O} \setminus O)$$
$$\text{F0eq}(\text{SIToFP}(X), C) \rightarrow \text{Eq}(X, \text{FPToSI}(C))$$
$$\text{F0eq}(\text{UIToFP}(X), C) \rightarrow \text{Eq}(X, \text{FPToUI}(C))$$
$$\text{And}(\text{SExt}(P^1), X) \rightarrow \text{Select}(P^1, X, 0)$$

Category Analysis

$$\mathbf{C} = \{\text{NaN}, -\infty, -, 0, +, +\infty\}$$

$$\frac{+ \in \text{cat}(x) \quad + \in \text{cat}(y)}{\{+, +\infty\} \subseteq \text{cat}(x + y)}$$

$$\frac{\text{cat}(x) = \{0, -\} \quad \text{cat}(y) = \{0, +\}}{\neg(x > y)}$$

SSE Intrinsic Lowering

- ▶ Total of 37 intrinsics supported
- ▶ Implemented via a lowering pass that translates the intrinsics into standard LLVM instructions

Input code:

```
%res = call <8 x i16> @llvm.x86.sse2.pslli.w(
    <8 x i16> %arg, i32 1)
```

Output code:

```
%1 = extractelement <8 x i16> %arg, i32 0
%2 = shl i16 %1, 1
%3 = insertelement <8 x i16> undef, i16 %2, i32 0
%4 = extractelement <8 x i16> %arg, i32 1
%5 = shl i16 %4, 1
%6 = insertelement <8 x i16> %3, i16 %5, i32 1
...
%22 = extractelement <8 x i16> %arg, i32 7
%23 = shl i16 %22, 1
%res = insertelement <8 x i16> %21, i16 %23, i32 7
```

Phi Node Folding

```
val = silhData[x] ? ts : val < delbound ? 0 : val;
```

```
bb156:
```

```
...
%106 = load float* %scevgep345346, align 4
%107 = load i8* %scevgep351, align 1
%108 = icmp eq i8 %107, 0
br i1 %108, label %bb158, label %bb163
```

```
bb158:
```

```
%109 = fcmp uge float %106, %51
%iftmp.388.0 = select i1 %109, float %106,
                           float 0.000000e+00
br label %bb163
```

```
bb163:
```

```
%iftmp.387.0 = phi float [ %iftmp.388.0, %bb158 ],
                           [ %49, %bb156 ]
```

```
...
```

Phi Node Folding

```
val = silhData[x] ? ts : val < delbound ? 0 : val;
```

```
bb156:
```


```
...
%106 = load float* %scevgep345346, align 4
%107 = load i8* %scevgep351, align 1
%108 = icmp eq i8 %107, 0
%109 = fcmp uge float %106, %51
%iftmp.388.0 = select i1 %109, float %106,
                           float 0.000000e+00
%iftmp.387.0 = select i1 %108, %iftmp.388.0 , %49
...
...
```

- ▶ 13×13 matrix:

$$2^{169} \rightarrow 1$$

Evaluation

- ▶ We evaluated our technique on a set of benchmarks that compare scalar and SIMD variants of code developed independently by third parties
- ▶ The code base that we selected was OpenCV 2.1.0, a popular C++ open source computer vision library



Evaluation

- ▶ Out of the twenty OpenCV source code files containing SSE code, we selected ten files upon which to build benchmarks
- ▶ Crosschecked 49 SIMD/SSE implementations against scalar versions
 - ▶ Proved the *bounded* equivalence (i.e. *verified*) 39
 - ▶ Found inconsistencies in the other 10

Evaluation – Coverage

Source File (src/)	# SIMD	Cov.
cv/cvcorner.cpp	44	100%
cv/cvfilter.cpp	1332	N/A
cv/cvimgwarp.cpp	1070	74.6%
cv/cvmoments.cpp	35	100%
cv/cvmorph.cpp	1220	43.6%
cv/cvmotempl.cpp	43	100%
cv/cvpyramids.cpp	125	44.0%
cv/cvstereobm.cpp	270	53.3%
cv/cvthresh.cpp	238	100%
cxcore/cxmatmul.cpp	352	100%

OpenCV – Verified up to a certain size

#	Bench	Algo	K	Fmt	Max Size
1	morph	dilate	R	u8	4 × 1
2				s16	13 × 13
3				u16	12 × 12
4		NR	s16	13 × 13	
5				u16	13 × 13
6				f32	13 × 13
7		erode	R	s16	13 × 13
8				u16	13 × 13
9			NR	s16	14 × 14
10				u16	13 × 13
11	pyramid			u8	8 × 2 → 4 × 1
12	remap	nearest neighbor		u8	19 × 19
13				s16	19 × 19
14				u16	19 × 19
15				f32	19 × 19
16		linear		u8	19 × 19
17				s16	19 × 19
18				u16	19 × 19
19				f32	19 × 19
20		cubic		u8	19 × 19
21				s16	19 × 19
22				u16	19 × 19
23				f32	19 × 19

#	Bench	Algo	K	Fmt	Max Size	
24	resize	linear		s16	4 × 4 → 8 × 8	
25				f32	4 × 4 → 8 × 8	
26		cubic		s16	4 × 4 → 8 × 8	
27				f32	4 × 4 → 8 × 8	
28	silhouette			u8 f32	4 × 4	
29	thresh	BINARY		u8	13 × 13	
30				f32	13 × 13	
31		BINARY_INV		u8	13 × 13	
32				f32	13 × 13	
33		TRUNC		u8	13 × 13	
34				u8	13 × 13	
35		TOZERO		f32	13 × 13	
36				u8	13 × 13	
37		TOZERO_INV		f32	13 × 13	
38	transff.43			f32		
39	transff.44			f32		

OpenCV – Mismatches found

#	Bench	Algo	K	Fmt	Size	Description
1	eigenval			f32	4×4	Precision
2	harris			f32	4×4	Precision, associativity
3	morph	dilate	R	f32	4×1	Order of min/max operations
4			NR	f32	4×1	
5		erode	R	f32	4×1	
6	thresh	TRUNC		f32	4×4	
7	pyramid			f32	$16 \times 2 \rightarrow 8 \times 1$	Associativity, distributivity
8	resize	linear		u8	$4 \times 4 \rightarrow 8 \times 8$	Precision
9	transsf.43			s16 f32		Rounding issue
10	transcf.43			u8 f32		Integer/FP differences

morph (f32) and thresh (TRUNC, f32)

- ▶ `std::min`, `std::max`, `std::minmax` PS:

$$\min(X, Y) = \text{Select}(\text{Folt}(X, Y), X, Y)$$
$$\max(X, Y) = \text{Select}(\text{Folt}(Y, X), X, Y)$$

$$\min(X, \text{NaN}) = \text{NaN}$$
$$\min(\text{NaN}, Y) = Y$$

$$\min(\min(X, \text{NaN}), Y) = \min(\text{NaN}, Y) = Y$$
$$\min(X, \min(\text{NaN}, Y)) = \min(X, Y)$$

morph (f32) and thresh (TRUNC, f32)

- ▶ `std::min`, `std::max`, `std::minmax` PS:

$$\min(X, Y) = \text{Select}(\text{Folt}(X, Y), X, Y)$$
$$\max(X, Y) = \text{Select}(\text{Folt}(Y, X), X, Y)$$

$$\min(X, \text{NaN}) = \text{NaN}$$
$$\min(\text{NaN}, Y) = Y$$

$$\min(\min(1, \text{NaN}), 2) = \min(\text{NaN}, 2) = 2$$
$$\min(1, \min(\text{NaN}, 2)) = \min(1, 2) = 1$$

Conclusion and Future Work

- ▶ KLEE-FP extends KLEE with floating point/SIMD capabilities
- ▶ Has been used to find bugs in code extracted from the wild
- ▶ Future work may involve:
 - ▶ Inequalities
 - ▶ Interval arithmetic
 - ▶ Affine arithmetic
 - ▶ Floating point counterexamples
 - ▶ GPUs: CUDA/OpenCL?

Q&A

```
git clone git://git.pcc.me.uk/~peter/klee-fp.git
```