


Service Manual

Applicable models	Model Code
UR-BD160CM-DQ	22031010001661



(The picture is only for reference, and specific appearance and configuration are subject to the real product)

Prepared by	R&D:Liu Zhiyong
Reviewed by	QA:Huang Juan SVC:Zhang Kun
Approved by	R&D:Ma Rui SVC:GuangTaoshuai



Important Safety Notice

The Maintenance Manual is only for the use of maintenance personnel with certain experience and background in electrical, electronic and mechanical field.

Any attempt to repair main devices may lead to personal injury and property loss.

Manufacturers or distributors are not responsible for the content of the Manual and interpretation thereof.

Midea Refrigerators

Technical Maintenance Manual

Copyright ©2017

All rights reserved. Replication of all or part of the Manual in any forms shall not be allowed without written approval by the Overseas Sales Corporation of Midea Refrigerators.

Contents


1. SAFETY WARNING CODE	5
1.1 WARNING FOR OPERATION SAFETY	5
1.2 SAFETY INSTRUCTION FOR REFRIGERANT	8
2. DESCRIPTION FOR PRODUCT FEATURES	9
3. INSTALLATION AND COMMISSIONING	10
3.1 HANDLING	10
3.2 DISASSEMBLY (NONE)	10
3.3 INSTALLATION LOCATION	10
3.4 LEVELING OF THE REFRIGERATOR	11
3.5 CHANGE THE DOOR OPENING DIRECTION	11
3.6 INSTALLATION OF HANDLE(NONE)	12
3.7 INSTALLATION OF DOOR LOCK(NONE)	12
3.8 ADJUSTMENT TO LEVEL THE DOOR(NONE)	12
3.9 ADJUSTMENT TO SHELVES(NONE)	12
4. TERMS	13
4.1 DEFINITION OF MODEL(NONE)	13
4.2 LOCATION OF NAMEPLATE	13
5. PRODUCT SPECIFICATION	14
5.1 TYPE SPECIFICATION(NONE)	14
5.2 ELECTRICAL PARAMETERS	14
5.3 REFRIGERATING TEMPERATURE	14
5.4 DEFROSTING PARTS	15
5.5 CIRCUIT DIAGRAM	15
6. INTERNAL VIEW AND DIMENSION	16
6.1 MAIN PARTS AND THEIR NAMES	16
6.2 EXTERNAL DIMENSION	17
7. REFRIGERATING PIPING SYSTEM AND CIRCULATING ROUTE OF COOLING AIR ..	18
7.1 REFRIGERATING PIPING SYSTEM	18
7.2 CIRCULATING ROUTE OF COOLING AIR(NONE)	18
8. DISMANTLING OF PARTS	19
8.1 PARTS ON THE DOOR	19
8.2 LIGHT SYSTEM(NONE)	19
8.3 AIR DUCT COMPONENTS REFRIGERATING CHAMBER	19
8.4 AIR DUCT COMPONENTS IN FREEZING CHAMBER AND FAN MOTOR	19
8.5 EVAPORATOR AND TEMPERATURE SENSING SYSTEM	20
8.6 COMPRESSOR CASE	21

8.7DISPLAY AND MAIN CONTROL PANEL(NONE)	22
8.8 BAR COUNTER(NONE)	22
8.9 WATER DISPENSER(NONE)	22
8.10 ICE MAKER(NONE)	22
9. FUNCTION AND OPERATION	23
9.2TEMPERATURE CONTROL.....	23
9.3GIVE AN ALARM(NONE)	23
9.4FAILURE CODE AND SOLUTIONS(NONE).....	23
9.5DEFROST FUNCTION	23
9.6COMPRESSOR FAN CONTROL(NONE)	23
9.7SELF-DIAGNOSIS (NONE).....	23
10.CIRCUIT DESCRIPTION	24
10.1 POWER SUPPLY(NONE).....	24
10.2 TEST CIRCUIT FOR DOOR SWITCH(NONE).....	24
10.3 TEMPERATURE TEST CIRCUIT(NONE)	24
10.4FREEZER CHAMBER FAN MOTOR CIRCUIT (NONE).....	24
10.5REFRIGERATING CHAMBER FAN MOTOR CIRCUIT (NONE)	24
10.6CONDENSATION FAN CIRCUIT (NONE)	24
10.7 FAN MOTOR CIRCUIT OF THE VENTILATION DOOR(NONE)	24
10.8RESISTANCE VALUE OF THE SENSOR (R/T) (NONE).....	24
11.TROUBLESHOOTING METHOD.....	24
11.1 NOT COOLING	24
11.2 NOT WORKING OF COMPRESSOR	25
11.3 -THERMOSTAT MALFUNCTION-UNDERCOOLING.....	25
11.4 LIGHT IS NOT ON(NONE)	26
11.5 NOISE	26
12. FIGURES AND DETAILS OF REPAIR	
PARTS(DOCUMENTSAREPROVIDEDSEPARATELY)	26
12.1FIGURES	26
12.2LIST OF PARTS AND COMPONENTS.....	26
13APPENDIX:.....	26
13.1ELECTRICAL SCHEMATIC DIAGRAM(NONE)	26
13.2REFRIGERATOR MAINTENANCE TOOLING AND EQUIPMENT AND MATERIAL	26

1. Safety Warning Code

1.1 Warning for operation safety

Important Safety Instructions



This symbol indicates that dangerous voltage constituting a risk of electric shock is present within your freezer.



This symbol indicates that there are important operating and maintenance instructions in the literature accompanying your freezer.

WARNING

- 1 Read these instructions.
- 2 Keep these instructions.
- 3 Heed all warnings.
- 4 Follow all instructions.
- 5 Do not use this appliance near water.
- 6 Clean only with a damp cloth.
- 7 Do not block any ventilation openings.
- 8 Install in accordance with the manufacturer's instructions.
- 9 Do not install near any heat sources, such as radiators, heat registers, stoves, or other apparatus that produce heat.
- 10 Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
- 11 Protect the power cord from being walked on or pinched, particularly at plugs, convenience receptacles, and the point where they exit from the appliance.
- 12 Do not attempt to modify or extend the power cord of this appliance.
- 13 Unplug this appliance during lightning storms or when it will not be used for long periods of time.
- 14 Make sure that the available AC power matches the voltage requirements of this appliance.

- 15 Do not handle the plug with wet hands. This could result in an electric shock.
- 16 Unplug the power cord by holding the plug, never by pulling the cord.
- 17 Do not turn the appliance on or off by plugging or unplugging the power cord.
- 18 Refer all servicing to qualified service personnel. Servicing is required when the appliance has been damaged in any way, such as the power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the appliance, the appliance has been exposed to rain or moisture, does not operate normally, or has been dropped.
- 19 To reduce the risk of fire or electric shock, do not expose this appliance to rain, moisture, dripping, or splashing, and no objects filled with liquids should be placed on top of it.
- 20 Do not use extension cords or ungrounded (two prong) adapters.
- 21 This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
- 22 Children should be supervised to ensure that they do not play with the appliance.
- 23 If the supply cord is damaged, it must be replaced by the manufacturer, its service agent, or similarly qualified person, in order to avoid a hazard.
- 24 Take off the doors and leave the shelves in place so that children may not easily climb inside.



WARNING

Electric Shock Hazard

Failure to follow these instructions can result in electric shock, fire, or death.

- 1 **WARNING**–Keep ventilation openings, in both the freezer and the built-in structure, clear of obstruction.
- 2 **WARNING**–Do not touch the interior of the freezer with wet hands. This could result in frost bite.
- 3 **WARNING**–Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.
- 4 **WARNING**–Do not damage the refrigerant circuit.

- 5 **WARNING**—Do not damage the refrigerant tubing when handling, moving, or using the freezer.
- 6 **WARNING–DANGER**—Never allow children to play with, operate, or crawl inside the freezer.
Risk of child entrapment. Before you throw away your old freezer:
 - 1) Take off the doors
 - 2) Leave the shelves in place so that children may not easily climb inside
- 7 Unplug the freezer before carrying out user maintenance on it.
- 8 This freezer can be used by children age eight years and older and persons with reduced physical or mental capabilities or lack of experience and knowledge if they are given supervision or instruction concerning the use of the freezer in a safe way and understand the hazards involved. Children should not play with the freezer. Cleaning and maintenance should not be performed by children without supervision.
- 5 **WARNING**—Do not damage the refrigerant tubing when handling, moving, or using the freezer.
- 6 **WARNING–DANGER**—Never allow children to play with, operate, or crawl inside the freezer.
Risk of child entrapment. Before you throw away your old freezer:
 - 1) Take off the doors
 - 2) Leave the shelves in place so that children may not easily climb inside
- 7 Unplug the freezer before carrying out user maintenance on it.
- 8 This freezer can be used by children age eight years and older and persons with reduced physical or mental capabilities or lack of experience and knowledge if they are given supervision or instruction concerning the use of the freezer in a safe way and understand the hazards involved. Children should not play with the freezer. Cleaning and maintenance should not be performed by children without supervision.
- 9 If a component part is damaged, it must be replaced by the manufacturer, its service agent, or similar qualified persons in order to avoid a hazard.
- 10 Please dispose of the freezer according to local regulations as the freezer contains flammable gas and refrigerant.
- 11 Follow local regulations regarding disposal of the freezer due to flammable refrigerant and gas. All refrigeration products contain refrigerants, which under the guidelines of federal law must be removed before disposal. It is the consumer's responsibility to comply with federal and local regulations when disposing of this product.


- 12** This freezer is intended to be used in household and similar environments.
- 13** Do not store or use gasoline or any flammable liquids inside or in the vicinity of this freezer.
- 14** Do not use extension cords or ungrounded (two-prong) adapters with this freezer. If the power cord is too short, have a qualified electrician install an outlet near the freezer. Use of an extension cord can negatively affect the freezer's performance.

Grounding requirement

This freezer must be grounded. This freezer is equipped with a cord having a grounding wire with a grounding plug. The plug must be inserted into an outlet that is properly installed and grounded.

Improper use of the grounding plug can result in a risk of electric shock. Consult a qualified electrician or service person if the grounding instructions are not completely understood, or if doubt exists as to whether the freezer is properly grounded.

1.2 Safety instruction for refrigerant

⚠ WARNING  **Explosion Hazard.**


Keep flammable materials and vapors, such as gasoline, away from freezer. Failure to do so can result in fire, explosion, or death.

DANGER—Risk of Fire or Explosion. Flammable Refrigerant Used. To Be Repaired Only By Trained Service Personnel. Do Not Use Mechanical Devices. Do Not Puncture Refrigerant Tubing.

CAUTION—Risk of Fire or Explosion. Flammable Refrigerant Used. Consult Repair Manual/Owner's Guide Before Attempting To Service This Product. All Safety Precautions Must be Followed.


CAUTION—Risk of Fire or Explosion. Dispose of Properly In Accordance With Federal Or Local Regulations. Flammable Refrigerant Used.

CAUTION—Risk of Fire or Explosion Due To Puncture Of Refrigerant Tubing; Follow Handling Instructions Carefully. Flammable Refrigerant Used.



2. Description for product features

This product is provided with following features:



(The picture is only for reference, and specific appearance and configuration are subject to the real product)

- 1、 The back plate and the box inclined plate are made of iron, More durable, There is no drawer inside and turn over,the display space is large,easy to extract objects;
- 2、 versatility, optional different colors;
- 3、 Freezer chamber design is four star
- 4、 the big freezer design,can store more food

3.Installation and commissioning

3.1 Handling

- 1) Protect the refrigerator in moving it
Same as shown as left photo, please move it by hand cart with cushion
- 2) Remove all packing materials and bottom cushion, then move into house for placement
- 3) After moving it to appropriate location, wait for 2 hours before power on.



3.2 Disassembly (None)

The refrigerator door needs to be dismantled if it cannot enter the room in the whole.


3.3 Installation location

Location that is easy for ventilation shall be chosen to facilitate heat dissipation, enhance its performance and reduce the energy consumption.






3.4 Leveling of the refrigerator

If the refrigerator cannot be placed steadily, adjust the footing to level it.



3.5 Change the door opening direction

<p>1) Remove the right cover</p>	
<p>2) Remove the upper hinge screw</p>	
<p>3) Remove the right cover, and then remove the door</p>	

<p>4) Tilt or lie down the refrigerator (compressor is forbidden to contact with ground to prevent pipe break and refrigerant leakage), and remove the lower hinge and adjustable foot assembly, and install them after exchanging</p>	
<p>5) Remove the refrigerator door of the limit block to install them at the left side, and then install it</p>	
<p>6) Remove the left cover, install the upper hinge and right cover at the left side, the left cover will be installed on right</p>	

3.6 Installation of handle(None)

3.7 Installation of door lock(None)


3.8 Adjustment to level the door(None)

3.9 Adjustment to shelves(None)

4.Terms

4.1 Definition of model(None)

4.2 Location of nameplate




(The picture is only for reference, and specific appearance and configuration are subject to the real product)

5. Product specification

5.1 Typespecification(None)

5.2 Electrical parameters

Product Name		UR-BD160CM-DQ	/	/	/	/	
Product Code		22031010001661	/	/	/	/	
Name	Item	Type	Specification	Specificat ion	Specification	Specification	Specification
Compress or	Compressor	/	HYB60MHU42	/	/	/	/
	Starter	PTC	QP2-4R7/QP2-4. 7	/	/	/	/
	Overload protector	OLP	DRB24P61A1/ BT68-125	/	/	/	/
	Winding resistance of compressor wiring terminal		Rmc: 8.9±7% Ω Rsc: 10.2±7% Ω Rms=Rmc+Rsc	/	/	/	/
Motor	Fan motor of the freezing chamber	/	/	/	/	/	/
	Ventilation door of the refrigerating chamber	/	/	/	/	/	/
	Condensation fan	/	/	/	/	/	/
Lights inside the refrigerat or	Lights inside the freezing chamber	/	/	/	/	/	/
	Lights inside the refrigerating chamber	/	/	/	/	/	/
	Switch of the refrigerator door	/	/	/	/	/	/

5.3Refrigerating temperature


Temperature tolerance ≤ 2 °C

Compartment	The highest (°C)	Lowest (°C)
Freezing	-10	-21
Refrigerating	/	/
Variable temperature	/	/

5.4 Defrosting parts


Defrosting period	Initial defrosting period	Normal defrosting period
	/	/
Defrosting sensor	/	/
Defrosting temperature controller	/	/
Thermal fuse	/	/
Defrosting heater in freezing chamber	/	/

5.5 Circuit diagram



6. Internal view and dimension






6.1 Main parts and their names



(The picture is only for reference, and specific appearance and configuration are subject to the real product)

Freezer chamber	Refrigerator chamber
1.left/right cover 2.thermostate 3.Wire tube evaporator 4.Steel wire rack 5.adjustable foot assembly 6.hinge and adjustable foot assembly	None

6.2 External dimension


Front view	Side view
	
Down view	Open Door
	
Maximum open angle of door	
	

(The picture is only for reference, and specific appearance and configuration are subject to the real product)

7. Refrigerating piping system and circulating route of cooling air

7.1 Refrigerating piping system

Compressor---Right condenser---Right condenser---Left condenser---Dry filter---Capillary tube---F
 evaporator---Suction tube---Compressor




(The picture is only for reference, and specific appearance and configuration are subject to the real product)

7.2 Circulating route of cooling air (None)

8. Dismantling of parts

8.1 Parts on the door

Door seal	
<p>Door seal is installed into door liner groove.</p> <p>1) Open the refrigerator door;</p> <p>2) Take the door seal ① out of door liner;</p>	
Door tray	None
Guardrail	None

8.2 Light system(Nothing)

Light	None
Light switch	None
Pilot light	None
Fresh light	None




8.3 Air duct components refrigerating chamber

Air duct components refrigerating chamber	None
---	------

8.4 Air duct components in freezing chamber and fan motor


Disassembly and installation of Air duct	None
Fan motor of air duct	None

8.5 Evaporator and temperature sensing system

<p>Evaporator in freezing chamber Remove the buckle, cut down the tube and remove the evaporator</p>	
<p>Components on the evaporator</p>	
<p>Defrost thermostat</p>	<p>None</p>
<p>Fuse</p>	<p>None</p>
<p>Defrost sensor</p>	<p>None</p>
<p>Defrost heater</p>	<p>None</p>
<p>Evaporator in refrigerating chamber</p>	<p>None</p>
<p>Components on the evaporator</p>	<p>None</p>
<p>Sensor</p>	
<p>Sensor in freezing chamber</p>	<p>None</p>
<p>Sensor in refrigerating chamber</p>	<p>None</p>
<p>Sensor in Variable temperature chamber</p>	<p>None</p>
<p>ambient temperature senser</p>	<p>None</p>
<p>Thermostat</p>	
<p>1. Remove the cover 1) Remove the left/right cover</p>	
<p>2. Remove the screws 1) One screw outside</p>	


3. Remove Thermostat

- 1) Remove the ornament
- 2) Remove thermostat knob
- 3) Unclench the buckle by slotted screwdriver, remove Thermostat



8.6 Compressor case

Piping system in the compressor case



1.compressor
2. suction transition tube
3.right condenser

4.left condenser
5.anti-dew tupe assembly
6.dry filter

7. Harness connector box

Starter and protector of the compressor

1. Remove the screws



- 2) Two screws outside
- 3) One screw inside



2. Remove the clipping strip

Slowly pull it out



<p>3. Remove the protective cover 1 Pry the protective cover slowly from the upper part, 2 Pull it out and remove it.</p>	
<p>4. Remove the starter and protector Unplug the starter and protector (you can use a screwdriver to pry it slowly)</p>	
<p>5. The reverse process can complete installation.</p>	

8.7 Display and main control panel(None)

Display control board	None
Main control board	None

8.8 Bar counter(None)

Disassembly and installation of bar counter	None
Disassembly and installation bar doorseal	None

8.9 Water dispenser(None)

Disassembly and installation of water valve	None
Disassembly and installation of water tank	None

8.10 Ice maker(None)

Disassembly and installation of ice maker	None
Disassembly and installation of water system	None
Disassembly and installation ice machine sensor	None

9. Function and operation

9.1 Operation panel

Direct cooling mechanical refrigerator, through the thermostat knob to adjust the stalls.



9.2 Temperature control

Turn the temperature control knob to MAX, the internal temperature of the refrigerator becomes lower.

Turn the temperature control knob to MIN, the internal temperature of the refrigerator becomes higher.

NOTE: Please adjusting and using between "MAX" and "MIN"

9.3 Give an alarm(None)

9.4 Failure code and solutions(None)

9.5 Defrost function

Manual defrost

9.6 Compressor fan control(None)

9.7 Self-diagnosis (None)

10. Circuit description

10.1 Power Supply(None)

10.2 Test circuit for door switch(None)

10.3 Temperature test circuit(None)

10.4 Freezer chamber fan motor circuit (None)

10.5 refrigerating chamber fan motor circuit (None)


10.6 Condensation fan circuit (None)

10.7 Fan motor circuit of the ventilation door(None)

10.8 Resistance value of the sensor (R/T) (None)


11. Troubleshooting Method

11.1 Not cooling





11.2 Not working of compressor

No working of compressor



11.3 -Thermostat malfunction-Undercooling


Thermostat malfunction-Undercooling



A clockwise circle, rise 3°C

11.4 Light is not on(None)

11.5 Noise



12. Figures and details of repair parts(Documentsareprovidedseparately)

12.1 Figures

12.2 List of parts and components

13 Appendix:








13.1 Electrical Schematic Diagram(None)



(Model: ***)

13.2 Refrigerator maintenance tooling and equipment and material




Tooling




No.	Name	Photo	Main Usage

1	Phillips screwdriver		screw assemble and disassemble
2	slotted screwdriver/scrapper		screw and rivet assemble and disassemble
3	Socket spanner 5/16"		hinge and compressor screw assemble and disassemble
4	Sucker		display panel and air duct cover disassemble
5	Allen wrench (2.8~4mm)		handle assemble and disassemble
6	Vise grip pliers		sealing process tube
7	Pipe cutter		pipe cutting





8	Knife		assistive tool
9	Nipper pliers		assistive tool
10	Capillary tube scissors		Shear capillary


Equipment

No.	Name	Photo	Main Usage
1	Vacuum pump		vacuum pumping
2	Electronic scale		weighing refrigerant/gas
3	High pressure nitrogen with piezometer		pipe and cooling system(condenser, evaporator, etc) impurities clean

4	Soldering gun		heating and welding
5	Quick coupling		connection process pipeline, vacuum or charge refrigerant will be used.
6	hand leak detector		welding point leakage detect, if no, use soap-suds

material

No.	Name	Photo	Main Usage
1	Process pipeline		Charge the refrigerant
2	Dry filter		Involving a system failure to be replaced
3	Copper welding rod		tube welding
4	Refrigerant/gas		Add refrigerant to the system

5	Sealing tape		door fixing for reversible door option
---	--------------	---	--

Midea Refrigerators

If you need to get detailed technical information from the manufacturer, please contact:

xxx@midea.com

Refrigeration Division

Overseas Sales Company

Address: No. 176, Jinxiu Avenue, Economic-Technological Development Area, Hefei, Anhui,
China