



US009278742B2

(12) **United States Patent**
Young

(10) **Patent No.:** **US 9,278,742 B2**
(45) **Date of Patent:** **Mar. 8, 2016**

(54) **REBREATHER MOUTHPIECE**

(75) Inventor: **James Michael Young**, Fort Smith, AR (US)
(73) Assignee: **KISS Rebreather, LLC**, Fort Smith, AR (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 344 days.

(21) Appl. No.: **13/823,238**
(22) PCT Filed: **Oct. 7, 2011**
(86) PCT No.: **PCT/CA2011/050632**
§ 371 (c)(1),
(2), (4) Date: **Mar. 14, 2013**
(87) PCT Pub. No.: **WO2012/045178**
PCT Pub. Date: **Apr. 12, 2012**

(65) **Prior Publication Data**
US 2013/0186402 A1 Jul. 25, 2013
Related U.S. Application Data

(60) Provisional application No. 61/390,928, filed on Oct. 7, 2010.
(51) **Int. Cl.**
B63C 11/24 (2006.01)
A62B 9/06 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC . **B63C 11/24** (2013.01); **A62B 9/06** (2013.01);
B63C 11/186 (2013.01); **B63C 11/22** (2013.01)

(58) **Field of Classification Search**
CPC A61M 16/0045; A62B 9/06; B63C 11/14;
B63C 11/18; B63C 11/186; B63C 11/24;
Y10S 128/914; F16K 31/084
USPC 128/200.29, 201.27, 201.28, 204.19,
128/205.12, 205.17, 205.24, 914; 251/65;
137/625.48

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,651,051 A * 9/1953 Parks E03B 1/04
137/625.44
2,667,895 A * 2/1954 Pool F16K 15/06
137/528

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO2007/126317 A1 11/2007
WO WO2009/058080 A1 5/2009

OTHER PUBLICATIONS

Walden, Linda Lee, "Learning the Scuba Language: A Dictionary for New Divers", retrieved from <http://web.archive.org/web/20071014030320/http://www.dtmag.com/Stories/What%20About/01-06-feature.htm>—Oct. 14, 2007.*



(Continued)

Primary Examiner — Tan-Uyen (Jackie) T Ho
Assistant Examiner — Joseph D Boecker
(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **ABSTRACT**

A mouthpiece for a rebreather has a tubular housing having opposed inhale and exhale ends, a mouth port, and a discharge port. Supported for movement within a bore of the housing is a valve assembly which is magnetically biased toward a valve-closed position preventing air in an air space of the bore from moving to the exhale end and the discharge port. As a diver exhales into the mouth port, the increase in air pressure of the air space causes the valve assembly to assume a valve-open position, exposing a transverse channel extending between the air space and the discharge port, and a recirculation air channel extending between the air space and the exhale end. A portion of the exhaled air is exhausted to the ambient environment through the discharge port, while the remainder exits the mouthpiece at the exhale end for recirculation through the rebreather.

33 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
B63C 11/18 (2006.01)
B63C 11/22 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,788,019 A * 4/1957 Mottram F16K 15/18
 137/625.48
 3,669,109 A 6/1972 Cheffers et al.
 3,695,293 A * 10/1972 Zeuner F16K 11/10
 137/625.48
 3,721,238 A * 3/1973 Wise A61M 16/104
 128/205.24
 3,726,274 A * 4/1973 Bird A61M 16/00
 128/205.24
 4,022,201 A * 5/1977 Diggs B63C 11/24
 128/201.11
 4,683,914 A * 8/1987 Brisland F01L 15/08
 137/625.25
 4,809,691 A 3/1989 Paole et al.
 4,938,211 A 7/1990 Takahashi et al.
 5,036,841 A * 8/1991 Hamilton A62B 7/10
 128/202.26
 5,127,398 A * 7/1992 Stone A62B 9/02
 128/204.18
 5,368,018 A 11/1994 Stone
 5,429,124 A 7/1995 Yoshida et al.
 5,619,987 A * 4/1997 Matsuoka A62B 7/04
 128/204.26

5,690,099 A * 11/1997 Abramov A62B 19/02
 128/202.26
 5,720,279 A 2/1998 Furuichi et al.
 5,724,961 A 3/1998 Tistrand
 5,971,021 A * 10/1999 Graham B60T 7/206
 137/625.48
 6,796,307 B1 * 9/2004 Hughson A62B 7/14
 128/204.28
 7,089,939 B2 * 8/2006 Walker A61M 16/06
 128/205.24
 2006/0266359 A1 11/2006 Van Beurden et al.
 2008/0216836 A1 9/2008 Ottestad
 2009/0320847 A1 * 12/2009 Bozanic A62B 9/022
 128/205.24
 2010/0043797 A1 * 2/2010 Deas A62B 9/02
 128/205.24
 2011/0073111 A1 * 3/2011 Stone B63C 11/186
 128/205.24

OTHER PUBLICATIONS

Tagliati, Michel, "The Long (his)Story About Scrubbers & Sensors: From Fleuss to Evolution"; X-Ray Mag: 4: 2005, p. 82-87; retrieved from http://www.xray-mag.com/pdfs/articles/Tech_Rebreather_Intro_04.pdf.
 International Search Report and Written Opinion of PCT/CA2011/050632 mailed on Jan. 3, 2012, 9 pages.
 Webpage titled BMD SCR4: <www.therebreathersite.nl/10_Semiclosedrebreathers/bmd_scr4.htm>.

* cited by examiner




FIG. 1A

FIG. 1B




FIG. 1C




FIG. 1D








FIG. 1E






FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F

1

REBREATHER MOUTHPIECE

RELATED APPLICATIONS

This application claims the benefit of the priority of U.S. application No. 61/390,928 filed 7 Oct. 2010 and entitled REBREATHER MOUTHPIECE which is hereby incorporated herein by reference. For the purpose of the United States this application claims the benefit of the provisions of 35 USC §119(e) with respect to U.S. application No. 61/390,928.

TECHNICAL FIELD

This invention relates to rebreathers. Embodiments of the invention relate to a mouthpiece for rebreather systems. Embodiments of the invention have particular application to semi-closed circuit scuba diving rebreather systems.

BACKGROUND

Scuba diving breathing systems include open-circuit and rebreather systems. In open-circuit systems, all of the diver's exhaled air is exhausted to the ambient environment (e.g. typically, into the surrounding water). In rebreather systems, at least a portion of the diver's exhaled air is recaptured and is recycled through a breathing loop which typically includes an expandable/contractible counterlung and a carbon dioxide scrubber. Rebreather systems include one or more gas supplies, containing gas such as pure oxygen, a mixture of oxygen, nitrogen and/or helium (e.g. trimix or nitrox) and/or the like. Gas from the one or more gas supplies is injected into the breathing loop to replenish the air consumed and/or exhaled by the diver.

Rebreather systems may be provided as closed-circuit or semi-closed circuit systems. In closed-circuit systems, all of the diver's exhaled air is recaptured and recycled through the breathing loop. Closed-circuit systems typically supply a combination of pure oxygen and a diluent gas (e.g. air or trimix) to the breathing loop, and include oxygen monitoring systems to monitor and adjust oxygen levels to guard against oxygen toxicity. In semi-closed circuit systems, a portion of the diver's exhaled air is exhausted from the rebreather loop to the ambient environment (typically from a port in the breathing loop located on the diver's back) and the remainder is recaptured and recycled through the breathing loop. Semi-closed circuit systems typically supply gas mixtures (e.g. nitrox) to the breathing loop and do not require oxygen monitoring systems. Semi-closed circuit systems tend to involve fewer components and are generally lighter, more compact, and easier and safer to use and maintain than closed-circuit systems.

In rebreather systems, a diver exhales and inhales through a mouthpiece which directs an incoming supply of air from the breathing loop to the diver's mouth, and directs outgoing or exhaled air from the diver's mouth toward the breathing loop for recirculation through the breathing loop. In semi-closed circuit rebreather systems, a portion of the exhaled air is discharged or exhausted to the ambient environment, typically at an outlet in the breathing loop and away from the mouthpiece.

There is a need for a mouthpiece which may be used with semi-closed circuit rebreather systems. There is a need for a mouthpiece which exhausts a portion of the exhaled air to the ambient environment while directing the remainder of the exhaled air to the breathing loop.

SUMMARY

One aspect of the invention provides a mouthpiece for a rebreather having a breathing loop. The mouthpiece includes

2

a tubular housing having longitudinally opposed inhale and exhale ends. The inhale end is in fluid communication with an egress of a breathing loop and the exhale end is in fluid communication with an ingress of the breathing loop.

The mouthpiece has a mouth port through which a user inhales and exhales. The mouth port leads to a bore of the housing. The mouthpiece also has discharge and recirculation air channels having openings into the bore. The discharge air channel extends transversely through a body of the housing and leads to a discharge port in fluid communication with the ambient environment. The recirculation air channel extends longitudinally through the body of the housing and leads to the exhale end.

A moveable valve component is supported for movement in longitudinal directions within the bore and is shaped to define a portion of an air space within the bore between the moveable valve component and the inhale end. The moveable valve component is biased toward a valve-closed position in which the moveable valve component is spaced apart from the exhale end by a valve closed distance d_{max} ; and is located to block air flow into the openings of the discharge and recirculation air channels. An increase of air pressure in the air space tends to counteract the bias and move the moveable valve component toward a valve-open position in which the distance between the moveable valve component and the exhale end is less than the valve closed distance d_{max} and the openings of the discharge and recirculation air channels are exposed to permit air flow therethrough. The distance by which the moveable valve component moves toward the exhale end determines a length of the openings of the discharge and recirculation air channels exposed to permit air flow therethrough. The increase in air pressure is caused by the user exhaling through the mouth port and thereby introducing air into the air space.

The movement of the moveable valve component to the valve-open position causes an increase in the size of the air space and a corresponding reduction in air pressure. The valve-open position represents an equilibrium between forces caused by the air pressure and the bias.

The moveable valve component may be magnetically biased toward the valve-closed position. A first magnet may be disposed within the moveable valve component and a second magnet may be disposed at the exhale end. The first and second magnets are arranged with like poles facing each other.

The discharge air channel has a first width and the recirculation air channel has a second width which is larger than the first width. In particular embodiments, a number of discharge air channels, a number of recirculation air channels and the first and second widths are selected such that between approximately 20% to 30% of the exhaled air travels through the discharge air channel to the discharge port while the remainder of the exhaled air travels through the recirculation air channel to the exhale end.

In addition to the exemplary aspects and embodiments described above, further aspects and embodiments will become apparent by reference to the drawings and by study of the following detailed descriptions.

BRIEF DESCRIPTION OF DRAWINGS

Exemplary embodiments are illustrated in referenced figures of the drawings. It is intended that the embodiments and figures disclosed herein are to be considered illustrative rather than restrictive. In drawings which depict non-limiting embodiments of the invention:

FIGS. 1A and 1B are isometric views of an outer casing of a mouthpiece according to one embodiment.

FIGS. 1C through 1E are side elevation views of the casing shown in FIGS. 1A and 1B.

FIGS. 2A and 2B are cross-sectional views of a sleeve and a valve assembly of a mouthpiece according to one embodiment which may be housed within the casing shown in FIGS. 1A through 1E. The cross-sectional views of FIGS. 2A and 2B are taken along line A-A of FIG. 2C, and illustrate the valve in a closed position and an open position, respectively.

FIGS. 2C and 2D are end elevation views of the sleeve and valve assembly shown in FIGS. 2A and 2B.

FIGS. 3A and 3B are isometric views of the sleeve shown in FIGS. 2A through 2D.

FIGS. 3C through 3E are side elevation views of the sleeve shown in FIGS. 2A through 2D.

FIG. 3F is an end elevation view of the sleeve shown in FIGS. 2A through 2D.

DESCRIPTION

Throughout the following description, specific details are set forth in order to provide a more thorough understanding to persons skilled in the art. However, well known elements may not have been shown or described in detail to avoid unnecessarily obscuring the disclosure. Accordingly, the description and drawings are to be regarded in an illustrative, rather than a restrictive, sense.

Particular embodiments provide a mouthpiece for semi-closed circuit rebreather systems which may be used in scuba diving applications and/or for other applications suitable for semi-closed circuit rebreather systems. The mouthpiece includes a valve assembly for controlling the flow of air through the mouthpiece. The valve assembly is operable to direct some of the diver's exhaled air to the ambient environment (i.e. surrounding water) through a discharge port in the mouthpiece. The valve assembly is operable to direct the remainder of the diver's exhaled air to the breathing loop for recirculation through the breathing loop. Operation of the valve assembly is controlled by the diver's breathing.

According to particular embodiments, the mouthpiece comprises an outer casing 30 (see FIGS. 1A through 1E), a sleeve 10 housed within casing 30 (see FIGS. 3A through 3F) and a valve assembly 20 housed within sleeve 10 (see FIGS. 2A and 2B). In the illustrated embodiment, as seen in FIGS. 1A through 1E, casing 30 is a generally tubular piece having longitudinally opposed first open end 34 ("inhale end") and second open end 35 ("exhale end").

In the illustrated embodiment, portions of casing 30 which are proximate to opposed ends 34, 35 comprise circumferential grooves 31 on the outer surface of casing 30 (see FIGS. 1A and 1B). Such grooves 31 may be shaped for receiving corresponding O-rings, deformable clips and/or the like to facilitate attachment of the mouthpiece to hose attachments and inhale and exhale hoses (not shown). Inhale end 34 is couplable by way of a hose attachment to an inhale hose for carrying air to be inhaled by the diver from an egress of a breathing loop (not shown) to the mouthpiece. Exhale end 35 is couplable by way of a hose attachment to an exhale hose for carrying the diver's exhaled air away from the mouthpiece and to an ingress of the breathing loop.

Grooves 31 shown in FIGS. 1A and 1B are not mandatory. In other embodiments, other suitable attachment mechanisms may be used to attach exhale and inhale hoses of the breathing loop to the mouthpiece. By way of non-limiting example, such attachment mechanisms may include one or more of the following: hose clamps, circlips, threaded attachments, cir-

cumferential ridges, and/or the like. In other embodiments, other forms of conduits may be used to connect mouthpiece exhale end 35 to the ingress of the breathing loop and mouthpiece inhale end 34 to the egress of the breathing loop.

A check valve (not shown), such as a mushroom valve, another type of one-way valve and/or the like, may be positioned between inhale end 34 and the inhale hose to ensure that air at inhale end 34 flows in a direction indicated generally by arrow 14 of FIG. 1E, and not in the reverse direction. Valve assembly 20 housed within sleeve 10 operates to ensure that air exiting the mouthpiece at exhale end 35 flows in a direction indicated generally by arrow 15 of FIG. 1E, and not in the reverse direction. In some embodiments, a second check valve (not shown), such as a mushroom valve, another type of one-way valve and/or the like, may be positioned between exhale end 35 and the exhale hose to ensure that air at exhale end 35 flows in the direction indicated generally by arrow 15.

As best seen in FIGS. 1A, 1B and 1D, casing 30 comprises a mouth port 32 through which the user (e.g. a diver) inhales and exhales. Port 32 of the illustrated embodiment comprises outwardly extending, curved cylindrical walls 32A for receiving a pliable (e.g. elastomeric) mouth bit (not shown) such as those used for mouthpieces for conventional scuba regulators and/or the like. The mouth bit typically has a U-shaped extension shaped to be received within the diver's mouth.

Casing 30 of the illustrated embodiment also comprises one or more discharge ports 36 through which air within the mouthpiece may be exhausted or discharged to the ambient environment. In some embodiments, there are a plurality (e.g. two) of discharge ports 36. Each discharge port 36 may have one or more apertures 36A. Each discharge port 36 includes a one-way valve assembly (not shown) which permits air from the mouthpiece to escape through apertures 36A to the surrounding environment, but does not permit fluid (e.g. water) from the surrounding environment to enter the mouthpiece.

By way of non-limiting example, the one-way valve assembly at discharge port 36 may comprise a flexible diaphragm or flap covering apertures 36A and a rigid (or semi-rigid) disc positioned over the diaphragm to hold the diaphragm in place. The diaphragm may be made of latex rubber and the disc may be made of Delrin™, for example. The diaphragm deforms or otherwise lifts away from apertures 36A to allow air to escape through apertures 36A when the air pressure in the mouthpiece is above a threshold level. The diaphragm returns to a closed position covering apertures 36A once the air pressure in the mouthpiece drops below the threshold level. One or more screws may be inserted through the diaphragm and disc to secure the diaphragm and disc to casing 30. Other fasteners may be used to secure the diaphragm and disc to casing 30. In other embodiments, other forms of one-way valves may be used in combination with discharge ports 36 to permit air to escape from the mouthpiece while preventing the ingress of fluid (e.g. water) from the surrounding environment.

As seen in FIGS. 1B and 1C, casing 30 has a circumferentially elongated slot 37. Slot 37 is shaped for receiving a selector knob 51 (FIGS. 3D and 3E) extending from and attached to a sleeve 10 housed within casing 30. The diver may move selector knob 51 within slot 37 to rotate sleeve 10 between an "ON" position in which all ports of the mouthpiece are opened (e.g. such that aperture 46 through sleeve 10 is aligned with mouth port 32, and each discharge slot 41 through sleeve 10 is aligned with a corresponding discharge port 36), and an "OFF" position in which all ports of the mouthpiece are closed (e.g. aperture 46 and discharge slots 41 through sleeve 10 are sealed from the ambient environment as

they are misaligned with their corresponding ports **32**, **36** in outer casing **30**). Sleeve **10** may be rotated to the “ON” position when the mouthpiece is being used by the diver, and may be rotated to the “OFF” position when the mouthpiece is not being used by the diver.

In the illustrated embodiment, as best seen in FIGS. 3A and 3B, sleeve **10** is a generally tubular piece having a first open end **24** (“inhale end”) and a second open end **25** (“exhale end”). When sleeve **10** is inserted into casing **30**, inhale end **24** of sleeve **10** is generally aligned with inhale end **34** of casing **30**, and exhale end **25** of sleeve **10** is generally aligned with exhale end **35** of casing **30**.

FIGS. 2A and 2B illustrate a valve assembly **20** that may be housed within sleeve **10**. Sleeve **10** and valve assembly **20** together are housed within casing **30**. In the illustrated embodiment, when valve assembly **20** is inserted into sleeve **10**, valve assembly **20** may be located generally proximate to exhale end **25** of sleeve **10**. An air space or chamber **18** is defined within sleeve **10** between inhale end **24** of sleeve **10** and valve assembly **20**.

When the mouthpiece is in use (i.e. when selector knob **51** and sleeve **10** are rotated to the “ON” position), discharge ports **36** are aligned with corresponding discharge slots **41** in sleeve **10** (see FIGS. 2A, 2B, 2C and 3A). Mouth port **32** in casing **30** (FIG. 1A) is aligned with a corresponding aperture **46** in sleeve **10** (FIG. 3A). Mouth port **32** and aperture **46** are in fluid communication with air space **18** such that air exhaled by the diver into the mouthpiece (via mouth port **32**) moves into air space **18** (FIGS. 2A and 2B). Conversely, air inhaled by the diver moves out of air space **18**, through aperture **46** and mouth port **32**, and into the diver’s mouth. As explained below, the changes in air pressure in air space **18** resulting from the diver’s breathing cause the components of valve assembly **20** to move, thereby controlling the discharge of exhaled air from the mouthpiece at exhale end **25** and at discharge ports **36** (via discharge slots **41** in sleeve **10**).

Valve assembly **20** is operable to control the flow of air from air space **18** toward exhale end **25** and discharge slots **41**. When valve assembly **20** is in the valve-closed position (e.g. see FIG. 2A), valve assembly **20** prevents air in air space **18** from travelling toward exhale end **25** and discharge slots **41**. When valve assembly **20** is in a valve-open position (e.g. see FIG. 2B), valve assembly **20** permits air in air space **18** to travel toward exhale end **25** and discharge slots **41**.

As shown in FIGS. 2A and 2B, valve assembly **20** comprises valve components **22**, **23** which are moveable in relation to one another. Such valve components may comprise a moveable component **22** and a fixed component **23**. Valve components **22**, **23** may be generally cylindrical in shape. In the illustrated embodiment, moveable component **22** is supported for movement in longitudinal (e.g. axial) directions within a generally tubular inner sleeve wall **29**. Inner sleeve wall **29** may be integrally formed with, or connected to, sleeve **10**. Valve components **22**, **23** may have generally parallel (or otherwise complementary-shaped), facing surfaces **22A**, **23A**, respectively.

In the illustrated embodiment, fixed component **23** is fixed in position relative to sleeve **10**, and is positioned at or close to exhale end **25**. A plurality of screws **13** or other fasteners may be used to secure fixed component **23** to the walls of sleeve **10** at or near exhale end **25**. In other embodiments, fixed component **23** may be secured to sleeve **10** in some other manner (e.g. deformable connectors, clasps, suitable adhesives, welding and/or the like.). In still other embodiments, fixed component **23** may be integrally formed with sleeve **10**.

In the illustrated embodiment, moveable component **22** is slidable between: (a) a valve-closed position in which move-

able component **22** is separated from fixed component **23** at exhale end **25** by a maximum or valve closed distance d_{max} (FIG. 2A), and (b) a valve-open position in which moveable component **22** has moved toward fixed component **23** and the distance between valve components **22**, **23** is less than distance d_{max} . FIG. 2B shows valve assembly **20** in the maximum valve-open position in which moveable component **22** has moved toward fixed component **23** by a distance such that surface **22A** of moveable component **22** abuts surface **23A** of fixed component **23**.

When moveable component **22** is in the valve-closed position (FIG. 2A), moveable component **22** is constrained from moving toward inhale end **24** by a stop **16**. For example, stop **16** may comprise a ridge or other protrusion(s) extending from the inside surfaces of sleeve **10** for engaging with corresponding surfaces of moveable component **22**. Stop **16** and the corresponding surfaces of moveable component **22** may be shaped to be complementary to one another (i.e. for generally airtight engagement) such that when moveable component **22** is in the valve-closed position, air in air space **18** is prevented from moving toward exhale end **25** and toward discharge slots **41** (see FIG. 2A). In the illustrated embodiment, when valve assembly **20** is in the valve-closed position, air in air space **18** is blocked from moving into air channels **21**, **26** leading to discharge slots **41** and exhale end **25**, respectively.

In the illustrated embodiment, valve components **22**, **23** are biased apart—i.e. valve assembly **20** is biased to be in the valve-closed position shown in FIG. 2A in the absence of any counteracting forces. Valve components **22**, **23** may be magnetically biased apart as described in further detail below. As the diver exhales into the mouthpiece, the air pressure in air space **18** initially increases since the exhaled air is trapped within air space **18**. When the air pressure in air space **18** increases beyond a level sufficient to overcome the biasing forces that are holding valve components **22**, **23** apart in the valve-closed position, moveable component **22** moves toward fixed component **23**—i.e. valve assembly **20** is moved to a valve-open position. The movement of moveable component **22** toward fixed component **23** results in an increase in the size of air space **18** and a corresponding reduction in the air pressure in air space **18**. The valve-open position represents an equilibrium between forces caused by the air pressure and the bias.

Movement of moveable component **22** toward fixed component **23** opens up a new air space **19** within sleeve **10** previously occupied by moveable component **22** (e.g. see FIG. 2B). This can also be described as an enlargement of air space **18** to include the air space previously occupied by moveable component **22**. In the illustrated embodiment, air space **19** (or enlarged air space **18**) is in fluid communication with one or more longitudinal (recirculation) air channels **26** extending longitudinally between air space **18** and exhale end **25**. In the illustrated embodiment, air space **19** (or enlarged air space **18**) is also in fluid communication with one or more discharge air channels **21**. Each discharge air channel **21** may extend transversely to a corresponding discharge slot **41** at the outer surface or walls of sleeve **10**. In the illustrated embodiment (see FIG. 2C), each discharge air channel **21** extends radially to a corresponding discharge slot **41**. Openings may be defined in inner sleeve wall **29** to permit air to travel from air space **19** to channels **21** and **26**.

As seen in FIG. 2B, during an exhale breath, moveable component **22** moves toward fixed component **23** by a distance which determines a length l of air channels **21**, **26** that is exposed to air space **19**. Length l varies according to the diver’s breathing (e.g. a relatively strong exhale breath tends

to cause moveable component **22** to move toward fixed component **23** by a greater distance, thereby causing a relatively long length *l* of exposed air channels **21**, **26**).

Once moveable component **22** has moved toward fixed component **23** (i.e. away from the valve-closed position and into a valve-open position), the diver's exhaled air which was previously trapped in air space **18** is able to move into new air space **19**, and into air channels **21** and **26**. As indicated in FIG. **2B**, a portion of the air travelling through the mouthpiece may take the flow path indicated by arrow **13A**, travelling through the one or more recirculation air channels **26** before exiting the mouthpiece at exhale end **25**, after which it is recirculated through the breathing loop. Another portion of the air travelling through the mouthpiece may take the flow path indicated by arrow **13B**, travelling through the one or more discharge air channels **21** before exiting the mouthpiece at discharge slot **41** (and discharge port **36**). Air exiting through discharge slot **41** is exhausted to the ambient environment.

In the illustrated embodiment, as best seen in FIG. **2C**, sleeve **10** has three recirculation air channels **26** each extending to exhale end **25**, and two discharge air channels **21** each extending to a corresponding discharge slot **41**. Each discharge slot **41** may be located in a corresponding recessed portion **40** of sleeve **10**. Recessed portion **40** provides an air space between discharge slot **41** and the one-way valve assembly at discharge port **36** (see FIG. **1B**).

In the illustrated embodiment, the three recirculation air channels **26** are evenly circumferentially spaced apart. Each of the two discharge air channels **21** extends transversely between two adjacent recirculation air channels **26**. Other configurations and shapes of air channels **21**, **26** are possible. For example, a different number and/or arrangement of air channels **21**, **26** may be provided than as shown in the illustrated embodiment.

As seen in FIG. **2C**, the circumferential width w_1 of each discharge air channel **21** is smaller than the circumferential width w_2 of each recirculation air channel **26**. The relative proportion of air travelling through channels **21**, **26** may be determined at least in part by the minimum cross-sectional areas in the flow paths between air spaces **18**, **19** and channels **21**, **26**. In the illustrated embodiment these cross-sectional areas are defined at least approximately by the circumferential widths w_1 , w_2 of air channels **21**, **26** at the interface between air space **19** and air channels **21**, **26**, and a length *l* of air channels **21**, **26** that is directly exposed to air space **19** (i.e. not covered by moveable component **22**) as a result of movement of moveable component **22** toward fixed component **23** (see FIG. **2B**).

In particular embodiments, the magnitude of the biasing forces acting on valve components **22**, **23** is such that when a diver exhales into the mouthpiece under typical operating conditions (for example, use at a depth of up to 100 feet), moveable component **22** typically moves toward fixed component **23** by a distance which is between 30% to 80% of d_{max} . In such embodiments, during the exhale breath, moveable component **22** rarely moves completely to the maximum valve-open position in which moveable component **22** abuts fixed component **23**, as seen in FIG. **2B**.

A decrease in air pressure in air space **18** to a level such that the force on moveable component **22** is less than the current bias force may result in moveable component **22** moving back toward inhale end **24** until moveable component **22** reaches either a new equilibrium position or the valve-closed position shown in FIG. **2A**. The air pressure in air space **18** may be decreased as a result of: moveable component **22** moving toward fixed component **23** (thereby resulting in a corresponding expansion to air space **18**), the diver inhaling

(thereby removing air from air space **18**), the diver ceasing to exhale or decreasing the strength of the exhale breath and/or air exiting space **18** via air channels **21**, **26**.

In particular embodiments, valve components **22**, **23** are magnetically biased apart—i.e. toward the valve-closed position shown in FIG. **2A**. In the illustrated embodiment, a plurality of magnets **12A**, **12B** are embedded within valve components **22**, **23**, respectively (see FIGS. **2A** and **2B**). Due to space constraints within sleeve **10**, fixed component **23** may include a cylindrical extension **27**, which may extend into the exhale hose, for accommodating magnets **12B**. Magnets **12A**, **12B** are arranged with their similar poles facing one another (i.e. magnets **12A** are arranged so as to repel magnets **12B**), resulting in biasing forces which keep valve components **22**, **23** apart in the valve-closed position, in the absence of any counteracting forces.

The rate of air being exhaled by the diver (i.e. volume of exhaled air entering the mouthpiece per time unit) determines the pressure in air spaces **18**, **19** and the corresponding distance by which moveable component **22** moves toward fixed component **23**. For higher rates of exhaled air, moveable component **22** moves by a correspondingly larger distance toward fixed component **23**, thereby increasing the exposed length *l* of air channels **21**, **26** and allowing air in air spaces **18** and **19** to flow into channels **21**, **26** at a higher rate. However, as the relative (i.e. ratio of) minimum cross-sectional areas in the flow paths between air spaces **18**, **19** and channels **21**, **26** remains generally constant, the relative proportion of air travelling through channels **21**, **26** also remains generally constant. Therefore, the proportion of the exhaled air that is exhausted to the ambient environment through discharge slots **41** relative to a total amount of exhaled air remains generally constant during operation.

For a given configuration of recirculation air channels **26** (e.g. number, volume and circumferential width w_2 of channels **26**, etc.), a larger the number and/or circumferential width w_1 of discharge air channels **21**, the greater the proportion of exhaled air that is exhausted to the ambient environment. In particular embodiments, the number and dimension(s) (e.g. circumferential width(s) w_2) of recirculation air channels **26** and the number and dimension(s) (e.g. circumferential width(s) w_1) of discharge air channels **21** are selected such that between approximately 20% to 30% of exhaled air is exhausted to the ambient environment through discharge air channels **21** and discharge slots **41**, and the remainder (i.e. between approximately 70% to 80%) of the exhaled air travels through recirculation air channels **26** and exits the mouthpiece at exhale end **25**, where it is recaptured for recirculation through the breathing loop.

A total amount of air that exhausted through both recirculation air channels **26** and discharge air channels **21** may be proportional to (or correlated with) the number of recirculation air channels **26** and discharge air channels **21** multiplied by their corresponding widths according to:

$$\text{total amount exhausted} \propto (\# \text{ of recirculation channels}) w_2 + (\# \text{ of discharge channels}) w_1$$

Accordingly, the proportion of air that is exhausted to the ambient environment through discharge air channels **21** relative to the amount of total amount of exhausted air through both discharge air channels **21** and recirculation air channels **26** may be proportional to (or correlated with) the ratio of the

number of discharge air channels **21** multiplied by their corresponding widths divided by the total amount of exhausted air according to:

$$\text{proportion discharged} = \frac{(\# \text{ of discharge channels})w_1}{(\# \text{ of recirculation channels})w_2 + (\# \text{ of discharge channels})w_1}$$

In some embodiments, various discharge air channels **21** and/or various recirculation air channels **26** may be provided with different widths, in which case the foregoing equations may be adjusted accordingly.

The number and dimension(s) (e.g. circumferential width(s) w_2) of recirculation air channels **26** and the number and dimension(s) (e.g. circumferential width(s) w_1) of discharge air channels **21** may vary between different embodiments rated for different skill levels, depths, dive duration, etc. For example, for recreational diving (e.g. at depths of up to 100 feet) it may be desirable to adjust one or more of these parameters such that approximately 30% of the exhaled air is exhausted to the ambient environment. For deeper or more technical diving, it may be desirable to adjust one or more of these parameters such that approximately 20% of the exhaled air is exhausted to the ambient environment. In particular embodiments, where there are two discharge air channels **21** and three recirculation air channels **26**, the ratio between circumferential widths w_1 and w_2 may be less than 0.15. In certain embodiments such ratio may be less than 0.10 and above 0.05.

It may be desirable to configure valve assembly **20** such that the air pressure needed to overcome the biasing forces (and other forces such as friction) holding valve components **22**, **23** apart in the valve-closed position is sufficiently low, so that during each typical exhale breath, moveable component **22** moves toward fixed component **23** (i.e. valve assembly **20** is moved to a valve-open position) thereby allowing exhaled air to exit at exhale end **25** and discharge ports **36**. Otherwise, if valve assembly **20** were to remain in the valve-closed position during an exhale breath, the exhaled air would remain trapped within air space **18** and could be subsequently inhaled by the diver.

In the illustrated embodiment (see FIGS. **2A** and **2B**), hollow spaces **17** may be formed within moveable component **22** to reduce the component's weight. This in turn may reduce friction between the outer surfaces of moveable component **22** and inner sleeve wall **29** and may help to facilitate movement of moveable component **22** relative to fixed component **23**.

As described above, by sliding selector knob **51** of sleeve **10** within slot **37** of casing **30**, sleeve **10** may be rotated between an "ON" position in which all ports of the mouthpiece are opened, and an "OFF" position in which all ports of the mouthpiece are closed. As best seen in FIG. **3E**, selector knob **51** may be surrounded by a groove **42A** for receiving a suitably-shaped ring seal for preventing water from entering through slot **37** of casing **30**.

Once the diver has rotated sleeve **10** to the "OFF" position, the diver may remove the mouth bit from his or her mouth. If the mouthpiece is kept immersed in water, the space circumscribed by the curved walls of mouth port **32** fills with water but the water is prevented from entering the mouthpiece given that openings into the mouthpiece (including aperture **46** and discharge slots **41**) are sealed from the ambient environment in the "OFF" position. If the diver wishes to begin using the mouthpiece while the mouthpiece is immersed in water, the diver can blow into mouth port **32** while sleeve **10** remains in the "OFF" position. In such "OFF" position, mouth port **32** is aligned with slot **47** of sleeve **10** (see FIG. **3C**) and slot **47** is

in fluid communication with aperture **38** of casing **30** (see FIG. **1E**). By blowing into mouth port **32**, water which has been trapped within mouth port **32** can be expelled through slot **47** and aperture **38** into the ambient environment. A one-way valve may cover aperture **38** to prevent water from entering the mouthpiece through aperture **38**. After the water has been cleared from mouth port **32** in this manner, the diver may rotate sleeve **10** to the "ON" position and the diver may begin exhaling and inhaling through mouth port **32** which is now aligned with aperture **46** of sleeve **10**.

In some embodiments, one or more grooves may be provided in sleeve **10** at locations such that when sleeve **10** has been rotated to the "OFF" position, the grooves are aligned with discharge ports **36** of casing **30**. Such grooves may receive corresponding ring seals (e.g. O-ring seals) for preventing gas from leaking through discharge ports **36** during positive pressure testing conducted on the mouthpiece when sleeve **10** has been rotated to the "OFF" position.

The illustrated embodiment contains a sleeve **10** within an outer casing **30**. As described above, sleeve **10** may be rotated to switch the mouthpiece between "ON" and "OFF" positions. In other embodiments, sleeve **10** is omitted. In such embodiments, outer casing **30** is adapted to include the structural features of sleeve **10** which support the operation of valve assembly **20**, such as, for example:

- inner walls **29** for supporting movement of moveable component **22** within a bore of casing **30**;
- stop **16** for limiting the movement of moveable component **22** toward inhale end **24**;
- one or more discharge air channels **21** extending transversely through casing **30** for carrying exhaled air toward discharge slot **41**;
- one or more recirculation air channels **26** extending longitudinally through casing **30** for carrying exhaled air toward exhale end **25**; and
- recessed portion **40** providing an air space between discharge slot **41** and the one-way valve assembly at discharge port **36**;

as described above with reference to sleeve **10**.

In the illustrated embodiment, two valve components **22**, **23** are used. Magnets are housed within each of the valve components. In other embodiments, fixed component **23** is omitted, and magnets are disposed within or on portions of sleeve **10** (or casing **30**) proximate to or at exhale end **25**. Such magnets are arranged so as to repel the other magnets disposed within moveable component **22**. In such embodiments, moveable component **22** is magnetically biased apart from the magnets positioned near exhale end **25**.

The embodiments described herein are only examples. As will be apparent to those skilled in the art in the light of the foregoing disclosure, many alterations and modifications are possible in the practice of this invention without departing from the spirit or scope thereof. For example:

- A mouthpiece as described herein is not limited to use in underwater environments. The mouthpiece may be used for semi-closed circuit rebreather systems in other applications and environments where a gas is supplied for inhalation by the user, such as, for example, outer space, mining, mountaineering, submarines, and the like.

The illustrated embodiment is generally tubular in shape. However, this is not mandatory. In other embodiments, the mouthpiece (including casing **30** and sleeve **10**) may have a non-tubular or non-cylindrical shape (i.e. a shape having a non-circular cross-section). Moveable valve component **22** may be shaped and supported for movement within non-tubular or non-cylindrical walls.

11

Other biasing mechanisms may be used for valve assembly 20, such as, for example, spring or coil biasing mechanisms.

For brevity, this description and the accompanying claims refer to fluids exhaled into the mouthpiece, inhaled from the mouthpiece, discharging from the mouthpiece, ingressing into the breathing loop, egressing from the breathing loop and/or the like as "air". It will be understood by those skilled in the art that such fluids are not limited to "air" in the conventional sense and may include other fluids (e.g. gases and gases mixed liquids), mixtures of fluids and/or the like. It will be understood further that.

Other example embodiments may be obtained, without limitation, by combining features of the disclosed embodiments.

Accordingly, this invention should be interpreted in accordance with the following claims.

What is claimed is:

1. A mouthpiece for a rebreather having a breathing loop for treating exhaled breath and making the exhaled breath suitable for re-inhalation, the mouthpiece comprising:

a tubular housing comprising:

longitudinally opposed inhale and exhale ends, the inhale end in fluid communication with an egress of the breathing loop and the exhale end in fluid communication with an ingress of the breathing loop;

a mouth port through which a user inhales and exhales, the mouth port leading to a bore of the housing;

a discharge air channel having an opening into the bore, the discharge air channel extending transversely through a body of the housing and leading to a discharge port in fluid communication with an ambient environment;

a recirculation air channel having an opening into the bore, the recirculation air channel extending longitudinally through the body of the housing and leading to the exhale end; and

a moveable valve component supported for movement in longitudinal directions within the bore and shaped to define a portion of an air space within the bore between the moveable valve component and the inhale end, the moveable valve component biased toward a valve-closed position wherein the moveable valve component is spaced apart from the exhale end by a valve closed distance d_{max} and is located to block air flow into the openings of the discharge and recirculation air channels; wherein an increase of air pressure in the air space tends to counteract the bias and move the moveable valve component toward a valve-open position wherein the distance between the moveable valve component and the exhale end is less than the valve closed distance d_{max} and the openings of the discharge and recirculation air channels are exposed to permit air flow there-through, wherein the increase in air pressure is caused by the user exhaling through the mouth port and thereby introducing air into the air space.

2. A mouthpiece according to claim 1 wherein the movement of the moveable valve component to the valve-open position causes an increase in the size of the air space and a corresponding reduction in air pressure, the valve-open position representing an equilibrium between forces caused by the air pressure and the bias.

3. A mouthpiece according to claim 1 wherein the moveable valve component is magnetically biased toward the valve-closed position.

4. A mouthpiece according to claim 1 comprising a first magnet disposed within the moveable valve component and a second magnet disposed at the exhale end, wherein the first

12

and second magnets are arranged with like poles facing each other to magnetically bias the moveable valve component toward the valve-closed position.

5. A mouthpiece according to claim 4 comprising a fixed valve component proximate to the exhale end, wherein the second magnet is disposed within the fixed valve component.

6. A mouthpiece according to claim 4 wherein at least a portion of the second magnet is located outside of the bore of the housing.

7. A mouthpiece according to claim 1 wherein the discharge port comprises an aperture and a one-way valve assembly.

8. A mouthpiece according to claim 7 wherein the one-way valve assembly comprises a flexible diaphragm covering the aperture.

9. A mouthpiece according to claim 8 wherein the one-way valve assembly comprises a rigid disc positioned over the diaphragm.

10. A mouthpiece according to claim 1 wherein the housing comprises an outer tubular casing and an inner tubular sleeve disposed within the casing and rotatable about a longitudinal axis of the housing, wherein the bore is formed within the sleeve.

11. A mouthpiece according to claim 10 wherein the mouth port and the discharge port are formed in the casing, and the mouth port and the discharge port are alignable with corresponding openings in the sleeve.

12. A mouthpiece according to claim 11 wherein the sleeve comprises a selector knob extending through a corresponding selector aperture in the casing, the sleeve being rotatable about the longitudinal axis of the housing by movement of the selector knob within the selector aperture.

13. A mouthpiece according to claim 1 wherein there are three recirculation air channels, and two discharge air channels each leading to a corresponding discharge port in fluid communication with the ambient environment.

14. A mouthpiece for a rebreather having a breathing loop for treating exhaled breath and making the exhaled breath suitable for re-inhalation, the mouthpiece comprising:

a tubular housing comprising:

longitudinally opposed inhale and exhale ends, the inhale end in fluid communication with an egress of the breathing loop and the exhale end in fluid communication with an ingress of the breathing loop;

a mouth port through which a user inhales and exhales, the mouth port leading to a bore of the housing;

a discharge air channel having an opening into the bore, the discharge air channel extending transversely through a body of the housing and leading to a discharge port in fluid communication with an ambient environment;

a recirculation air channel having an opening into the bore, the recirculation air channel extending longitudinally through the body of the housing and leading to the exhale end; and

a moveable valve component supported for movement in longitudinal directions within the bore and shaped to define a portion of an air space within the bore between the moveable valve component and the inhale end, the moveable valve component biased toward a valve-closed position wherein the moveable valve component is spaced apart from the exhale end by a valve closed distance d_{max} and is located to block air flow into the openings of the discharge and recirculation air channels; wherein an increase of air pressure in the air space tends to counteract the bias and move the moveable valve component toward a valve-open position wherein the distance between the moveable valve component and

13

the exhale end is less than the valve closed distance d_{max} and the openings of the discharge and recirculation air channels are exposed to permit air flow there-through, wherein a distance by which the moveable valve component moves from the valve closed position toward the exhale end determines a length P of the openings of the discharge and recirculation air channels exposed to permit air flow therethrough.

15. A mouthpiece according to claim 14 wherein the discharge air channel has a first width w_1 and the recirculation air channel has a second width w_2 which is greater than the first width w_1 .

16. A mouthpiece according to claim 15 wherein a ratio between the first and second widths is such that between approximately 20% to 30% of the exhaled air travels through the discharge air channel to the discharge port while the remainder of the exhaled air travels through the recirculation air channel to the exhale end.

17. A mouthpiece for a rebreather having a breathing loop for treating exhaled breath and making the exhaled breath suitable for re-inhalation, the mouthpiece comprising:

a housing comprising an inhale end in fluid communication with an egress of the breathing loop and an exhale end in fluid communication with an ingress of the breathing loop;

a valve located within the housing, the valve comprising a moveable valve component positionable between a valve-closed position wherein the valve confines air in an interior bore of the housing and a valve-open position wherein the valve permits air flow out of the bore through a recirculation air channel to the exhale end and through a discharge air channel to an ambient environment;

wherein the moveable valve component is magnetically biased toward the valve closed position;

wherein the housing is tubular, the bore is located on an interior of the tubular housing and inhale and exhale ends are located at longitudinally opposed ends of the tubular housing; and

wherein the moveable valve component is shaped to occupy substantially an entirety of a cross-section of the bore.

18. A mouthpiece according to claim 17 comprising a first magnet disposed within the moveable valve component and a second magnet disposed at the exhale end, wherein the first and second magnets are arranged with like poles facing each other to magnetically bias the moveable valve component toward the valve-closed position.

19. A mouthpiece according to claim 18 comprising a fixed valve component proximate to the exhale end, wherein the second magnet is disposed within the fixed valve component.

20. A mouthpiece according to claim 18 wherein at least a portion of the second magnet is located outside of the bore of the housing.

21. A mouthpiece according to claim 17 wherein the housing comprises an outer tubular casing and an inner tubular sleeve disposed within the casing, the inner tubular sleeve rotatable about a longitudinal axis of the housing and the bore formed within the sleeve.

22. A mouthpiece according to claim 21 wherein the casing comprises a discharge port and a mouth port, wherein the mouth port and the discharge port are respectively alignable with a corresponding mouth opening and the discharge air channel through the sleeve.

23. A mouthpiece according to claim 22 wherein the sleeve comprises a selector knob extending through a corresponding selector aperture in the casing, the sleeve being rotatable

14

about the longitudinal axis of the housing by movement of the selector knob within the selector aperture.

24. A mouthpiece for a rebreather having a breathing loop for treating exhaled breath and making the exhaled breath suitable for re-inhalation, the mouthpiece comprising:

a tubular housing comprising:

longitudinally opposed inhale and exhale ends at axial ends of the tubular housing, the inhale end in fluid communication with an egress of the breathing loop and the exhale end in fluid communication with an ingress of the breathing loop;

a mouth port located between the longitudinally opposed inhale and exhale ends through which a user inhales and exhales, the mouth port leading to a bore of the housing;

a discharge air channel having an opening into the bore, the discharge air channel leading to a discharge port in fluid communication with an ambient environment;

a recirculation air channel having an opening into the bore, the recirculation air channel leading to the exhale end; and

a moveable valve component supported for movement in longitudinal directions within the bore and shaped to occupy substantially an entirety of a transverse cross-section of the bore and to thereby define a portion of an air space within the bore between the moveable valve component and the inhale end;

wherein the mouth port leads to the air space within the bore.

25. A mouthpiece according to claim 24 wherein the moveable valve component is positionable between a valve-closed position wherein the valve confines air in the air space and a valve-open position wherein the valve permits air flow out of the bore through the recirculation air channel to the exhale end and through the discharge air channel to the ambient environment.

26. A mouthpiece according to claim 25 wherein the moveable valve component is magnetically biased toward the valve closed position.

27. A mouthpiece according to claim 26 comprising a first magnet disposed within the moveable valve component and a second magnet disposed at the exhale end, wherein the first and second magnets are arranged with like poles facing each other to magnetically bias the moveable valve component toward the valve-closed position.

28. A mouthpiece according to claim 27 comprising a fixed valve component proximate to the exhale end, wherein the second magnet is disposed within the fixed valve component.

29. A mouthpiece according to claim 27 wherein at least a portion of the second magnet is located outside of the bore of the housing.

30. A mouthpiece according to claim 24 wherein the housing comprises an outer tubular casing and an inner tubular sleeve disposed within the casing, the inner tubular sleeve rotatable about a longitudinal axis of the housing and the bore formed within the sleeve.

31. A mouthpiece according to claim 30 wherein the discharge port and the mouth port are in the casing and are respectively alignable with a corresponding mouth opening and the discharge air channel through the sleeve.

32. A mouthpiece according to claim 31 wherein the sleeve comprises a selector knob extending through a corresponding selector aperture in the casing, the sleeve being rotatable about the longitudinal axis of the housing by movement of the selector knob within the selector aperture.

33. A method for controlling air flow in a rebreathing system comprising a mouthpiece and a rebreather having a

breathing loop for treating exhaled breath and making the exhaled breath suitable for re-inhalation, the method comprising:

providing a housing comprising an inhale end in fluid communication with an egress of the breathing loop and an exhale end in fluid communication with an ingress of the breathing loop;

providing a valve located within the housing, the valve comprising a moveable valve component positionable between a valve-closed position wherein the valve confines air in an interior bore of the housing and a valve-open position wherein the valve permits air flow out of the bore through a recirculation air channel to the exhale end and through a discharge air channel to an ambient environment;

magnetically biasing the moveable valve component toward the valve closed position;

upon receiving an exhalation of breath into an air space located in the bore of the housing, permitting the moveable valve component to move from the valve-closed position to the valve-open position.

* * * * *