


(12) UK Patent Application (19) GB (11) 2 039 755 A

- (21) Application No **7933310**
- (22) Date of filing **26 Sep 1979**
- (30) Priority data
- (31) **5142U**
- (32) **22 Jan 1979**
- (33) **United States of America (US)**
- (43) Application published **20 Aug 1980**
- (51) **INT CL³**
A63B 65/02
- (52) Domestic classification
A6S 26E5A1C 26E5A1E 26E5A2A
- (56) Documents cited
GB 1541886
GB 504676
GB 469863
- (58) Field of search
A6S
- (71) Applicant
Walter E. Bottelsen, 309 Felicia Drive, Santa Maria, California 93454, United States of America
- (72) Inventor
Walter E. Bottelsen
- (74) Agents
Marks & Clerk

(54) **A dart**

(57) A dart has an elongate body (20) with a point (21) sliding in one end of the body and a tail (22) carried at the other end of the body. The point is normally in an extended position. On

impact with a target, the momentum of the body causes the point to slide in the body to a position where the body impacts the head of the point and hammers the point into the target thereby reducing the likelihood of bounce of the dart.



GB 2 039 755 A

FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.




FIG. 10.





FIG. 11.



SPECIFICATION

A dart

This invention relates to darts.

In a dart game, the dart is shot or thrown to a target marked on a dart board. Typically the scoring areas are outlined by a wire grid on the face of the target. When a dart point strikes a wire, the dart is deflected and often does not stick in the target, that is, the dart bounces back and lands on the floor. When this occurs, the dart player scores no points and the darts often are damaged or the point is dulled by hitting the floor.

Accordingly, it is an object of the present invention to provide a dart which substantially reduces the likelihood of bouncing of the dart on impact with a target or an obstruction.

The invention provides a dart comprising an elongate body having at one end, means defining an interior cavity of larger cross-section area and an axial passage of smaller cross-section area, and at the other end, means for mounting a tail; a point with a head positioned in said cavity and a shaft slidable in said passage for moving said head between a first position with said head remote from the bottom of said cavity and a second position with said head engaging said cavity bottom; said point and body including interengaging means resisting movement of said head from said first to said second position.

Preferably, said interengaging means is disposed about substantially the entire periphery of said head and cavity.

It is thus possible to provide a dart wherein the point moves with respect to the body, with the body providing a hammering action on the point when the point impacts the target or an obstruction, so as to drive the dart point forward into the target. It is further possible to provide such a dart wherein the interengagement between the point and body is uniform and symmetrical and provides for movement of the point head from a first extended position to a second hammering position without affecting the balance or accuracy of the dart. It is yet further possible to provide such a dart construction which is rugged and durable and have a life corresponding to that of the ordinary dart.

The invention will now be more particularly described, by way of example with reference to the accompanying drawings, wherein:—

Figure 1 is a perspective view of a dart incorporating the presently preferred embodiment of the invention;

Figure 2 is an enlarged partial sectional view of the dart of Figure 1;

Figure 3 is an enlarged sectional view of the insert of Figure 2;

Figure 4 is an enlarged sectional view taken along the line 4—4 of Figure 2;

Figure 5 is a view similar to that of Figure 2 showing impact of the dart with a target;

Figures 6, 7 and 8 are views similar to that of Figure 2 showing alternative embodiments;

Figure 9 is an enlarged sectional view taken

65 along the line 9—9 of Figure 8;

Figure 10 is a view similar to that of Figure 2 showing another alternative embodiment; and

Figure 11 is an enlarged sectional view taken along the line 11—11 of Figure 10.

Referring initially to Figures 1—5, the dart shown therein includes a body 20, a point 21, and a tail assembly 22. Typically, the body 20 is a metal cylinder with a threaded opening 24 at one end for receiving a threaded boss 25 of a tail assembly 22.

A cavity 28 is provided at the other end of the body 20 and is closed by an insert 29 having a passage 30 therethrough for sliding of the shaft 31 of the point 21. The insert 29 may be a press fit into the body 20 or may be secured by cementing or otherwise as desired.

The insert 29 has four resilient fingers 33 which project into the cavity 28, with the tips of the fingers turned inwardly. An enlarged head 34 of the point 21 is normally positioned within the fingers 33, as shown in Figure 2.

The dart with the point in the extended position as shown in Figure 2 is ready for use. When the thrown dart strikes a target 35 or an obstruction, the momentum of the body 20 causes the body to move forward relative to the point, causing the head 34 to expand the fingers 33 and move from the throwing position of Figure 2 to the impact position of Figure 5, with the body 20 impacting the head 34 and driving the point 21 forward. This hammering action obtained when the head moves through the insert and engages the body functions to fix the dart in the target and prevent bouncing. Preferably, the head 34 is tapered for ease of movement past the fingers 33. The fingers surround the head in the throwing position and engage the head on all sides at impact.

An alternative construction is shown in Figure 6, wherein components corresponding to those of Figures 1-5 are identified by the same reference numerals. A groove 40 is provided in the inner wall of the cavity 28 of the body 20. A plurality of resilient fingers 41 are carried on the inner end of the point 21, with the fingers projecting outwardly into the groove 40. The dart is shown in the throwing position in Figure 6. On engagement with a target, the body 20 moves to the right, moving the fingers 41 inwardly out of the groove 40, with the head 42 of the point impacting the bottom 43 of the cavity to provide the hammering action.

In the embodiment of Figure 7, a coil spring 45 is carried on the head 34 of the point 21, typically by having the ends of the spring bent at right angles and inserted in openings in the head. The spring is designed so that it will be slightly compressed when inserted in the cavity 28 of the body 20, providing a resilient frictional engagement between the spring and the body. In use, the pin is pulled out to the throwing position of Figure 7. When impacting a target, the body 20 moves forward and impacts the head, driving the point into the target.

In the embodiment of Figure 8, a U-shaped

spring clip 48 is carried on the insert 49, engaging the head 34 and providing sliding friction as the head moves in the clip, (normally retaining the point head in the throwing position). The dart operates in the same manner as previously described.

In the embodiment of Figures 10 and 11, a sleeve 51 is mounted in the cavity of the body 20, with the point 21 sliding in the insert 49 and with the head 34 positioned within the sleeve. A plurality of resilient spines 53 are carried within the sleeve 51, projecting inwardly, as shown in Figure 11. The spines preferably are positioned in the central zone of the sleeve 51, leaving an open area at the right and at the left. In the throwing position as shown in Figure 10, the head 34 is positioned at the right end of the sleeve. On impact, the head is forced past the spines 51 to the left end of the sleeve engaging the body. The spines may be of metal wire or plastic rod and may be mounted directly in the body if desired. However, it is preferable to mount them in a sleeve which is then inserted into the body.

CLAIMS

1. A dart comprising an elongate body having at one end, means defining an interior cavity of larger cross-section area and an axial passage of smaller cross-section area, and at the other end, means for mounting a tail; a point with a head positioned in said cavity and a shaft slidable in said passage for moving said head between a first position with said head remote from the bottom of said cavity and a second position with said head engaging said cavity bottom; said point and body including interengaging means resisting movement of said head from said first to said

second position.

2. A dart as claimed in claim 1, wherein said interengaging means is disposed about substantially the entire periphery of said head and cavity.

3. A dart as claimed in claim 1, wherein said body cavity is closed by an insert having said axial passage therein, with said insert carrying a plurality of resilient fingers having inwardly directed portions tending to maintain said head in said first position, with said head movable past said fingers to engage said cavity bottom when said point impacts a target.

4. A dart as claimed in claim 1, wherein said cavity includes a peripheral groove, and said head carries a plurality of resilient fingers having outwardly directed portions for engaging said groove and tending to maintain said head in said first position, with said head movable past said groove to engage said cavity bottom when said point impacts a target.

5. A dart as claimed in claim 1, wherein said interengaging means comprises a coil spring carried on said head and compressed within said cavity to engage the wall of said cavity.

6. A dart as claimed in claim 1, wherein said interengaging means comprises a plurality of resilient spines carried in said body projecting into said cavity for engagement with said head.

7. A dart as claimed in claim 1, wherein said interengaging means includes a resilient member disposed about and engaging said head as said head moves in said cavity.

8. A dart substantially as hereinbefore described with reference to and as shown in Figures 1-5, Figure 6, Figure 7, Figures 8 and 9 or Figures 10 and 11 of the accompanying drawings.