

19



NL Octrooicentrum

11

2009963

12 C OCTROOI

21

Aanvraagnummer: **2009963**

51

Int.Cl.:

A61B 5/00 (2006.01)

A61B 5/155 (2006.01)

A61B 5/145 (2006.01)

22

Aanvraag ingediend: **11.12.2012**

30

Voorrang:
11.12.2011 US 61/569287

43

Aanvraag gepubliceerd:
19.06.2013

47

Octrooi verleend:
11.11.2013

45

Octrooischrift uitgegeven:
20.11.2013

73

Octrooihouder(s):
Abbott Diabetes Care, Inc. te Alameda, California, Verenigde Staten van Amerika (US).

72

Uitvinder(s):
**Louis Pace te San Carlos, California (US).
Peter G. Robinson te Alamo, California (US).
Udo Hoss te Castro Valley, California (US).
Samuel Mason Curry te San Francisco, California (US).
Phillip William Carter te Oakland, California (US).
Vincent Michael DiPalma te Hayward, California (US).
Amit Mhatre te Sunnyvale, California (US).
Jennifer Olson te San Francisco, California (US).
Manuel Luis Miguel Donnay te San Francisco, California (US).
Marc Barry Taub te Mountain View, California (US).**

74

Gemachtigde:
Ir. A.A.G. Land c.s. te DEN HAAG.

54

Analyte sensor devices, connections, and methods.

57

Devices associated with on-body analyte sensor units are disclosed. These devices include any of packaging and/or loading systems, applicators and elements of the on-body sensor units themselves. Also, various approaches to connecting electrochemical analyte sensors to and/or within associated on-body analyte sensor units are disclosed. The connector approaches variously involve the use of unique sensor and ancillary element arrangements to facilitate assembly of separate electronics assemblies and sensor elements that are kept apart until the end user brings them together.

NL C 2009963

Dit octrooi is verleend ongeacht het bijgevoegde resultaat van het onderzoek naar de stand van de techniek en schriftelijke opinie. Het octrooischrift komt overeen met de oorspronkelijk ingediende stukken.

ANALYTE SENSOR DEVICES, CONNECTIONS, AND METHODSCROSS-REFERENCE TO RELATED APPLICATION

5 The present application claims priority to US
Provisional Patent Application Serial No. 61/569,287, filed
on December 11, 2011, entitled "Analyte Sensor Devices,
Connections, And Methods," the entirety of which is
incorporated herein by reference.

10

BACKGROUND

Diabetes Mellitus is an incurable chronic disease in
which the body does not produce or properly utilize insulin.
15 Insulin is a hormone produced by the pancreas that regulates
blood sugar (glucose). In particular, when blood sugar
levels rise, e.g., after a meal, insulin lowers the blood
sugar levels by facilitating blood glucose to move from the
blood into the body cells. Thus, when the pancreas does not
20 produce sufficient insulin (a condition known as Type 1
Diabetes) or does not properly utilize insulin (a condition
known as Type II Diabetes), the blood glucose remains in the
blood resulting in hyperglycemia or abnormally high blood
sugar levels.

25 The vast and uncontrolled fluctuations in blood
glucose levels in people suffering from diabetes cause long-
term, serious complications. Some of these complications
include blindness, kidney failure, and nerve damage.
Additionally, it is known that diabetes is a factor in
30 accelerating cardiovascular diseases such as atherosclerosis
(hardening of the arteries), leading to stroke, coronary
heart disease, and other diseases. Accordingly, one

important and universal strategy in managing diabetes is to control blood glucose levels.

One element of managing blood glucose levels is testing to monitor blood glucose levels. Conventional *in vitro* techniques, such as drawing blood samples, applying the blood to a test strip, and determining the blood glucose level using colorimetric, electrochemical, or photometric test meters may be employed. Another more recent technique for monitoring glucose levels is by using an *in vivo* glucose monitoring system, that continuously or automatically tests glucose, such as for example, the FreeStyle Navigator[®] Continuous Glucose Monitoring System, manufactured by Abbott Diabetes Care Inc.

Unlike conventional *in vitro* blood glucose monitoring approaches, analyte monitoring systems employ an insertable or implantable *in vivo* sensor in contact with interstitial fluid of a user for a period of time that detects and monitors glucose levels. Prior to use of a new sensor, a user inserts at least a portion of the sensor under his skin. Typically, an applicator assembly is employed to insert the sensor in the body of the user, with the sensor maintained in position by an on-body device including sensor electronics. For insertion, a sharp engaged with the sensor, pierces the skin of the user and is then removed from the body of the user leaving the sensor in place.

To fully realize the advantages associated with such systems, what is needed are applicator systems configured to handle insertion, as well as associated storage and user interface issues, that are easy-to-use, reliable and minimize both user inconvenience and pain. The present invention provides such solutions and additional or alternative advantages as described below and/or as may be

appreciated by those of skill in the art upon review of the subject disclosure.

SUMMARY

5 Certain embodiments concern the subject packaging and/or loading systems, applicators and elements of the on-body devices themselves. The on-body devices include electronics and mounting for a sensor held in a sensor assembly. Certain embodiments also concern the connection of
10 electrochemical analyte sensors to and/or within the associated on-body devices. The approaches variously involve the use of unique sensor and unique ancillary element arrangements to facilitate assembly of separate on-body devices and sensor assembly units that are kept apart until
15 the user brings them together. Methods associated with such use also form part of the inventive subject matter.

 Certain embodiments are described that include an analyte sensor (e.g., a glucose sensor) and an applicator assembly to position a portion of the sensor beneath a skin
20 surface, as well as methods of positioning at least a portion of the sensor and methods of analyte testing or monitoring. Further methods include the manner of preparing the applicator assembly. Namely, such acts associated with user assembly and mating of the component parts of a
25 monitoring system.

 Such a monitoring system includes an on-body device mount typically adapted to adhere to a skin of a subject, an analyte sensor coupled to the on-body device, and an insertion sharp having a longitudinal body including a
30 longitudinal opening to receive at least a portion of the sensor body. The details of the sensor may vary. Exemplary chemistries and constructions are described in any of US Patent Nos. 5,593,852, 6,284,478, and 6,329,161, each

incorporated by reference herein in its entirety. Exemplary form-factors or configurations (e.g., for associated use with an insertion "sharp") are described in any of US Patent Nos. 6,175,752, 6,565,509, 6,134,461 and 6,990,366 and in US
5 Publication No. 2010/0230285, each incorporated by reference herein in its entirety.

Likewise, the details of the mount may vary. For instance, the mount may include sensor electronics and other adaptation to communicate with a monitoring device. Various
10 options for communications facilities (e.g., wireless transmitters, transponders, etc.) are described in detail in US Publication Nos. 2010/0198034 and 2011/0213225, the entirety of the applications hereby incorporated by reference, including cited and incorporated references.

15 In some embodiments, the invention includes an on-body device that includes a sensor assembly. The sensor assembly includes a sensor with a distal portion for operative contact with a fluid of the user. The on-body device also includes an electronics assembly defining a distal surface
20 adapted for attachment to the skin of the user and housing a circuit coupleable to the sensor for detecting electrical signals from the sensor. An applicator assembly includes a sleeve defining a distal surface for placement on the skin of the subject, a handle for a user interface, and various
25 internal support, coupling, guide, grasping, stop and detent features as well as driver elements. A container is provided to interface with the applicator assembly for the purpose of loading one or more of the sensor, the sharp, and/or the mount/electronics assembly into the applicator assembly and
30 readying the applicator assembly for use.

The present disclosure includes the subject devices, kits in which they are included, and methods of use and manufacture. A number of aspects of such manufacture are

discussed herein. Further details can be appreciated in reference to the figures and/or associated description.

Notwithstanding the claims, the invention is also described in the following clauses:

5

1. An apparatus comprising:

a first assembly including a portion of an on-body device;

10 a second assembly coupleable to the first assembly to form the on-body device and a sharp supporting a sensor of the on-body device;

an applicator assembly releasably coupled to the first assembly; and

15 a container releasably coupled to the second assembly, wherein in response to force applied to the applicator assembly along a longitudinal axis that drives the applicator assembly into the container, the applicator assembly releases and retrieves the second assembly from the container and couples the first assembly to the second
20 assembly to form the on-body device releasably held within the applicator assembly, and

wherein the on-body device once held within the applicator assembly is ready to be applied to a user.

25 2. The apparatus of clause 1 wherein in response to a force applied to the applicator assembly along the longitudinal axis with the applicator assembly loaded with the on-body device and held against the user, the applicator assembly collapses along the longitudinal axis, drives the sharp
30 supporting the sensor of the on-body device through skin of the user in a direction along the longitudinal axis, releases the on-body device from the applicator assembly upon the applicator assembly reaching a fully collapsed

position, adheres the on-body device to the skin of the user, and retracts the sharp into the applicator assembly leaving the sensor in the user.

5 3. The apparatus of clause 2 wherein the applicator assembly includes an isolated inner space defined by an enclosure and a carrier of the first assembly, and wherein the sharp is entirely contained in the inner space when retracted into the applicator assembly.

10

4. The apparatus of clause 1 wherein the first assembly is an electronics assembly including sensor electronics and an enclosure surrounding the sensor electronics, the sensor electronics including a processor and a communications
15 facility; and

15

wherein the second assembly is a sensor assembly including a sensor, a sharp supporting the sensor, a support structure, and a connector coupled to the sensor and coupleable to the sensor electronics, the support structure
20 supporting the connector and sensor, and releasably supporting the sharp.

20

5. The apparatus of clause 1 wherein the second assembly is an electronics assembly including sensor electronics and an enclosure surrounding the sensor electronics, the sensor
25 electronics including a processor and a communications facility; and

25

wherein the first assembly is a sensor assembly including a sensor, a sharp supporting the sensor, a support
30 structure, and a connector coupled to the sensor and coupleable to the sensor electronics, the support structure supporting the connector and sensor, and releasably supporting the sharp.

30

6. An apparatus comprising:

an electronics assembly including sensor electronics;

5 a sensor assembly including a sensor coupleable to the sensor electronics;

an applicator assembly releasably coupled to the electronics assembly; and

10 wherein in response to force applied to the applicator assembly along a longitudinal axis that drives the applicator assembly into the container, the applicator assembly releases and retrieves the sensor assembly from the container and couples the electronics assembly to the sensor assembly to form an on-body device releasably held within
15 the applicator assembly, and

wherein the on-body device once held within the applicator assembly is ready to be applied to a user.

7. The apparatus of clause 6 wherein in response to a force

20 applied to the applicator assembly along the longitudinal axis with the applicator assembly loaded with the on-body device and held against the user, the applicator assembly is enabled to collapse along the longitudinal axis, drive a sharp supporting the sensor of the on-body device through
25 skin of the user in a direction along the longitudinal axis, release the on-body device from the applicator assembly upon the applicator assembly reaching a fully collapsed position, adhere the on-body device to the skin of the user, and retract the sharp into the applicator assembly leaving the
30 sensor in the user.

8. The apparatus of clause 7 wherein the applicator assembly includes an isolated inner space defined by an enclosure and

a carrier of the electronics assembly, and wherein the sharp is entirely contained in the inner space when retracted into the applicator assembly.

5 9. The apparatus of clause 6 wherein the container further includes a platform disposed to protect and releasably retain the sensor assembly in the container and operative to translate between an initial position and a compressed position.

10

10. The apparatus of clause 9 wherein the platform is lockable in the initial position and is operable to be unlocked by the applicator assembly, to translate to the compressed position in response to the force applied to the applicator assembly along the longitudinal axis that drives the extended, locked applicator assembly into the container, and to release the sensor assembly upon reaching the compressed position.

20 11. The apparatus of clause 9 wherein the platform includes a sensor assembly guide feature operative to direct the sensor assembly into the electronics assembly independent of an overall orientation of the apparatus.

25 12. The apparatus of clause 7 wherein the sensor disposed within a support structure includes a biasing feature operative to bias the sensor into the sharp while the sharp and the sensor are driven through the skin of the user.

30 13. The apparatus of clause 6 wherein the sensor electronics include at least one electronic contact and the sensor assembly includes a support structure that includes a compression feature operative to compress and seal a

connector of the sensor assembly to the at least one electronic contact.

14. The apparatus of clause 6 wherein the container includes
5 guide features to control movement of the applicator
assembly into the container and a detent feature which
provides an amount of resistance to the force applied to the
applicator assembly along the longitudinal axis that drives
10 the applicator assembly into the container to insure that
once overcome, the sensor assembly is driven into and seated
in the electronics assembly by a resulting translation of
the electronics assembly in the applicator assembly.

15. The apparatus of clause 7 wherein the applicator
15 assembly includes guide features to allow the applicator
assembly to collapse along the longitudinal axis and a
detent feature which provides an amount of resistance to the
force applied to the applicator assembly along the
longitudinal axis with the applicator assembly held against
20 a user to insure that once overcome, the sharp and sensor
are driven into the user by a resulting translation of the
on-body device in the applicator assembly.

16. The apparatus of clause 6 wherein the electronics
25 assembly includes an adhesive patch for adhering the
assembled on-body device to the skin of the user, the
electronics assembly is sterilized using a first method, the
sensor assembly is sterilized using a second method, the
electronics assembly and adhesive patch are incompatible
30 with the second method of sterilization, and the sensor
assembly is incompatible with the first method of
sterilization.

17. An apparatus comprising:

an electronics assembly including sensor electronics;
a sensor assembly including a sensor coupleable to the
sensor electronics;

5 an applicator assembly releasably coupled to the
electronics assembly, the applicator assembly being lockable
in an extended position and collapsible along a longitudinal
axis of the applicator assembly to a retracted position when
unlocked; and

10 a container releasably coupled to the sensor assembly
and including an applicator assembly unlock feature disposed
to unlock the applicator assembly,

wherein in response to force applied to the applicator
assembly along the longitudinal axis that drives the
15 extended, locked applicator assembly into the container, the
applicator assembly releases and retrieves the sensor
assembly from the container, couples the electronics
assembly to the sensor assembly to form an on-body device
releasably held within the applicator assembly, and unlocks
20 the applicator assembly.

18. The apparatus of clause 17 wherein in response to a
force applied to the applicator assembly along the
longitudinal axis with the extended, unlocked applicator
25 assembly held against a user, the applicator assembly is
enabled to collapse along the longitudinal axis to the
retracted position, drive a sharp supporting the sensor of
the on-body device through skin of the user in a direction
along the longitudinal axis, release the on-body device from
30 the applicator assembly upon the applicator assembly
reaching the retracted position, adhere the on-body device
to the skin of the user, and retract the sharp into the
applicator assembly leaving the sensor in the user.

19. The apparatus of clause 18 wherein the applicator assembly includes an isolated inner space defined by an enclosure and a carrier of the electronics assembly, and
5 wherein the sharp is entirely contained in the inner space when retracted into the applicator assembly .

20. The apparatus of clause 17 wherein the container further includes a platform disposed to protect and releasably
10 retain the sensor assembly in the container and operative to translate between an initial position and a compressed position.

21. The apparatus of clause 20 wherein the platform is
15 lockable in the initial position and is operable to be unlocked by the applicator assembly, to translate to the compressed position in response to the force applied to the applicator assembly along the longitudinal axis that drives the extended, locked applicator assembly into the container,
20 and to release the sensor assembly upon reaching the compressed position.

22. The apparatus of clause 20 wherein the platform includes a sensor assembly guide feature operative to direct the
25 sensor assembly into the electronics assembly independent of an overall orientation of the apparatus.

23. The apparatus of clause 18 wherein the sensor disposed within a support structure includes a biasing feature
30 operative to bias the sensor into the sharp while the sharp and the sensor are driven through the skin of the user.

24. The apparatus of clause 17 wherein the sensor electronics include at least one electronic contact and the sensor assembly includes a support structure that includes a compression feature operative to compress and seal a connector of the sensor assembly to the at least one electronic contact.

25. The apparatus of clause 17 wherein the container includes guide features to control movement of the applicator assembly into the container and a detent feature which provides an amount of resistance to the force applied to the locked applicator assembly along the longitudinal axis that drives the locked applicator assembly into the container to insure that once overcome, the sensor assembly is driven into and seated in the electronics assembly by a resulting translation of the electronics assembly in the applicator assembly and that the applicator assembly is unlocked by the applicator assembly unlock feature in the container.

20

26. The apparatus of clause 18 wherein the applicator assembly includes guide features to allow the unlocked applicator assembly to collapse along the longitudinal axis and a detent feature which provides an amount of resistance to the force applied to the applicator assembly along the longitudinal axis with the unlocked applicator assembly held against a user to insure that once overcome, the sharp and sensor are driven into the user by a resulting translation of the on-body device in the applicator assembly.

30

27. The apparatus of clause 17 wherein the electronics assembly is sterilized using a first method, the sensor assembly is sterilized using a second method, the

electronics assembly is incompatible with the second method of sterilization, and the sensor assembly is incompatible with the first method of sterilization.

5 28. An apparatus comprising:

an electronics assembly including sensor electronics;

a sensor assembly including a sensor coupleable to the sensor electronics;

10 an applicator assembly releasably coupled to the electronics assembly and including a guide sleeve lockable in an extended position and translatable along a longitudinal axis of the applicator assembly to a retracted position when unlocked; and

15 a container releasably coupled to the sensor assembly and including a guide sleeve unlock feature disposed to unlock the guide sleeve of the applicator assembly,

20 wherein in response to force applied to the applicator assembly along the longitudinal axis that drives the extended, locked guide sleeve into the container, the applicator assembly releases and retrieves the sensor assembly from the container, couples the electronics assembly to the sensor assembly to form an on-body device releasably held within the applicator assembly, and unlocks the guide sleeve.

25

29. The apparatus of clause 28 wherein in response to a force applied to the applicator assembly along the longitudinal axis with the extended, unlocked guide sleeve held against a user, the applicator assembly enables the 30 extended, unlocked guide sleeve to translate along the longitudinal axis to the retracted position, drive a sharp supporting the sensor of the on-body device through skin of the user in a direction along the longitudinal axis, release

the on-body device from the applicator assembly upon the guide sleeve reaching the retracted position, adhere the on-body device to the skin of the user, and retract the sharp into the applicator assembly leaving the sensor in the user.

5

30. The apparatus of clause 28 wherein the container further includes a platform disposed to protect and releasably retain the sensor assembly in the container and operative to translate between an initial position and a compressed position.

10

31. The apparatus of clause 30 wherein the platform is lockable in the initial position and is operable to be unlocked by the guide sleeve of the applicator assembly, to translate to the compressed position in response to the force applied to the applicator assembly along the longitudinal axis that drives the extended, locked guide sleeve into the container, and to release the sensor assembly upon reaching the compressed position.

15
20

32. The apparatus of clause 30 wherein the platform includes a sensor assembly guide feature operative to direct the sensor assembly into the electronics assembly independent of an overall orientation of the apparatus.

25

33. The apparatus of clause 29 wherein the sensor disposed within the support structure includes a biasing feature operative to bias the sensor into the sharp while the sharp and the sensor are driven through the skin of the user.

30

34. The apparatus of clause 28 wherein the sensor electronics include at least one electronic contact and the support structure includes a compression feature operative

to compress and seal the connector to the at least one electronic contact.

35. The apparatus of clause 28 wherein the container
5 includes guide features to control translation of the guide sleeve and a detent feature which provides an amount of resistance to the force applied to the applicator assembly along the longitudinal axis that drives the extended, locked guide sleeve into the container to insure that once
10 overcome, the sensor assembly is driven into and seated in the electronics assembly by a resulting translation of the electronics assembly in the applicator assembly.

36. The apparatus of clause 29 wherein the applicator
15 assembly includes guide features to allow the guide sleeve to translate into the applicator assembly and a detent feature which provides an amount of resistance to the force applied to the applicator assembly along the longitudinal axis with the extended, unlocked guide sleeve held against a
20 user to insure that once overcome, the sharp and sensor are driven into the user by a resulting translation of the on-body device in the applicator assembly.

37. The apparatus of clause 28 wherein the electronics
25 assembly is sterilized using a first method, the sensor assembly is sterilized using a second method, the electronics assembly is incompatible with the second method of sterilization, and the sensor assembly is incompatible with the first method of sterilization.

30

38. An on-body device comprising:

an electronics assembly including sensor electronics and an enclosure surrounding the sensor electronics, the

sensor electronics including a processor and a communications facility; and

5 a sensor assembly including a sensor, a sharp supporting the sensor, a support structure, and a connector coupled to the sensor and coupleable to the sensor electronics, the support structure supporting the connector and sensor, and releasably supporting the sharp,

10 wherein the electronics assembly is releasably coupleable to an applicator assembly that includes a guide sleeve lockable in an extended position and operative to translate along a longitudinal axis of the applicator assembly to a retracted position when unlocked, the guide sleeve including an electronics assembly decouple feature disposed to release the electronics assembly from the applicator assembly when the guide sleeve is in the retracted position,

15 wherein the sensor assembly is releasably coupled to a container and includes a guide sleeve unlock feature disposed to unlock the guide sleeve of the applicator assembly,

20 wherein in response to a first force to the applicator assembly along the longitudinal axis that drives the extended, locked guide sleeve into the container, the applicator assembly is operable to release and retrieve the sensor assembly from the container, couple the electronics assembly to the sensor assembly to form the on-body device releasably held within the applicator assembly, seal the sealable enclosure with the support structure, and unlock the guide sleeve, and

30 wherein in response to a second force to the applicator assembly along the longitudinal axis with the extended, unlocked guide sleeve held against a user, the applicator assembly is operable to allow the extended, unlocked guide

sleeve to translate along the longitudinal axis to the retracted position, drive the sharp and the sensor of the on-body device through skin of the user in a direction along the longitudinal axis, release the on-body device from the applicator assembly upon the guide sleeve reaching the retracted position; adhere the on-body device to the skin of the user, and retract the sharp into the applicator assembly leaving the sensor in the user and the on-body device sealed from moisture.

10

39. An on-body device comprising:

an electronics assembly including sensor electronics and an enclosure surrounding the sensor electronics, the sensor electronics including a processor and a communications facility; and

15

a sensor assembly including a sensor, a support structure, and a connector coupled to the sensor and coupleable to the sensor electronics, the support structure supporting the connector and sensor,

20

wherein the sensor assembly is sealably matable to the electronics assembly with the sensor in electrical communication with the sensor electronics,

wherein the support structure of the sensor assembly further supports a removable sharp that supports the sensor,

25

wherein the on-body device is assembled within an applicator in response to a first force applied to the applicator, and

wherein the assembled on-body device is applied to a user in response to a second force applied to the applicator.

30

40. An applicator of on-body device comprising:

a housing including integrally formed grip features;

a removable cap coupleable to the housing and operative to seal the applicator;

an electronics assembly retention support coupled to the housing and operative to releasably retain an
5 electronics assembly including sensor electronics and a sealable enclosure surrounding the sensor electronics, the sensor electronics including a processor and a communications facility;

a guide sleeve lockable in an extended position
10 partially within the housing and operative to translate along a longitudinal axis of the applicator to a retracted position when unlocked, the guide sleeve including an electronics assembly decouple feature disposed to release the electronics assembly from the applicator when the guide
15 sleeve is in the retracted position; and

a sharp retraction assembly contained within the housing and operative to remove a sharp from a sensor assembly when the guide sleeve reaches the retracted position, wherein the sensor assembly includes a sensor, the
20 sharp supporting the sensor, a support structure, and a connector coupled to the sensor and coupleable to the sensor electronics, the support structure supporting the connector and sensor, and releasably supporting the sharp.

25 41. The applicator of clause 40 wherein the guide sleeve includes a proximate end and a distal end, the distal end defining a first distal plane,

wherein the electronics assembly retention support defines a second distal plane, and

30 wherein the second distal plane is closer to the proximate end of the guide sleeve than the first distal plane when the guide sleeve is in the extended position.

42. The applicator of clause 41 wherein in response to a first force applied to the applicator along the longitudinal axis that drives the extended, locked guide sleeve into a container releasably holding the sensor assembly, the applicator is operable to release and retrieve the sensor assembly from the container, couple the electronics assembly to the sensor assembly to form an on-body device releasably held within the applicator, seal the sealable enclosure with the support structure, and unlock the guide sleeve using a guide sleeve unlock feature disposed within the container.

43. The applicator of clause 42 wherein in response to a second force applied to the applicator along the longitudinal axis with the extended, unlocked guide sleeve held against a user, the applicator is operable to allow the guide sleeve to translate along the longitudinal axis to the retracted position, drive the sharp and the sensor of the on-body device through skin of the user in a direction along the longitudinal axis, release the on-body device from the applicator upon the guide sleeve reaching the retracted position, adhere the on-body device to the skin of the user, and retract the sharp into the applicator leaving the sensor in the user and the on-body device sealed from moisture.

44. The applicator of clause 43 wherein the first distal plane is closer to the proximate end of the guide sleeve than the second distal plane when the guide sleeve is in the retracted position.

45. A method comprising:

applying a first force to an applicator assembly along a longitudinal axis of the applicator assembly to drive a guide sleeve of the applicator assembly into a container

that releasably holds a sensor assembly, the sensor assembly including a sensor, a sharp supporting the sensor, a support structure, and a connector coupled to the sensor, the support structure supporting the connector and sensor, and
5 releasably supporting the sharp;

engaging a platform retaining the sensor assembly in the container with the guide sleeve to release the sensor assembly;

coupling an electronics assembly releasably held within
10 the applicator assembly to the sensor assembly to form an on-body device;

sealing an enclosure surrounding sensor electronics within the electronics assembly with the support structure of the sensor assembly, the sensor electronics including a
15 processor and a communications facility;

unlocking the guide sleeve of the applicator assembly using a guide sleeve unlock feature disposed within the container to allow the guide sleeve to be translated along the longitudinal axis of the applicator assembly from an
20 extended position to a retracted position, the guide sleeve including an electronics assembly decouple feature disposed to release the electronics assembly from the applicator assembly when the guide sleeve is in the retracted position;

removing the applicator assembly including the on-body
25 device from the container;

applying a second force to the applicator assembly along the longitudinal axis with the extended, unlocked guide sleeve held against a user;

urging the extended, unlocked guide sleeve to translate
30 along the longitudinal axis to the retracted position;

driving the sharp and the sensor of the on-body device through skin of the user in a direction along the longitudinal axis;

releasing the on-body device from the applicator assembly upon the guide sleeve reaching the retracted position;

adhering the on-body device to the skin of the user;

5 and

retracting the sharp into the applicator assembly leaving the sensor in the user and the on-body device sealed from moisture.

10 46. The method of clause 45 wherein coupling the electronics assembly within the applicator assembly to the sensor assembly includes coupling the connector to the sensor electronics.

15 47. An apparatus comprising:

an electronics assembly including sensor electronics and a sealable enclosure surrounding the sensor electronics, the sensor electronics including a processor and a communications facility;

20 a sensor assembly including a sensor, a sharp supporting the sensor, a support structure, and a connector coupled to the sensor and coupleable to the sensor electronics, the support structure supporting the connector and sensor, and releasably supporting the sharp;

25 an applicator assembly releasably coupled to the electronics assembly and including a guide sleeve lockable in an extended position and operative to translate along a longitudinal axis of the applicator assembly to a retracted position when unlocked, the guide sleeve including an
30 electronics assembly decouple feature disposed to release the electronics assembly from the applicator assembly when the guide sleeve is in the retracted position; and

a container releasably coupled to the sensor assembly and including a guide sleeve unlock feature disposed to unlock the guide sleeve of the applicator assembly,

5 wherein in response to a first application of linear force to the applicator assembly along the longitudinal axis that drives the extended, locked guide sleeve into the container, the applicator assembly is operable to release and retrieve the sensor assembly from the container, couple the electronics assembly to the sensor assembly to form an
10 on-body device releasably held within the applicator assembly, seal the sealable enclosure with the support structure, and unlock the guide sleeve, and

wherein in response to a second application of linear force to the applicator assembly along the longitudinal axis
15 with the extended, unlocked guide sleeve held against a user, the applicator assembly is operable to allow the extended, unlocked guide sleeve to translate along the longitudinal axis to the retracted position, drive the sharp and the sensor of the on-body device through skin of the
20 user in a direction along the longitudinal axis, release the on-body device from the applicator assembly upon the guide sleeve reaching the retracted position, adhere the on-body device to the skin of the user, and retract the sharp into the applicator assembly leaving the sensor (202) in the user
25 and the on-body device sealed from moisture.

48. The apparatus of clause 47 wherein the container further includes a platform disposed to protect and releasably retain the sensor assembly in the container and operative to
30 translate between an initial position and a compressed position.

49. The apparatus of clause 48 wherein the platform is lockable in the initial position and is operable to be unlocked by the guide sleeve of the applicator assembly, to translate to the compressed position in response to the first application of linear force, and to release the sensor assembly upon reaching the compressed position.

50. The apparatus of clause 48 wherein the platform includes a sensor assembly guide feature operative to direct the sensor assembly into the electronics assembly independent of an overall orientation of the apparatus.

51. The apparatus of clause 47 wherein the sensor disposed within the support structure includes a biasing feature operative to bias the sensor into the sharp while the sharp and the sensor are driven through the skin of the user.

52. The apparatus of clause 47 wherein the sensor electronics include at least one electronic contact and the support structure includes a compression feature operative to compress and seal the connector to the at least one electronic contact.

53. The apparatus of clause 47 wherein the container includes guide features to control translation of the guide sleeve and a detent feature which provides an amount of resistance to the first application of linear force to insure that once overcome, the sensor assembly is driven into and seated in the electronics assembly by a resulting translation of the electronics assembly in the applicator assembly.

54. The apparatus of clause 47 wherein the applicator assembly includes guide features to allow the guide sleeve to translate into the applicator assembly and a detent feature which provides resistance to the second application of linear force to insure that once overcome, the sharp and sensor are driven into the user by a resulting translation of the on-body device in the applicator assembly.

55. The apparatus of clause 47 wherein the electronics assembly is sterilized using a first method, the sensor assembly is sterilized using a second method, the electronics assembly is incompatible with the second method of sterilization, and the sensor assembly is incompatible with the first method of sterilization.

15

56. An apparatus storing a sensor, the apparatus comprising:
an enclosure including an opening, sides, and an end;
a platform having a proximal position proximate to the opening and a distal position proximate to the end, the sides including guide features disposed to engage the platform and to direct the platform to translate from the proximal position to the distal position along a longitudinal axis of the enclosure; and

20
a support disposed on the end and including a structure arranged to support a sensor assembly, the sensor assembly including a sensor, a sharp supporting the sensor, and a connector,

25
wherein the sensor assembly is retained within the enclosure when the platform is in the proximal position and released when the platform is in the distal position.

30

57. The apparatus of clause 56 wherein the platform provides a barrier to protect the sensor assembly from being contacted when the platform is in the proximal position, and wherein the guide features maintain a major surface of the platform approximately parallel to the end of the enclosure.

58. The apparatus of clause 56 wherein the platform is locked from translating when the platform is in the proximal position.

59. The apparatus of clause 58 wherein the platform is unlocked and operable to translate from the proximal position to the distal position in response to contact with an applicator.

60. The apparatus of clause 56 wherein the platform is operable to lock in the distal position upon reaching the distal position.

61. The apparatus of clause 56 wherein the end includes a sealable end port and the enclosure further comprises a cover for sealing the opening.

62. A sensor assembly comprising:
a sensor having a tail portion, a contacts portion, and a bendable portion;
a seal including electrical contacts disposed to align with the contacts portion of the sensor and to allow electrical signals to pass through the seal;
a support including a distal surface and features for sealably coupling to an electronics assembly; and

a sharp including a channel for supporting the tail portion of the sensor and a hub for gripping the sharp during retraction,

5 wherein the seal is shaped to enclose the contacts portion of the sensor within the support.

63. The sensor assembly of clause 62 wherein the seal is formed from flexible material and includes a hinge allowing the seal to be folded around the contacts portion of the sensor, sealing both sides of the contacts portion.

10

64. The sensor assembly of clause 62 wherein the bendable portion of the sensor facilitates having a major surface of the contacts portion of the sensor substantially parallel with a circuit board of an electronics assembly when the sensor assembly is mated to the electronics assembly while also concurrently facilitating having the tail portion of the sensor substantially perpendicular to the major surface of the contacts portion.

15

20

BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of various aspects, features, and embodiments of the subject matter described herein is provided with reference to the accompanying drawings, which are briefly described below. The drawings are illustrative and may or may not be drawn to scale, with the possibility of some components and features being exaggerated for clarity. Similar components may be numbered identically or not. The drawings illustrate various aspects and features of the present subject matter and may illustrate one or more embodiment(s) or example(s) of the present subject matter in whole or in part.

25

30

FIG. 1 is a flowchart, indicating user activity in handling the subject devices;

FIGS. 2A-2G illustrate such activity with additional detail;

5 FIG. 3 is an assembly view of an applicator or inserter;

FIG. 4 is an assembly view of a sensor container or loader;

10 FIGS. 5A and 5B are section views of the container in FIG. 4;

FIG. 6 is an assembly view of an alternative container;

FIG. 7 is a section view of the assembly of FIG. 6;

15 FIGS. 8 is an assembly view of yet another sensor container set or loader;

FIGS. 9A and 9B are top and section views, respectively, of the container set assembly of FIG. 8 in stages of operation;

20 FIGS. 10A-10N variously illustrate the mechanics of preparing the applicator for use;

FIGS. 11A-11F illustrate the mechanics of applicator use;

25 FIGS. 12A-12D are perspectives illustrating another applicator/container set approach in which the container holds the electronics assembly;

FIGS. 13A-13C variously illustrate use of the applicator in FIGS. 12A-12D in connection with a locking-sleeve feature;

30 FIGS. 14A and 14B illustrate an applicator with a removable locking strip;

FIGS. 15A-15F variously illustrate use of the applicator in FIGS. 14A and 14B;

FIGS. 16A and 16B are sectional and detail to views, respectively, of features of the container in FIGS. 15A-15D;

FIGS. 17A and 17B are perspective assembly views illustrating alternative container configurations to that
5 illustrated in FIG. 16A and 16B;

FIG. 18 is a side-section view illustrating the features of the applicator and container sets variously shown in FIGS. 15A-15F;

FIGS. 19A and 19B are perspective views of a sensor
10 assembly incorporated in the system shown in FIG. 18;

FIGS. 20A and 20B are perspective views of the operation of a sensor assembly retention unit incorporated in the system shown in FIG. 18;

FIGS. 21A-21C are perspective section views
15 illustrating sensor assembly receipt by the sensor mount and sharp withdrawal from the assembled complex;

FIG. 22 is a perspective assembly view of advantageous sensor and sensor connector elements;

FIGS. 23A and 23B are perspective assembly and final-
20 assembly views, respectively of the sensor components in FIG. 22;

FIGS. 24A and 24B are top and bottom perspective views, respectively of circuit board components to be used with the assembly shown in FIGS. 23A and 23B;

FIGS. 25A and 25B are perspective views illustrating
25 assembly of the subject components in stages;

FIG. 26 is an assembly view of the on-body/sensor mount unit in FIGS. 25A and 25B illustrating an advantageous seal element;

FIGS. 27A and 27B are section views further
30 illustrating the seal element and its relation to the mount in FIG. 26;

Figs 28A-F are perspective views of another advantageous sensor and sensor element arrangement;

Figs 29A-D are perspective views of another advantageous sensor and sensor connector arrangement;

5 FIGS. 30A-30C are perspective views illustrating yet another advantageous sensor approach with the sensor as originally produced, modified for use, and shown coupled to a PCB, respectively;

10 FIG. 30 is a perspective view illustrating the sensor as configured in FIG. 29B in contact with a circuit board assembly;

FIG. 31 is a side-section view showing a comparative approach, in a final on-body sensor assembly;

15 FIGS. 32A and 32B are perspective views of still other advantageous sensor configurations, these figures illustrating split-sensor approaches;

FIGS. 33A-33G are plane, side, magnified, and sectional views of an additional sensor configuration;

20 FIGS. 33H-33J are plane views of various sensor designs;

FIGS. 34A-34D are perspective views illustrating combination electrical connector and sensor isolator in yet another advantageous sensor arrangement;

25 FIGS. 35A and 35B are side assembly and section views, respectively, of the system shown in FIGS. 34A-34D;

FIG. 35C is an end-section view, with detail view, FIG. 35D, illustrating additional sensor features;

30 FIG. 36 is a perspective assembly view illustrating a sensor connection approach related to that in FIGS. 34A-34D for a sensor with contacts on a single side;

FIG. 37 is a perspective partial assembly view illustrating a mount-and-socket interface for the sensor assembly employing the components in FIG. 36;

FIG. 38 is a complete assembly view of that illustrated in Fig 37;

FIGS. 39A and 39B are perspective assembly and assembled views of a stacked non-directional sensor connect
5 arrangement;

FIG. 40 is a side partial-sectional view of the sensor in FIG. 39 received within an on-body device;

FIGS. 41A and 41B are partial perspective assembly views of another stacked non-directional sensor connection
10 arrangement;

FIG. 41C is a section view of the complete assembly of the components variously illustrated in FIGS. 41A and 41B;

FIG. 42 is an assembly view of an advantageous radial arrangement sensor connector assembly;

FIGS. 43A and 43B are reversed perspective views of the mount-side sensor connection component for use with an
15 assembly as shown in FIG. 42;

FIG. 44 is a section view of the complete assembly of the components variously illustrated in FIGS. 42, 43A and
20 43B;

FIGS. 45A and 45B are reversed assembly views of an alternative advantageous sensor connection assembly that can be used like that in FIG. 42;

FIGS. 46A and 46B are assembly and sectional views, respectively of a complete on-body device employing the
25 sensor and connection elements illustrated in FIGS. 45A and 45B;

FIG. 47A-47C are assembly and cross-sectional views of an on-body device including an integrated connector for the
30 sensor assembly;

FIGS. 48A-48D are construction views of an on-body subassembly;

FIG. 48E is a perspective view of a complete on-body electronics subassembly;

FIGS. 49A-49D illustrate the process of co-molding/overmolding the assembly in FIG. 48E;

5 FIGS. 50A-50C are assembly and sectional views of an alternative snap-together approach with the assembly in FIG. 48E; and

FIGS. 51A-51B are assembly views illustrating adhesive backing application in producing a final on-body device
10 ready for use as shown in perspective-view FIG. 51C.

DETAILED DESCRIPTION

Before the present disclosure is further described, it is to be understood that this disclosure is not limited to
15 the particular embodiments described, as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present disclosure will be
20 limited only by the appended claims.

As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein includes discrete components and features which may be readily separated from
25 or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present disclosure.

Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the
30 lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the disclosure. The upper and lower

limits of these smaller ranges may independently be included in the smaller ranges, and are also encompassed within the disclosure, subject to any specifically excluded limit in the stated range. Where the stated range includes one or
5 both of the limits, ranges excluding either or both of those included limits are also included in the disclosure.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this
10 disclosure belongs. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present disclosure, exemplary methods and materials are now described. All publications mentioned herein are incorporated herein by
15 reference to disclose and describe the methods and/or materials in connection with which the publications are cited.

As used herein and in the appended claims, the singular forms "a," "an," and "the" include plural referents
20 unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as "solely," "only" and the like in connection with the
25 recitation of claim elements, or use of a "negative" limitation.

The publications discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an
30 admission that the present disclosure is not entitled to antedate such publication by virtue of prior disclosure. Further, the dates of publication provided may be different

from the actual publication dates which may need to be independently confirmed.

Various exemplary embodiments of the disclosure are described below. Reference is made to these examples in a non-limiting sense. They are provided to illustrate more broadly applicable aspects of the present disclosure.

Various changes may be made to the disclosure described and equivalents may be substituted without departing from the true spirit and scope of the disclosure. In addition, many modifications may be made to adapt a particular situation, material, composition of matter, process, process act(s) or step(s) to the objective(s), spirit or scope of the present disclosure. All such modifications are intended to be within the scope of the claims made herein.

Applicator and Container Overview

Turning to FIG. 1, a flowchart depicting an example method 100 of using the apparatus of the present invention is provided. In some embodiments, a user starts with unpacking the applicator and container (102, 104). Unpacking the applicator (102) may include removing an end cap. Next, in an assembly operation (106), the constituent components are merged or connected (these elements include a sensor assembly and an electronics assembly which together form an on-body device and an insertion needle or sharp) and the user unlocks the applicator (or removes a locking element). The process of the assembly operation (106) and the constituent components are described in detail below.

Next, once the user has chosen an application site, an on-body device application operation (108) is performed. In a single continuous motion, the applicator is driven to insert the distal end of the sensor through the user's skin,

adhere the on-body device to the skin surface, and retract the sharp into the applicator for disposal. All three of these actions are perceived by the user to be an automated response to applying a force to the applicator causing it to trigger. Note that the user places the applicator on the skin of the insertion site and then applies the force to install the on-body device. Even after the applicator has been placed on the skin, the user can decide to move the applicator to a different location up until the application operation (108). Advantageously, the adhesive of the on-body device does not contact the user until the application operation (108) is performed. In a post application stage (110), use of the sensor for monitoring the user's analyte level occurs during wear followed by appropriate disposal.

Details of method 100 are illustrated in the sequence of drawings shown in FIGS. 2A to 2G. In FIG. 2A, one of the highlighted application sites 202, 204 on a user 200 is selected. In some embodiments, other application sites may be used. In some embodiments, a site preparation operation may optionally be performed. The application site 202, 204 may be shaved, exfoliated, cleaned, or otherwise treated to better adhere the on-body device. More specifically, the skin at the site of the user's body where the on-body device will be adhered is prepared to receive the on-body device. For example, the skin may be shaved with a razor, cleaned with isopropyl alcohol (IPA), and exfoliated with an abrasive. There are a number of mechanically exfoliating elements which could be used to remove an outer layer of dead skin and expose newer skin below. These elements include: microfiber exfoliating cloths; pumice or other abrasive mineral; metal-stamped components of a rasp/file type configuration; synthetic scouring material, e.g., Scotch-Brite®; an alternate adhesive tape or patch to be

applied and stripped off to remove dead skin; and organic abrasive elements such as salt, crushed almond shells, apricot kernels, etc. Likewise, there are a number of chemically exfoliating elements which could be used including: mild acids such as alpha hydroxyl acid, beta-hydroxyl acid and salicylic acid; and fruit enzymes. Such chemically abrasive element(s) may be incorporated in a preparation pad, towelette, swab or be supplied otherwise. In some embodiments, the end cap may include one or more exfoliating elements. In some embodiments, the end cap may be textured or otherwise formed to provide a surface that can be used to exfoliate the skin of the site where the on-body device will be adhered. Exfoliating away an outer layer of dead skin before application may allow the on-body device to better adhere to the skin for a longer period of time.

FIG. 2B illustrates loader or container 206 preparation, including removing cover 208 from a casing 210. FIG. 2C illustrates applicator 212 preparation including separating removable cap 214 from applicator assembly 216. In some embodiments, container 206 and applicator 212 can initially be coupled together to simplify packaging and shipping. For example, the removable cap 214 may include a boss or other feature that couples or snaps to a corresponding feature in the container 206. Thus, in some embodiments, before removing the cover 208 from the casing 210 and separating the removable cap 214 from the applicator assembly 216, the container 206 and applicator 212 are separated from each other.

As shown in FIG. 2D, once alignment indicators 218, 220 are aligned, the user assembly operation 106 (FIG. 1) is achieved by pushing the applicator assembly 216 firmly into the container 206 to retrieve a sensor and a sharp and to unlock a guide sleeve of the applicator assembly 216. In

FIG. 2E, the assembled and unlocked applicator assembly 216 is placed on the application site 204 (or 202) and pushed down firmly to effect on-body device application 108 (FIG. 1). As shown in FIG. 2F, upon used applicator assembly 216 removal from the application site 204, on-body device 222 is adhered to the user. In some embodiments, as illustrated in FIG. 2G, analyte levels detected by the sensor of the on-body device 222 are transmitted over a wireless communication link 224 via a communications facility (e.g., a transmitter, a transponder, etc.) within the on-body device 222 to a receiver unit 226 (referred to alternatively as a "reader unit" or "receiver device", or in some contexts, depending on the usage, as a "display unit," "handheld unit," or "meter"). Relevant information is presented on the receiver unit's display 228.

The applicator 212, container 206, and associated components shown in FIGS. 2A to 2G are illustrated in more detail in FIGS. 3 and 4. In addition, numerous other variations are described in detail below. These alternative embodiments may operate differently insofar as their internal workings, but may present no difference concerning user activity.

Turning to FIG. 3, applicator 212 includes a removable cap 214 and applicator assembly 216. The removable cap 214 can be secured to the applicator assembly 216 via complimentary threadings 306, 306'. In some embodiments, the end (not visible) of the removable cap 214 can include one or more openings. The openings are sealed by a DuPont™ Tyvek®, or other suitable material, seal 308. Such provision allows for ethylene oxide (ETO) sterilization of the applicator 300 through the seal 308 when closed. In some embodiments, the openings in the removable cap 214 may not be present and the removable cap 214 may be made from an ETO

permeable plastic. ETO sterilization is compatible with the electronics within the electronics assembly 310 and with the associated adhesive patch 312, both of which are releasably retained within the applicator assembly 216 until applied to the user. As shown, the applicator assembly 216 includes a housing 314 including integrally formed grip features 316 and a translating sheath or guide sleeve 318.

In reference to FIG. 4, the container 206 includes a cover 402 (*e.g.*, made of a removable foil) and casing 404. Housed within the casing 404 is a desiccant body 412 and a table or platform 408. In some embodiments, the desiccant body 412 can have an annular shape so that the desiccant body 412 can be disposed within the casing 404 and a sensor assembly support (not visible in FIG. 4 but see 512 in FIGS. 5A and 5B) can extend up through the desiccant body 412. This arrangement allows the container 206 to include a desiccant without requiring any additional height to accommodate the desiccant. A sensor assembly 410 is snap-fit or otherwise held by the sensor assembly support 512. The sensor assembly 410 can also be snap-fit or otherwise held by the platform 408 (*e.g.*, using fingers 414). With the cover 402 sealed, the container 206 can be subjected to gamma or radiation (*e.g.*, e-beam) sterilization, an approach compatible with the chemistry of the sensor included in the sensor assembly 410.

Use of different sterilization approaches for the applicator 212 and the container 206 as mentioned above, speaks to the utility of the separate container and applicator design of the present invention. In other words, by separately sealing the container 206 and the applicator 212, the present invention facilitates the use of otherwise incompatible sterilization methods for these two components. For example, ETO sterilization which could damage the

chemistry of the sensor can be used to efficiently and cost effectively sterilize the applicator 212 including the electronics assembly 310 including the adhesive patch 312. Likewise, radiation sterilization which could damage the electronics in the electronics assembly 310 (and/or the adhesive patch 312 used to adhere the electronics assembly 310 to the user's skin) can be used to efficiently and cost effectively sterilize the container 206 including the sensor therein. Still other advantages may exist, given different shelf-life attributes for the active (*i.e.*, electronic, chemical, *etc.*) elements. In some embodiments, all components can be sterilized using the same sterilization technique, such as, but not limited to ETO and e-beam sterilization described above.

In some embodiments, the platform 408 in the container 206 functions as an anti-tamper barrier for the sensor assembly 410 and prevents handling of the sensor assembly 410 by the user. More specifically, the platform 408 is disposed to protect and assist in the retention of the sensor, a sharp, and an associated connector. In some embodiments, the platform 408 is locked in place within the casing 404 until released by a longitudinally directed force from the applicator assembly 216 during the user assembly operation 106 (FIG. 1). In other words, as the guide sleeve 318 of the applicator assembly 216 is inserted down against the platform 408, the sleeve 318 releases a locking mechanism (*e.g.*, a catch) and allows the platform to translate deeper into the casing 404. Additionally, features of the casing 404 can be employed to unlock a guide sleeve lock feature of the applicator assembly 216. In some embodiments, the platform 408 in the container 206 can only be unlocked if the guide sleeve 318 of the applicator assembly 216 is inserted into the container 206 with

alignment marks on the applicator assembly 216 and the container 206 properly aligned. (See FIG. 10C and associated text below).

FIG. 5A is an isometric, cross-sectional view of the casing 404 of FIG. 4. FIG. 5B is an assembled, isometric, cross-sectional view of the container 206 of FIG. 4 including the component parts. As can be seen in Figs 5A and 5B, platform 408 is surrounded by multiple locking features 502 (at least one is advantageously provided in some embodiments). Each of locking features 502 includes a cantilevered arm 504 with a tongue 506 received in a slot or groove 508. So disposed, the platform 408 is locked in place. When the arm(s) 504 are urged inward, in the direction represented by arrows P and P', from a concentrically disposed sleeve 318 (not shown) of the applicator assembly 216 riding over ramp(s) 510, the locking feature(s) 502 are released and the platform 408 can translate in direction B along a longitudinal axis of the combined applicator assembly 216 interfaced with the container 206. The translation of the platform 408 into the casing 404 provides access to sensor assembly 410 by the applicator assembly 216. Until the platform 408 is unlocked and driven down into the casing 404, the sensor assembly 410 is otherwise isolated from being touched or otherwise handled/accessed by a user. In some embodiments, additional detent ramp features can be provided to hold the platform 408 until depressed with force applied by a user. In addition, various key-and-way or slot-and-groove guidance features can be provided to control such motion and ensure that it is smooth and linear (*i.e.*, to avoid platform canting, binding, *etc.*).

In some embodiments, the sleeve/ramp interface with associated locks relies only on detent features to maintain

the platform's position. So configured, inadvertent handling of the sensor assembly can be avoided. The detent(s) can be tuned to require deliberate action to clear the platform 408.

5 In some embodiments, alternative mechanisms and arrangements may be employed to provide a platform 408 that collapses upon application of force via the applicator assembly 216 by the user. For example, FIGS. 6 and 7 depict an alternative container 600 embodiment including an
10 alternative platform 602 arrangement. Here, a collapsible armature or linkage 604 supports the platform 602. This linkage 604 is integrally guided and spring-loaded by virtue of the "living hinge" design of the linkage 604. Alternatively, a coil spring could be employed along with
15 guides for the platform 602. A sleeve 318 of an applicator 216 or the base of sensor mount unit 606 itself, can be used to translate the platform 602 to provide clearance for sensor assembly 608 access and pick-up by the applicator 216 and incorporation as a complete assembled on-body device
20 222. The container 600 includes a casing 610 and can also include a desiccant ring 612 to protect the sensor assembly 608 from moisture.

 Another embodiment for sensor storage and protection is illustrated in FIG. 8 with container 800. Here, casing 802
25 is provided in connection with a support base 804. The support base 804 receives sensor assembly 608 and a frame 806. The frame 806 includes a pivoting door 808. As shown, the support base 804 incorporates three channels 810 for receipt of frame legs 812 to serve as guidance. In its
30 up/closed position shown in FIG. 9A, door 808 protects the sensor assembly 608 from contact by the user. Spiral ramp features interacting between the support base 804 and the frame 806 cause the door 808 to swing open as the frame 806

is moved down as shown in Fig 9B. Likewise, features of the frame 806 can hold the sensor assembly 608 against the support base 804 until the frame 806 is pushed down by user activity.

5 Similar to the container embodiment 206 shown in FIGS. 5A and 5B, the frame 806 in container 800 can be locked in place and released by applicator sleeve introduction. A support ring 902 may lock against boss or tang 814 until the boss 814 is urged inward by the action of an applicator sleeve along angled interface surface 904 of each leg 812. In some embodiments, the legs 812 can be biased outward with a preload but in other embodiments, the locking/unlocking function can operate without such biasing. FIG. 9A illustrates the locked configuration, whereas FIG. 9B illustrates unlocked/translated relation of components.

10 FIGS. 10A to 10N illustrate example details of embodiments of the internal device mechanics of preparing the applicator 212 for use, using the container 206. All together, these drawings represent an example sequence of assembling an on-body device 222 by connecting a sensor assembly 410 stored in the container 206 with an electronics assembly 310 stored in the applicator 212. In addition, the sequence prepares the applicator 212 to apply the assembled on-body device 222 to the user. Modification of such activity for use with the alternative container embodiments (as described above or others) can be appreciated in reference to the same by those with skill in the art.

25 FIGS. 10A and 10B show container 206 and applicator 212 with their constituent parts, along with arrows indicating the manner of cover 402 and cap 214 removal, respectively. Upon peeling off foil cover 402 from the casing 404, the platform 408 within is locked, thus protecting the sensor assembly 410 (not visible but see FIG. 4) which includes a

sensor, a sensor support (also referred to as a plug), a connector, and a sharp. (These components are discussed in detail below.) Likewise, upon removal of cap 214 from the applicator assembly 216, the applicator 212 is locked. As a result of being locked, a guide sleeve 318 (not visible but see FIG. 3) cannot be collapsed into the applicator's housing 314.

In FIG. 10C, applicator assembly 216 is set within container 206. The two components 206, 216 are rotated and advanced until mechanical alignment features M and M' engage, allowing the applicator assembly 216 to register and sit level within the container 206. Visual alignment indicators A and A' assist or guide the user to quickly find the proper alignment position. Note that in some embodiments, the platform 408 cannot be unlocked to translate into the container 206 unless the alignment features M and M' are properly aligned. FIG. 10D depicts the components 206, 216 with the mechanical alignment features M, M' engaged. Sleeve 318 passes over platform 408, with the platform 408 nested concentrically inside the inner diameter of sleeve 318.

Cross-sectional views FIGS. 10E and 10F illustrate the relationship of parts overviewed in FIGS. 10C and 10D. When the sleeve 318 of applicator assembly 216 is seated onto the platform 408 of the container 206 and pushed downward, platform locking features 502 disposed around the platform 408 on locking ribs 1002 are unlocked to allow the platform 408 to translate along a longitudinal axis (labeled "Z") of the interfaced components 206, 216. More specifically, a portion of platform 408 bends and platform locking arms 504 are displaced inward as indicated by arrow P to clear locking grooves 508 in the locking ribs 1002 of casing 404, thus unlocking the platform 408. At this point, the platform

408 is held in place by guide ribs 1004 each providing a detent feature 1006 between the platform 408 and the guide ribs 1004 that can be overcome by further downward pressure applied by the user upon further depression of the applicator assembly 216 in the direction of the longitudinal axis Z.

Turning now to FIGs. 10G and 10H, the dropping of the unlocked platform 418 is illustrated. FIG. 10G depicts further depression of the applicator assembly 216 in the direction of the longitudinal axis Z. The force from the sleeve 318 causes inward, radial deflection of a portion of the platform 408. The effect is that detent arms 1008 are flexed down, inward and away from the detent feature 1006 of guide ribs 1004 as shown. This action releases the platform 418 and the applicator assembly 216 into freefall into the container 206. In some embodiments, the force to flex detent arms 1008, or in other words, the force to overcome the resistance from the detent features 1006, is selected to create a predetermined amount of momentum sufficient to ultimately properly mate the electronics assembly 310 with the sensor assembly 410 and unlock the sleeve 318. In some embodiments, the force to overcome the resistance from the detent features 1006 is from approximately 1 N to approximately 23 N. Other practicable values are possible.

In FIG. 10H, once detent arms 1008 of the platform 418 are past the detent features 1006, a relieve or undercut 1010 in each of the guide ribs 1004 provides increased clearance for the platform 418 to reduce sliding friction as the sleeve 318 and platform 418 slide or telescope further into the container's casing 404 along the longitudinal axis Z (FIG. 10F). Also, one or more flexible grasping arms 1012 previously in contact with the sensor assembly 410, particularly through sharp boss 1014, are moved from a

stabilizing configuration in FIG. 10G to a freed state or configuration in FIG. 10H. In other words, as the platform 418 translates further into the container 206, the sharp boss 1014 of the sensor assembly 410 protrudes through a central opening in the platform 418 and pushes the flexible grasping arms 1012 out of the way.

Turning now to FIGS. 10I and 10J, a cross-sectional view depicting a slightly different cut plane than the prior views is provided to illustrate additional features. In FIG. 10I, sleeve lock arms 1016 are shown engaged with a sleeve lock ledge 1018. This engagement locks the applicator assembly 216 and prevents the sleeve 318 from being able to be retracted or pushed into the housing 314 of the applicator assembly 216. In FIG. 10J, as the applicator assembly 216 is further advanced into the container 206 along the longitudinal axis Z (FIG. 10F), sleeve unlock features 1020 contact and bend the sleeve lock arms 1016 clear of the sleeve lock ledge 1018 thereby unlocking the applicator assembly 216. Note that in the particular example embodiment depicted in FIGS 10I and 10J, the sleeve lock ledge 1018 is formed in a carrier 1022 of the electronics assembly 310.

When the platform 418 bottoms-out in the container 206 as shown in FIG. 10J, the sleeve 318 of the applicator assembly 216 is fully unlocked/released and ready to move. Note that while the sleeve lock arms 1016 are shown flexing outward to unlock, in some embodiments, the sleeve lock arms 1016 can be oriented to flex radially inward to free the elements. The same may hold true for the various locking/unlocking features of the present invention. However, the present arrangement offers advantages in terms of a coordinated whole providing an advantageous form factor and minimized container casing size (a factor that affects

the user experience) in which the carrier 1022 of the electronics assembly 310 is coaxially arranged. Regarding the carrier 1022, it is advantageously designed with unique carrier arm features as detailed in, for example, U.S.

5 Patent Application Serial No. 13/071,461, the disclosure of which is incorporated herein by reference.

In FIGS. 10K and 10L, now that the sleeve 318 of the applicator assembly 216 is fully unlocked, the momentum along the longitudinal axis Z (FIG. 10F) from the force used to overcome the resistance of the detent features 1006 (FIG. 10H) causes three additional concurrent actions. First, even though the sleeve 318 cannot descend any further into the container 206 (since it is in contact with the platform 418 which is bottomed-out), the housing 314 of the applicator assembly 216, the carrier 1022, and the electronics assembly 310 are free to continue to descend into the container 206, now that the sleeve 318 is unlocked as shown in FIG. 10L.

Second, as the electronics assembly 310 descends further along the longitudinal axis Z (FIG. 10F), the sensor assembly 410 is forced into an opening in the electronics assembly 310 which couples the sensor to the electronics and completes assembly of the on-body device 222 (FIG. 2F). In some embodiments, mating snap features on the sensor assembly 410 and the electronics assembly 310 can be used to compel the components to remain locked and compressed together to insure a sealed, reliable connection. As an alternative to mating snap features, in some embodiments, the sensor assembly 410 and the electronics assembly 310 may be coupled by a light press fit or other connection method. However, the positive interaction and lock of snap features is an advantage. So too is the minimal force use to deflect fine locking features that spring back for engagement.

Third, along with the housing 314, the carrier 1022,

and the electronics assembly 310, a sharp retraction assembly 1024 also continues to descend into the container 206 along the longitudinal axis Z (FIG. 10F) and is forced to receive the sharp boss 1014 of the sensor assembly 410.

5 The conical head of the sharp boss 1014 is pushed past a radial arrangement of flexible arms 1026 of the sharp retraction assembly 1024. The flexible arms 1026 bend outwardly, as they are forced to ride against the passing conical surface of the head of the sharp boss 1014. The sharp is thus thereby engaged by the sharp retraction

10 assembly 1024 as the flexible arms 1026 snap back into place once the head of the sharp boss 1014 has passed by, securely grasping the head at the narrowed neck portion of the sharp boss 1014. Note that a base of the sharp boss 1014 may be

15 included to limit insertion into the sharp retraction assembly 1024 through interference with a stop limit or shoulder of the flexible arms 1026. FIG 10K illustrates the arrangement immediately before the above three actions have completed and FIG. 10L illustrates the resulting arrangement

20 immediately after the actions have completed.

In some embodiments, the connection features between the sharp boss 1014 of the sensor assembly 410 and the sharp retraction assembly 1024 can be otherwise configured. For example, the sharp retraction assembly 1024 can include a

25 conical channel formed from a radial arrangement of inwardly biased flexible finger members configured to receive the head of sharp boss 1014 such that once the head has passed through the channel, the flexible fingers conform to the narrowed neck of the sharp boss 1014. With the fingers so

30 conformed, the sharp boss 1014 is captured by the sharp retraction assembly 1024. Retention force is limited only by material strength because the self-energizing lock is not prone to slip between the pieces.

Turning to FIG. 10M, a slightly rotated view, relative to FIG. 10L, is shown. When the sharp boss 1014 is engaged in the sharp retraction assembly 1024, the sensor assembly 410 is coupled to the electronics assembly 310 completing assembly of the on-body-device 222, and the sleeve 318 is unlocked, platform locking arms 504 and detent arms 1008 have engaged undercut grooves 1028 in the container 206, thereby locking the platform 418 in the casing 404. This engagement between the platform 418 and the casing 404 marks the final position of the container 206 from which the loaded applicator assembly 216 is withdrawn for use to apply the on-body device 222 to the user.

Now, once removed from the container 206, the applicator assembly 216 is ready to "fire" as illustrated in FIG. 10N. As such, the applicator assembly 216 is ready to use as in act 108 described in connection with FIG. 2E. Here, the applicator assembly 216 has already been unlocked by interaction with the container 206, and the sensor assembly 410 is coupled to the electronics assembly 310. The sharp 1030 extends from the on-body device 222 which is held in the sleeve 318 of the applicator assembly 216 as shown.

FIGS. 11A to 11F illustrate example details of embodiments of the internal device mechanics of "firing" the applicator assembly 216 to apply the on-body device 222 to a user and including retracting the sharp 1030 safely back into the used applicator assembly 216. All together, these drawings represent an example sequence of driving the sharp 1030 (supporting a sensor coupled to the on-body device 222) into the skin of a user, withdrawing the sharp while leaving the sensor behind in operative contact with interstitial fluid of the user, and adhering the on-body device to the skin of the user with an adhesive. Modification of such activity for use with the alternative applicator assembly

embodiments and components can be appreciated in reference to the same by those with skill in the art.

Turning now to FIG. 11A, a sensor 1102 is supported within sharp 1030, just above the skin 1104 of the user. 5 Rails 1106 (optionally three of them) of an upper guide section 1108 may be provided to control applicator assembly 216 motion relative to the sleeve 318. The sleeve 318 is held by detent features 1110 within the applicator assembly 216 such that appropriate downward force along the 10 longitudinal axis of the applicator assembly 216 will cause the resistance provided by the detent features 1110 to be overcome so that the sharp 1030 and on-body device 222 can translate along the longitudinal axis into (and onto) the skin 1104 of the user. In addition, catch arms 1112 of 15 carrier 1022 engage the sharp retraction assembly 1024 to maintain the sharp 1030 in a position relative to the on-body device 222.

In FIG. 11B, user force is applied to overcome or override detent features 1110 and sleeve 318 collapses into 20 housing 314 driving the on-body device 222 (with associated parts) to translate down as indicated by the arrow L along the longitudinal axis. An inner diameter of the upper guide section 1108 of the sleeve 318 constrains the position of carrier arms 1112 through the full stroke of the 25 sensor/sharp insertion process. The retention of the stop surfaces 1114 of carrier arms 1112 against the complimentary faces 1116 of the sharp retraction assembly 1024 maintains the position of the members with return spring 1118 fully energized.

30 In FIG. 11C, sensor 1102 and sharp 1030 have reached full insertion depth. In so doing, the carrier arms 1112 clear the upper guide section 1108 inner diameter. Then, the compressed force of the coil return spring 1118 drives

angled stop surfaces 1114 radially outward, releasing force to drive the sharp carrier 1120 of the sharp retraction assembly 1024 to pull the (slotted or otherwise configured) sharp 1030 out of the user and off of the sensor 1102 as indicated by the arrow R in FIG. 11D.

With the sharp 1030 fully retracted as shown in FIG. 11E, the upper guide section 1108 of the sleeve 318 is set with a final locking feature 1120. As shown in FIG. 11F, the spent applicator assembly 216 is removed from the insertion site, leaving behind the on-body device 222, and with the sharp 1030 secured safely inside the applicator assembly 216. The spent applicator assembly 216 is now ready for disposal.

Operation of the applicator 216 when applying the on-body device 222 is designed to provide the user with a sensation that both the insertion and retraction of the sharp 1030 is performed automatically by the internal mechanisms of the applicator 216. In other words, the present invention avoids the user experiencing the sensation that he is manually driving the sharp 1030 into his skin. Thus, once the user applies sufficient force to overcome the resistance from the detent features of the applicator 216, the resulting actions of the applicator 216 are perceived to be an automated response to the applicator being "triggered." The user does not perceive that he is supplying additional force to drive the sharp 1030 to pierce his skin despite that all the driving force is provided by the user and no additional biasing/driving means are used to insert the sharp 1030. As detailed above in FIG. 11C, the retraction of the sharp 1030 is automated by the coil return spring 1118 of the applicator 216.

As for further details of the operation, alternative embodiments may be appreciated in view of related approaches

discussed below, others in review of the incorporated subject matter and still more appreciated by those with skill in the art based upon further review of the figures which depict actual hardware produced according to various aspects of the subject disclosure.

Turning to FIGS. 12A to 12D an alternative applicator/container set approach is now described. As shown in FIG. 12A, the container 1200 holds the electronics assembly 1202. This is in contrast to the above embodiments wherein the relationship between the sensor assembly and the electronics assembly was reversed. Upon aligning markers M and M', the applicator 1204 is inserted in the container 1200. In FIG. 12B, the units are merged. In FIG. 12C, the parts are separated. Finally, in FIG. 12D the applicator 1204 is unlocked (e.g., in some embodiments by twisting the sleeve 1206 within the applicator 1204, in some embodiments by the act of loading the electronics assembly 1202 into the applicator 1204, or in some embodiment by the act of removing a locking strip from the sleeve 1206) and ready for use with the assembled on-body device (not visible) including the sensor assembly loaded therein. These various alternative embodiments are illustrated in FIG. 13A to 15F.

FIGS. 13A to 13C variously illustrate use of the applicator 1204 of FIGS. 12A to 12D in connection with a locking-sleeve feature 1206. FIG. 13A shows the sleeve 1206 locked as indicated by the closed window 1208. After twisting the sleeve 1206 relative to the rest of the applicator 1204 to unlock the sleeve 1206, a visual indication (e.g., open window 1208') is seen when the applicator 1204 is ready for use as presented in FIG. 13B. Upon use, as shown in FIG. 13C, the unit is compressed with the sleeve 1206 collapsed into the applicator 1204.

FIGS. 14A and 14B illustrate an alternative applicator

1400 embodiment with a removable locking strip 1402. With the locking strip 1402 in place around the sleeve 1406, the sleeve 1406 cannot be pushed into the applicator 1400. The strip 1402 includes a pull-tab 1404 and adhesive or other
5 fastening member to keep it in place until removed and the applicator 1400 is ready for use.

FIGS. 15A to 15F illustrate preparation of the applicator 1400 of FIGS. 14A and 14B for use with a container 1500. Once the cover 1502 has been removed from
10 the container 1500 and the cap 1506 removed from the applicator 1400, the applicator 1400 is inserted into container 1500 to load the electronics assembly 1504 into the applicator 1400 and mate the sensor assembly (not shown) with the electronics assembly 1504 as shown in FIGs. 15B and
15 15C. Once loaded, the applicator 1400 is removed from the container 1500 as shown in FIG. 15D. FIG. 15E shows the applicator 1400 loaded with the assembled on-body device 222 and ready for sensor/sharp insertion. The locking strip 1404 is removed from the sleeve 1406 and the open ready indicator
20 1208' signals that the applicator 1400 is ready to be used. FIG. 15F illustrates the system after such action has been taken in transferring the on-body device 222 from the applicator 1400 onto the skin of a user.

FIGS. 16A and 16B are sectional and detail to views,
25 respectively, of features of the container 1500 in FIGS. 15A-15F. Specifically, the on-body device 1604 is shown in the container 1500 with an adhesive patch 1602 and its backing 1606. The backing 1606 is spiral-cut and attached to a boss so that when the on-body device 1604 is transferred
30 from the container 1500, the peel-away backing 1606 is left behind. In this fashion, the adhesive patch 1602 remains covered by the backing 1606 so it does not inadvertently adhere to the container 1500.

As an alternative to the spiral peel-around backing approach of FIGS. 16A and 16B, FIGS. 17A and 17B are perspective assembly views illustrating alternative container 1702 configurations for capturing separate peel-off "butterfly" wings or bilateral liner panels from the adhesive-backed patch of the on-body device 1706. In each case, a two-part base 1704 is provided for gripping the peel-away backing liner pieces. Naturally, the base 1704 is adapted to fit in the container casing. In some embodiments, the container 1702 can be configured differently. In the version depicted in FIG. 17A, traction/tread 1708 is provided to assist with grip of the backing. In the version depicted in FIG. 17B, ramps 1710 are provided to assist in removing the backing. In another version, the base can be a one-piece molding incorporating a living hinge in a "clamshell" arrangement. The backing liner piece(s) may be captured along a center line or at an offset location. However configured, the base 1704 may snap into place with complementary band and rib interface features associated with each of the base 1704 and container 1702, snaps, or other features. As with other assemblies described herein, these features may alternatively be press fit, ultrasonically welded or otherwise secured in place.

FIG. 18 is a cross-sectional view illustrating features of the applicator and container sets shown in FIGS. 15A-15F. The embodiment shown in FIG. 18 includes several of the features described in connection with the alternative loading approach above. However, it is simplified in approach. Most notably, the container 1806 includes no active/mobile components. Once the applicator 1800 is pressed down into the container 1806, the on-body device 1808 is assembled (e.g., the sensor assembly is mated with the electronics assembly), released from the container 1806

(*e.g.*, using releasable latches), and held by the applicator 1800 (*e.g.*, using latching arms). This embodiment offers an advantage of not having to expose the adhesive of the on-body device 1808 as in other embodiments. Furthermore, the position of the on-body device 1808 provides a stable surface for the sensor assembly insertion. Other embodiments where the applicator is pre-loaded with the on-body device do provide the advantage of not having to perform the above-described hand-off. Also, the use or inclusion of a protector for the sharp is avoided.

FIGS. 19A and 19B show a sensor assembly 1902 in association with a needle guard 1904. In use, a distal interface feature (*e.g.*, a barb) of the needle guard 1904 is captured by a complimentary split ring or other feature in the container during the assembly of the on-body device. Then, when the applicator is separated from the container, the needle guard 1904 is retained in the container and the sharp is unsheathed. In some embodiments, the needle guard 1904 may be made from polypropylene with a thermoplastic elastomer (TPE) insert to releasably secure the sharp. Other materials may be selected.

Other materials may be selected for construction of other elements of the present invention. For example, the applicator housing may be made of polycarbonate or any other practicable material. The guide sleeve, container, *etc.* may be constructed from acetyl (for reason of lubricity of sliding parts). Any number of the parts may be injected molded, thermoformed or otherwise produced.

Regarding the sensor assembly hand-off to the electronics assembly, FIGS. 20A and 20B illustrate a manner of holding a sensor assembly boss 2006 to the element 2002 that will pick up the electronics assembly 2004 to form the on-body device. Spring armatures 2008 clip to a lip of the

sensor assembly 2006 and hold the sensor assembly 2006 within the applicator during shipping and handling. When the applicator and the container are brought together, lever arms 2010 contact the on-body device 2004, causing the associated spring armatures (or "spring arms") to twist and rotate the connection away from the lip of the sensor assembly, thereby releasing the sensor assembly. A chamfer on the sensor assembly boss can help ensure alignment and proper actuation of the one or more (e.g., three) torqueing spring armatures 2008.

FIGS. 21A-21C illustrate an alternative hand-off approach. In this embodiment, a sensor assembly gripper 2106, with a light snap fit, grabs and orients the sensor assembly 2104 for connection to the electronics assembly 2102. After the sensor assembly 2104 is firmly snapped into the electronics assembly 2102, the sensor assembly gripper 2106 is retracted with an amount of force that overcomes its grip. Such an approach offers simplicity by reducing the number of parts required (given that the snap features may be incorporated in the sharp hub/boss).

Electrical Connections Details

The selection of various hardware options from the above alternative embodiments will depend, at least in part, on the sensor assembly configuration. Sensor assembly configuration, in turn, depends on the mechanism selected for establishing electrical contact between the sensor assembly and the electronics assembly, as well as the method used to seal the contacts. A number of advantageous alternative embodiments are illustrated in FIGs. 22 through 48.

A first example is presented in FIG. 22. Here a sensor 2202 is provided with an elongate "tail" section. The distal portion of the tail is to be inserted through the skin surface guided by a sharp. The proximal portion of the sensor 2202 includes a "flag" type connector region. Three carbon-doped (for conductivity) silicone electrical connectors 2204 are provided to interface with the electrical contacts of the sensor 2202. A split "V" portion of each connector 2204 receives the electrical contacts of the sensor 2202. A flexible nubbin on the opposite side of each connector 2204 is provided for electrical contact with the circuit board incorporated in the electronics assembly. When inserted in a housing 2210, the sensor 2202 and the connector 2204 are advantageously sealed, encased or potted with an adhesive. Epoxy, a UV cure or another type of dielectric (non-conductive) compound may be used. Generally, the compound selected is of such viscosity that it is able to flow around features and fully seal the sensor 2202 within its housing 2210 to avoid leakage. Such an approach avoids contamination and/or current leakage due to fluid intrusion. FIGS. 23A and 23B are perspective assembly and final-assembly cross-sectional views, respectively of the sensor components of FIG. 22. The tail of the sensor 2202 is supported within the sharp 2206 and the sharp 2206 extends through the connector housing 2210. The electrical contacts of the sensor 2202 are seated in the connector 2204 and the assembly is sealed within the housing 2210 including the housing top 2208.

FIGS. 24A and 24B are top and bottom perspective views, respectively of circuit board components to be used with the sensor assembly 2300 of FIGs. 23A and 23B. In each, a custom printed circuit board (PCB) 2402 is shown. The PCB 2402 includes a battery 2406 with mount 2408, an application

specific integrated circuit (ASIC) 2410, or other appropriate processing unit, and various other circuitry, including a thermocouple. On its face, the PCB 2402 includes a housing 2404 with snap features for receiving the sensor assembly 2300 of FIGs. 23A and 23B. On the reverse side of the PCB 2402, heat stakes 2412 show the mode of attaching the housing 2404.

Turning to FIGs 25A and 25B, in some embodiments, the on-body device 2502 is formed by over molding with a polymer "macromelt" (e.g., a thermoplastic hot-melt based on polyamide) or other compound and then affixing an adhesive patch with a releasable liner thereto. A completed on-body device 2502 is provided once fitted with a complimentary sensor assembly 2300, as illustrated in FIGs. 25A and 25B. Internal to such assembly, it may be desirable to include a seal or gasket 2604 as shown in assembly view FIG. 26. As shown in cross section, in FIG. 27A, and magnified in FIG. 27B, the gasket 2604 advantageously includes discrete ring/rim elements to compress and ensure sealing in critical areas, including around each circuit connection/nubbin.

FIGs. 28A-28F illustrate another advantageous sensor 2802 and sensor mount or connector 2804 arrangement. This embodiment resembles the previous approach, but is configured with a bend and a curve imparted to the sensor connection "flag." This permits package and sealing within in a roughly triangular envelope to shorten the length of the connector. Doing so results in a generally more compact sensor assembly body and the ability to downsize all associated components. Yet, it does not significantly complicate manufacture. FIG. 28A depicts the sensor 2802 before it is shaped to fit within the connector 2804. FIG. 28B depicts the bent and curved sensor connection "flag." FIG. 28C depicts the relative orientation of the sensor 2802

as it is inserted into the connector 2804. FIG. 28D depicts a wedge 2806 that is press-fit into the connector 2804 to retain the sensor 2802 and press the connector's electrical contacts against the electrical contacts of the sensor 2802. FIG. 28E depicts the relative orientation of the sharp 2808 as it is inserted into the connector 2804 and FIG. 28F depicts the completed sensor assembly including potting 2810 (e.g., UV potting) used to seal the electrical contacts.

An alternative embodiment is contemplated in connection with the sensor approach illustrated in FIGS. 29A-29D. Using a sensor 2902 with a vertically disposed "flag" connector portion that is supported by coupling 2904, coupling 2904 is configured to snap into connector block 2908 which is attached to PCB 2914. Connector block 2908 includes a connector socket 2910 to receive the contacts portion of the sensor 2902. Connector block 2908 also includes a coupling feature 2912 to receive snap-fit tab 2906 on the coupling 2904 which retains the sensor 2902 in the connector socket 2910.

Another alternative embodiment is contemplated in connection with the sensor approach illustrated in FIGS. 30A-30C. Here, a design is provided that eliminates a connection element and the need for separate spring contacts (be they metal or elastomeric as above). In addition, the approach offers the advantage of effectively converting a sensor with contacts on two sides into a sensor with contacts on a single side after folding. The sensor 3004 shown in FIG. 30A initially has two electrical contacts facing a first direction on the split contact area and one contact facing in a second, opposite direction (obscured by the view). When folded and optionally clamped, glued or otherwise affixed in the orientation shown in FIG. 30B, all of the electrical contacts lie in a single plane, facing the

same direction (e.g., downward in the drawing). Set within a housing (not shown) to restrain and/or seal the sensor 3004, the sensor 3004 is coupled to electrical contacts on the PCB 3002 as shown in FIG. 30C.

5 Such an approach in some embodiments includes a thinner (e.g., lower profile) on-body device relative to the on-body device 3102 variation shown in FIG. 31. The reduced thickness dimension is represented by height H. In FIG. 31, a flag type sensor is shown in a housing with separate
10 electrical connectors. The "stack height" in FIG. 31 includes these connectors as well as the housing. The approach shown in FIG. 30 enables eliminating the connector height above the sensor 3004. Thus, elements are eliminated without losing functionality. Moreover, the elimination of
15 parts reduces cost, and impedance (relative at least to the inclusion of elastomeric connectors as shown in FIG. 22, etc.) between the sensor 3004 and the PCB. Another useful aspect is allowing a sensor with contacts on two sides to connect to the PCB without requiring vias or holes in the
20 sensor, thereby helping with sealing considerations and ease of electrical connection.

 FIGS. 32A and 32B illustrate two additional sensor configurations. In these embodiments, sensors 3202, 3212 with contacts on two sides are split and bent in opposite
25 directions to orient the electrical contacts 3204, 3214 onto a single face or plane. As above, orienting the electrical contacts 3204, 3214 onto a single plane facilitates ease of sealing the electrical connections. Moreover, overall sensor assembly height can be reduced relative to other approaches.
30 Any of conductive adhesives, conductive films and/or mechanical contacts may be used to electrically connect with the sensor contacts so arranged.

FIGS. 33A-33G depict a low-profile multilayer sensor configuration with the electrical contacts all on one side and some details of its construction. FIGS. 33A and 33B illustrate the two sides of this embodiment of a sensor 3300 and its overall shape. The example sensor 3300 includes a tail portion 3302 that is initially supported by a sharp and then disposed within the user's interstitial fluid below the skin upon application of the on-body device. The tail portion 3302 includes electrodes 3304, 3306, 3308 that are used to contact the interstitial fluid and to sense (*e.g.*, transmit and receive) the electrical signals used to measure the analyte concentration within the interstitial fluid. The sensor 3300 also includes an electrical contacts portion 3310 which includes electrical contacts 3312, 3314, 3316 that are disposed all on one side of the sensor 3300 and are in electrical communication with the electrodes 3304, 3306, 3308 via conductive traces (not visible in FIGS. 33A and 33B but see FIG. 33F). Note also that the electrical contacts portion 3310 is shaped to facilitate being securely held and sealed into a connector support that will be described below. For example, the electrical contacts portion 3310 includes tabs 3310A and notches 3310B that allow the electrical contacts portion 3310 to be held securely in the connector support which includes mating features.

The sensor 3300 also includes a bendable portion 3318 that allows the electrical contacts portion 3310 to be arranged parallel to the circuit board of the electronics assembly to facilitate a relatively flat or low profile within the electronics assembly. The bendable portion 3318 also allows the tail portion 3302 to extend down from the electronics assembly so that it can be inserted below the skin of the user while the electrical contacts portion 3310 lays parallel to the circuit board. Lastly, the sensor 3300

includes an armature portion 3320 that allows the sensor 3300 to be held securely to the connector support of the sensor assembly. The armature portion 3320 also provides a leverage point to apply a biasing force to compel the tail portion 3302 into a channel of the sharp as described below in FIG. 35D and the associated text.

FIG. 33C depicts a side view of the sensor 3300. The encircled portion labeled D is shown in more detail in FIG. 33D. FIG. 33D provides a magnified side view of the distal most part of the tail portion 3302 of the sensor 3300. The encircled portion labeled E is shown in more detail in FIG. 33E. FIG. 33E provides an even further magnified view of the electrodes 3304, 3306, 3308 of the tail portion 3302. As can be seen in FIG. 33E, the electrodes 3304, 3306, 3308 are formed as layers on a substrate 3322. The substrate 3322 is made of a flexible, non-conductive dielectric material. In some embodiments, a clear, high-gloss, heat stabilized polyester film may be used for the substrate 3322 and conductive carbon ink can be used to create the trace layers used for the electrodes 3304, 3306, 3308. In other embodiments, other practicable materials may be used for the substrate 3322 such as polymeric or plastic materials and ceramic materials and for the trace layers such as gold. Dielectric layers 3324, 3326, 3328 are disposed between and upon the electrodes 3304, 3306, 3308 to insulate the electrodes 3304, 3306, 3308 from each other. In some embodiments, a ultraviolet (UV) light curable dielectric material may be used for the dielectric layers 3324, 3326, 3328. In other embodiments, other practicable materials may be used. In the particular example embodiment shown, electrode 3304 is a counter electrode, electrode 3306 is a working electrode, and electrode 3308 is a reference electrode. Note that reference electrode 3308 also includes

a secondary conductive layer 3330, e.g., an Ag/AgCl layer. Further details of the arrangement, dimensions, chemistry, and manufacturing methods of the sensor 3300 may be found in U.S. Patent Application No. 13/526,136, entitled "Connectors For Making Connections Between Analyte Sensors And Other Devices," which was filed June 18, 2012, and which is incorporated by reference herein in its entirety and for all purposes.

FIG. 33F depicts a view of the sensor 3300 of FIGS. 33A and 33B including hidden lines representing different layers of electrically conductive trace lines 3332, 3334, 3336 connecting the electrical contacts 3312, 3314, 3316 to the electrodes 3304, 3306, 3308. The electrical contacts 3314, 3316 for the electrodes on the opposite side of the sensor 3300 are coupled to the respective conductive traces 3334, 3336 using vias 3338, 3340 (only two labeled). FIG. 33G is a cross-sectional view of the sensor 3300 taken along line GG of FIG. 33F. As can be seen, conductive trace 3332 covered by dielectric layer 3324 is on one side of the substrate 3322 while conductive traces 3334, 3336 separated by dielectric layer 3326 and covered by dielectric layer 3328 is on the opposite side on the substrate 3322. The electrical contacts 3314, 3316 are accessible via openings in the dielectric layer 3328.

FIGS. 33H to 33J depict three alternative sensor designs 3342, 3344, 3300 side by side for comparison. Notably sensor 3342 includes an aperture 3346 to receive a rivet or other fastener for physical attachment to the PCB of the electronics assembly. Details of sensor 3342 are provided in previously incorporated U.S. Patent Application No. 13/526,136, entitled "Connectors For Making Connections Between Analyte Sensors And Other Devices," which was filed June 18, 2012. Sensors 3344 and 3300 are suitable for use

with the alternative connector arrangements described below with respect to FIGS. 34A-35D.

Turning now to FIGS. 34A-35D, an alternative connector arrangement for connecting a circuit board to a sensor 3300 such as depicted in FIGS. 33A, 33B, and 33J is described. As shown in FIG. 34A, a flexible one-piece seal or connector 3402 is molded in silicone or other practicable elastic material. Separate doped silicone conductive elements are set therein which provide electrical contacts 3410 for connection to a circuit board. In some embodiments, the conductive elements can alternatively be overmolded or insert-molded into place. The result is a generally malleable/flexible hybrid connection and sealing unit or connector 3402 incorporating a living hinge joining two (as-
15 shown) symmetrical sections. Alternatively, a two-piece design is possible. Yet, with the unitary design, the arrangement can be neatly secured using a single catch boss or post 3412 opposite the hinged section. In some
20 embodiments, two or more posts can be used to secure the connector 3402 folded around and sealing both sides of the contacts portion of the sensor 3300. Thus, even if a dielectric coating on the sensor 3300 fails (e.g., pinhole leaks), the connector 3402 insures that the sensor contacts 3312, 3314, 3316 are protected from moisture or any
25 contaminants. The one-piece design also facilitates assembly as illustrated, in which the flexible connector 3402 is set in a rigid or semi-rigid housing or connector support 3404 with one side located on the post 3412. Then a sensor 3300 is inserted, and bent approximately ninety degrees at the
30 bendable portion 3318 of the sensor 3300. Once bent, the sensor 3300 is then captured with the upper part of the connector 3402 by folding over the connector 3402 as indicated by arrow S in FIG. 34C. The connector 3402 is

illustrated as bilaterally symmetrical, however, the connector 3402 can be formed in a direction-specific orientation because in some embodiments, certain of the electrical contacts 3410 may not be necessary. In some
5 embodiments, all the sensor's electrical contacts 3312, 3314, 3316 can be provided on a single side of the sensor 3300 or, in other embodiments, both sides of the sensor 3300.

As shown in FIG. 34D, in some embodiments, the top
10 surface of the connector 3402 includes a raised lip 3418 disposed at the top surface edge of the connector 3402 that encircles the electrical contacts 3410 of the connector 3402. The raised lip 3418 can be integrally formed in the elastomeric material that forms the connector 3402 and is
15 thus compressible when the sensor assembly is inserted into the electronics assembly. Alternatively, the raised lip can be embodied as gasket or o-ring on the top surface of the connector 3402. The raised lip 3418 functions to ensure that a seal is formed around the electrical contacts 3410 of the
20 connector 3402 and the electrical contacts of the PCB before any electrical connectivity between the sensor and the electronics assembly is established. Thus, the raised lip 3418 provides a failsafe against a short by insuring the order of assembly includes creating a seal and then creating
25 electrical connectivity as the sensor assembly is mated with the electronics assembly.

In any case, with the sensor 3300 captured within the seal 3402, a sharp 3408 is then introduced, with its hub 3414 contacting the connector support 3404 as shown in FIG.
30 34D. FIG. 35A illustrates the orientation of the sharp 3408 prior to the insertion of the sharp 3408 into the connector support 3404. FIGS. 35B and 35C provide a cross-sectional overview of the relationship of the sharp 3408 to the sensor

3300. Notably, once inserted in the connector support 3404, the sharp 3408 surrounds and supports the tail portion 3302 of the sensor 3300. In FIG. 35D, further details of the sensor configuration are visible. Particularly, biasing features are shown that abut surfaces of the connector support 3404 in order to center and bias the sensor 3300 into the channel of the sharp 3408. Specifically, armature portion 3320 abuts the surface at arrow 3502 of the connector support 3404 which causes the biasing feature 3508 to act as a fulcrum at arrow 3504 to push the tail portion 3302 of the sensor 3300 into the sharp 3408 at arrow 3506.

In some embodiments, the curved section 3508 of the sensor 3300 can overlie a corresponding surface of the connector support 3404 to help limit the insertion depth (*i.e.*, provide a depth stop) for the sensor 3300. Sensor 3300 vertical placement, including insertion depth, is also controlled based on the relationship between the seal 3302 halves. As noted with respect to the other sensor assembly housings/supports discussed herein, the sensor assembly of FIG. 35C can also include various clip or snap features for its precise associations with a socket in the electronics assembly within the on-body device.

A related arrangement to that described in connection with FIGS. 34A-34D and 35A-35D is presented in FIGS. 36 to 38. In FIG. 36, a sensor 3300 with all electrical contacts on the same side is shown with a sharp 3602 for insertion in a connector support 3604. The connector support 3604 includes an elastomeric (*e.g.*, silicone) seal backing. Once such a sensor assembly set is in a container (or alternatively in an applicator), the sensor assembly can be coupled to the sensor electronics to form an on-body device 222. As shown in FIG. 37, the sensor assembly 3702 is shaped to fit within a socket 3704 that includes a second

elastomeric unit with electrical contacts in the elastomer body of the socket 3704. Note that in FIG. 37, the enclosure of the electronics assembly is not shown so that the socket can be more clearly displayed. The socket 3704 is affixed to a circuit board 3706 via any practicable method. The socket 3704 and/or the connector support 3604 can include various coupling features (e.g., a snap fit lip and hook arrangement) to ensure that the electrical contacts are pressed tightly together and sealed within the socket 3704 and sensor assembly 3702. Once the sensor assembly 3702 is received within the socket 3704, the on-body device (e.g., with the complete over-mold enclosure around the circuit board 3706 and adhesive patch 3802 as shown in FIG. 38) is ready for use.

Notably, the electrical contacts/connector approaches described above are "directional." In other words, before the sensor assembly is mated with the electronics assembly, the two are aligned relative to each other both longitudinally and rotationally. In some embodiments, the coupling arrangement is "non-directional" and the sensor assembly can be mated with the electronics assembly without aligning the two rotationally. For example, the sensor assembly construction shown in FIGS. 39A and 39B offers such an approach. Separate conductive (e.g., optionally metal) bands 3904 mounted on a core support 3906 connect to sensor electrical contacts 3908 as shown in FIGS. 39A and 39B. The assembled unit (i.e., the sensor assembly 3910), with sharp 3902 in place, is received in the socket of an electronics assembly 4002 to form an on-body device as illustrated in FIG. 40. In some embodiments, brush-type connectors 4004 on the circuit board in the electronics assembly 4002 reach up to the individual levels of the conductive bands 3904. Such a sensor assembly 3910 can be inserted into the socket of

the electronics assembly 4002 in any radial/rotational orientation.

A "reversed" approach is illustrated in the sensor assembly 4100 of FIGS. 41A-41C. Here, the circuit board 4102
5 includes a socket connector 4104 that has an arrangement of stacked conductive elastomeric O-rings 4106 disposed within the inner diameter of the socket connector 4104. A sensor support 4108 is adapted to hold the electrical contacts 4110 of the sensor 4112 in a corresponding stack facing radially
10 outward. When the sensor support 4108 is inserted into the socket connector 4104, the conductive elastomeric O-rings 4106 align vertically with the electrical contacts of the sensor as shown in FIG 41B (with the socket connector 4104 not shown so that the conductive elastomeric O-rings 4106
15 are more clearly visible) and in the cross-sectional view of FIG. 41C. In some embodiments, the electrical contacts of the sensor 4110 can be formed by rolling up a sensor with contacts all on the same side or using the oppositely directed folding/rolling approach shown in connection with
20 FIG. 30 - but oriented vertically. Other approaches may be utilized as well. In any case, the electrical contacts of the sensor subtend less than 360 degrees while the conductive elastomeric O-rings on the circuit board provide a multi-level encircling relationship. As with the approach
25 associated with FIGS. 39A to 40, such a sensor assembly 4100 can be inserted into the socket connector 4104 of the electronics assembly 4102 in any radial/rotational orientation.

The sensor connections associated with the circuit
30 board 4404 in the embodiment shown in FIGS. 42 to 44 are arranged in concentric rings. The sensor 4202 includes electrical contacts 4204 held within housing member 4206 and base 4208. The electrical contacts 4204 include "micro-

spring" wireform connectors. These springs provide compliance as well as a discrete top loop. Each electrical contact 4204 is disposed at a different radial distance from the center corresponding to a different concentric
5 conductive track 4304 on a circuit board coupling 4302. Thus, no matter the rotational orientation of the sensor assembly 4200 relative to the circuit board coupling 4302, the electrical contacts 4204 of the sensor 4202 align with the correct concentric conductive tracks 4304. Very fine
10 wire can be used for the springs, thus producing an easily miniaturized system.

Turning now to Figs 45A and 45B, another non-directional sensor assembly connection approach that can be employed with a concentric electronics assembly connection
15 is depicted. As illustrated in the isometric top and bottom views of Figs 45A and 45B, a sensor 4504 bent approximately ninety degrees with contacts positioned along different radial paths or arcs, connects with conductive elastomeric contacts 4508 supported by two opposing discs 4502, 4506.
20 Two of the elastomeric contacts 4508 are set on one disc 4506, and a third, configured to pass through a sensor via, is set on the other disc 4502. As shown in FIG. 46A, this sensor assembly 4500 can then be received by a circuit board coupling 4604 which includes concentric tracks for
25 connecting the radially disposed conductive elastomeric contacts 4508 of the sensor assembly 4500 to the circuit board 4606. The enclosure 4608 snap fits or is otherwise adhered to (e.g., using adhesive/welding) a base supporting the circuit board 4606. The as-assembled on-body device 4600
30 is depicted in FIG. 46B.

Turning now to FIGS. 47A to 47C, an alternative sensor assembly/electronics assembly connection approach is illustrated. As shown, the sensor assembly 4702 includes

sensor 4704, connector support 4706, and sharp 4708. Notably, sensor assembly 4702 does not include a separate connector or seal to enclose the sensor's connectors within the connector support 4706 as in the embodiment depicted in FIGS. 34A to 34D (*i.e.*, no seal 3402). Instead, a recess 4710 formed directly in the enclosure of the electronics assembly 4712 includes an elastomeric sealing member 4714 (including conductive material coupled to the circuit board and aligned with the electrical contacts of the sensor 4704). Thus, when the sensor assembly 4702 is snap fit or otherwise adhered to the electronics assembly 4712 by driving the sensor assembly 4702 into the integrally formed recess 4710 in the electronics assembly 4712, the on-body device 4714 depicted in FIG. 47C is formed. This embodiment provides an integrated connector for the sensor assembly 4702 within the electronics assembly 4712.

On-body device Construction Details

Certain elements of the on-body device fabrication may apply to any or all of the above electrical connection configurations. FIGS. 48A-48D provide top (FIG. 48A) and bottom (FIG. 48B-48D) construction views of an exemplary on-body device subassembly. A socket 4802 or mount is fit through vias in a printed circuit board 4800 along with other associated components including a processor 4804 (*e.g.*, an ASIC including a communications facility), thermistor/thermocouple 4806, a battery mount 4808, *etc.* Once the circuit board 4800 has been populated with these components as shown in FIGS. 48C, the socket 4802 is adhered to the circuit board 4802 (*e.g.*, using heat stakes). Once a battery 4810 is set in place, the circuit board 4800 as shown in FIG. 47E is prepared for incorporation into an on-body device.

The circuit board 4800 is ready for an over-mold process or other sealing method. As illustrated in FIGS. 49A-49D, the circuit board 4800 is first set in the two-piece mold 4902, 4904. With the mold slide 4906 inserted and mold 4902, 4904 closed as shown in FIG. 49B. As depicted in FIG. 49C, a macromelt material is injected into the mold 4902, 4904, encasing the circuit board 4800. The mold 4902, 4904 is opened and the near-final part ejected as shown in FIG. 49D.

Alternatively, the enclosure of the electronics assembly of the on-body device 222 may comprise elements snap-fit (or welded/adhered) together as illustrated in the assembly view of FIG. 50A, the as-assembled view of FIG. 50B, and in cross-sectional perspective view of FIG. 50C. An enclosure including a top shell 5002 and a mounting base 5004 can be used to sealably enclose and protect the circuit board 4800. When snap-fit, various interference or snap fit elements (e.g., annular rims 5006) may be provided around the entirety of the periphery of the enclosure or as discrete snap-fit connectors (not shown). Notably, such an approach may benefit from additional O-ring sealing elements to avoid fluid intrusion. Alternatively or additionally, adhesive set at the snap junction(s) may be used to ensure good sealing, especially in connection with continuous annular snap-fit features 5006. As seen in FIG. 50C, a trough 5008 or other features can be provided to insure that adhesive 5010 that may be squeezed out during assembly is not forced into areas that could interfere with operation or assembly of the on-body device 222. In some embodiments, when the a top shell 5002 and a mounting base 5004 are fit together with a bead of adhesive 5010 in place as shown, the trough 5008 not only provides space to capture the adhesive

5010 squeezed out but also provides additional surface area for a thicker layer of adhesive 5010 to seal the joint.

However constructed, final assembly of the electronics assembly of on-body device 222 involves adhesive patch installation. An exemplary approach is illustrated in FIGS. 51A-51C. First, a double-sided adhesive patch 5104 has the inner liner 5102 removed. This exposed adhesive is set over the on-body device body 5106 (with the temperature sensor 4806 folded to seat within a complimentary pocket) and adhered with a first window 5108 aligned for temperature sensing and second window 5110 for sensor assembly receipt. As such, it is ready for placement in an applicator assembly upon removal of the outer release liner, or alternatively ready for placement in a container with or without the outer liner in place, depending on the presence or absence of any liner-puller features provided therein.

Various other modifications and alterations in the structure and method of operation of the embodiments of the present disclosure will be apparent to those skilled in the art without departing from the scope and spirit of the present disclosure. Although the present disclosure has been described in connection with certain embodiments, it should be understood that the present disclosure as claimed should not be unduly limited to such embodiments. It is intended that the following claims define the scope of the present disclosure and that structures and methods within the scope of these claims and their equivalents be covered thereby.

C O N C L U S I E S

1. Toestel voor het in positie rangschikken van een sensor voor een analyt, het toestel omvattende:

- 5 - een eerste samenstel omvattende een eerste deel van een on-body inrichting;
 - een tweede samenstel omvattende een tweede deel van de on-body inrichting;
 - een applicatorsamenstel dat losmaakbaar gekoppeld is
10 aan het eerste samenstel;

waarin het toestel uitgevoerd is zodat bij het in positie rangschikken van de sensor de eerste en tweede delen met elkaar gekoppeld worden.

- 15 2. Toestel volgens conclusie 1, verder omvattende een container voor het tweede samenstel, waardoor de container losmaakbaar gekoppeld is aan het tweede samenstel.

3. Toestel volgens conclusie 2, waarin het
20 applicatorsamenstel verplaatsbaar is in de container teneinde het tweede samenstel los te maken en terug te brengen van de container en om het eerste samenstel te koppelen met het tweede samenstel om de on-body inrichting te vormen.

- 25 4. Toestel volgens één van de voorafgaande conclusies, omvattende een scherp element dat inbrengbaar is in een gebruiker van de sensor wanneer de on-body inrichting in positie gerangschikt is.

- 30 5. Toestel volgens conclusie 4, waarin het scherpe element is opgenomen in het tweede samenstel.

6. Toestel volgens één van de voorafgaande conclusies, waarin het eerste samenstel een elektronicasamenstel met elektronica voor een sensor is.
- 5 7. Toestel volgens één van de voorafgaande conclusies, waarin het tweede samenstel een sensorsamenstel met een sensor is.
8. Toestel volgens conclusie 7, waarin de sensor op het
10 scherpe element ondersteund wordt.
9. Toestel volgens één van de voorafgaande conclusies 4-8, waardoor in antwoord op kracht die aangebracht wordt op het applicatorsamenstel langs een longitudinale as, het
15 applicatorsamenstel inklapbaar is langs de longitudinale as om het scherpe element dat de sensor van de on-body inrichting ondersteunt, door de huid van de gebruiker in de richting langs de longitudinale as te verplaatsen.
- 20 10. Toestel volgens conclusie 9, waardoor het inklappen van het applicatorsamenstel het losmaken van de on-body inrichting van het applicatorsamenstel mogelijk maakt.
11. Toestel volgens conclusie 9 of 10, waardoor het
25 inklappen van het applicatorsamenstel de hechting van de on-body inrichting aan de huid van de gebruiker mogelijk maakt.
12. Toestel volgens één van de conclusies 9-11, waardoor het inklappen van het applicatorsamenstel de terugtrekking
30 mogelijk maakt van het scherpe element in het applicatorsamenstel teneinde de sensor in de gebruiker achter te laten.

13. Toestel volgens één van de voorafgaande conclusies 8-12, waarin het applicatorsamenstel een geïsoleerde binnenruimte omvat die gedefinieerd is door een omhulling alsmede een drager van het eerste samenstel en waarin het scherpe element geheel opgenomen is in de binnenruimte 5 wanneer dit in het applicatorsamenstel is teruggetrokken.

14. Toestel volgens één van de voorafgaande conclusies 6-13, waarin het eerste samenstel een elektronicasamenstel is 10 met sensorelektronica en een de sensorelektronica omgevende omhulling, waarbij de sensorelektronica een processor en een communicatiefaciliteit omvat; en waarin het tweede samenstel de sensor, het scherpe element dat de sensor ondersteunt, een steunstructuur en een connector omvat, waarbij de 15 connector gekoppeld is aan de sensor en koppelbaar is aan de sensorelektronica, waarbij de steunstructuur de connector en sensor ondersteunt en het scherpe element op losmaakbare wijze ondersteunt.

20 15. Toestel volgens één van de voorafgaande conclusies, waarin het applicatorsamenstel vergrendelbaar is in een uitgeklapte positie en inklapbaar is langs een longitudinale as van het applicatorsamenstel tot in een onvergrendelde teruggetrokken positie.

25

16. Toestel volgens conclusie 15, waarin de container een applicatorsamenstelontgrendelmechanisme omvat om het applicatorsamenstel te ontgrendelen.

30 17. Toestel volgens conclusie 16, waarin in antwoord op kracht die aangebracht wordt op het applicatorsamenstel langs de longitudinale as die het uitgeklapte, vergrendelde applicatorsamenstel in de container verplaatst, het

applicatorsamenstel het sensorsamenstel losmaakt en terugbrengt, het elektronicasamenstel koppelt aan het sensorsamenstel teneinde een on-body inrichting te vormen die losmaakbaar gehouden wordt binnen in het applicatorsamenstel en het applicatorsamenstel ontgrendelt.

18. Toestel volgens één van de voorafgaande conclusies 6-17, waarin de container een platform omvat voor het tweede samenstel, welk platform transleerbaar is tussen een initiële en gecomprimeerde positie.

19. Toestel volgens conclusie 18, waarin het platform vergrendelbaar is in de initiële positie en werkzaam is om ontgrendeld te worden door het applicatorsamenstel teneinde te translereen naar de gecomprimeerde positie in antwoord op de kracht die aangebracht wordt op het applicatorsamenstel langs de longitudinale as die het uitgeklapte, vergrendelde applicatorsamenstel verplaatst naar de container, en om het sensorsamenstel los te maken bij het bereiken van de gecomprimeerde positie.

20. Toestel volgens conclusie 18 of 19, waarin het platform een sensorsamenstelgeleidingsfeature omvat dat werkzaam is om het sensorsamenstel naar het elektronicasamenstel te sturen onafhankelijk van de algemene oriëntatie van het toestel.

21. Toestel volgens één van de conclusies 14-20, waarin de binnen in de steunstructuur geplaatste sensor een voorspanningsfeature omvat dat werkzaam is om de sensor voor te spannen in het scherpe element terwijl het scherpe element en de sensor door de huid van de gebruiker verplaatst worden.

22. Toestel volgens één van de conclusies 6-21, waarin de sensorelektronica ten minste een elektronisch contact omvat en het sensorsamenstel een steunstructuur omvat die een
5 compressiefeature omvat dat werkzaam is om een connector van het sensorsamenstel te comprimeren en af te dichten ten opzichte van het ten minste ene elektronische contact.

23. Toestel volgens één van de voorafgaande conclusies 9-
10 22, waarin de container geleidingsfeatures omvat om de verplaatsing van het applicatorsamenstel in de container te sturen en een arreterfeature dat een hoeveelheid weerstand verschaft tegen de kracht die aangebracht wordt op het applicatorsamenstel langs een longitudinale as die het
15 applicatorsamenstel in de container verplaatst teneinde te verzekeren dat wanneer deze eenmaal overwonnen is het sensorsamenstel verplaatst wordt tot in en gehuisvest wordt in het elektronicasamenstel door een resulterende translatie van het elektronicasamenstel in het applicatorsamenstel.

20

24. Toestel volgens één van de conclusies 9-23, waarin het applicatorsamenstel geleidingsfeatures omvat teneinde het applicatorsamenstel mogelijk te maken om langs de
longitudinale as ingeklapt te worden en een arreterfeature
25 dat een hoeveelheid weerstand biedt tegen de kracht die aangebracht wordt op het applicatorsamenstel langs de longitudinale as waarbij het applicatorsamenstel tegen een gebruiker gehouden wordt teneinde te verzekeren dat wanneer deze eenmaal overwonnen is het scherpe element en de sensor
30 tot in de gebruiker verplaatst worden door een resulterende translatie van de on-body inrichting in het applicatorsamenstel.

25. Toestel volgens één van de voorafgaande conclusies 6-24, waarin het elektronicasamenstel gesteriliseerd wordt gebruikmakend van een eerste werkwijze, het sensorsamenstel gesteriliseerd wordt gebruikmakend van een tweede werkwijze, 5 het elektronicasamenstel incompatibel is met de tweede werkwijze voor sterilisatie en het sensorsamenstel incompatibel is met de eerste werkwijze van sterilisatie.

26. Toestel volgens één van de voorafgaande conclusies, 10 waarin het applicatorsamenstel een geleidingshoes omvat die vergrendelbaar is in een uitgeklapte positie en transleerbaar is langs een longitudinale as van het applicatorsamenstel tot in de teruggetrokken positie wanneer dit ontgrendeld is en waarin de container een 15 geleidingshoesontgrendelfeature omvat dat gerangschikt is om de geleidingshoes van het applicatorsamenstel te ontgrendelen.

27. Toestel volgens conclusie 26, waarin het platform 20 vergrendelbaar is in de initiële positie en werkzaam is om ontgrendeld te worden door de geleidingshoes van het applicatorsamenstel teneinde te transleren naar de gecomprimeerde positie in antwoord op de kracht die aangebracht wordt op het applicatorsamenstel langs de 25 longitudinale as die de uitgeklapte, vergrendelde geleidingshoes tot in de container verplaatst en om het sensorsamenstel los te maken bij het bereiken van de gecomprimeerde positie.

30 28. Toestel volgens conclusie 27, waarin het platform een sensorsamenstelgeleidingsfeature omvat dat werkzaam is om het sensorsamenstel te sturen tot in het

elektronicasamenstel, onafhankelijk van de algehele oriëntatie van het toestel.

29. Toestel volgens één van de conclusies 14-28, waarin de
5 sensorelektronica ten minste één elektronisch contact omvat en de steunstructuur een compressiefeature omvat dat werkzaam is om de connector te comprimeren en af te dichten ten opzichte van het ten minste ene elektronische contact.

10 30. Toestel volgens één van de conclusies 26-29, waarin de container geleidingsfeatures omvat om translatie van de geleidingshoes te sturen.

31. Toestel volgens één van de conclusies 26-30, waarin het
15 applicatorsamenstel geleidingsfeatures omvat om het de geleidingshoes mogelijk te maken om tot in het applicatorsamenstel te transleren.

32. Een on-body inrichting, rangschikbaar in positie door
20 middel van het toestel volgens één van de voorafgaande conclusies, waarbij de on-body inrichting omvat:

- een eerste samenstel omvattende een eerste deel van de on-body inrichting, waarbij het eerste deel bij voorkeur een elektronicasamenstel is met sensorelektronica, bij
25 voorkeur verder een omhulling omvat die de sensorelektronica omgeeft, waarbij de sensorelektronica een processor en een communicatiefaciliteit omvat, en

- een tweede samenstel omvattende een tweede deel van de on-body inrichting, waarbij het tweede deel bij voorkeur
30 een sensorsamenstel is omvattende een sensor en bij voorkeur verder een scherp element omvat dat de sensor ondersteunt, een steunstructuur, en een connector die gekoppeld is aan de sensor en koppelbaar is aan de sensorelektronica, waarbij de

steunstructuur de connector en sensor ondersteunt en het scherpe element op losmaakbare wijze ondersteunt.

33. On-body inrichting volgens conclusie 32, waarin het
5 elektronicasamenstel losmaakbaar gekoppeld is met een applicatorsamenstel dat bij voorkeur een geleidingshoes omvat die vergrendelbaar is in een uitgeklapte positie en werkzaam is om te transleren langs een longitudinale as van het applicatorsamenstel tot in een teruggetrokken positie
10 wanneer deze ontgrendeld is, de geleidingshoes omvattende een elektronicasamenstel een ontkoppelfeature dat gerangschikt is om het elektronicasamenstel los te maken van het applicatorsamenstel waarin de geleidingshoes zich in de teruggetrokken positie bevindt,
15 waarin het sensorsamenstel losmaakbaar gekoppeld is met een container en een geleidingshoes ontgrendelfeature omvat dat gerangschikt is om de geleidingshoes van het applicatorsamenstel te ontgrendelen, waarin in antwoord op een eerste kracht op het
20 applicatorsamenstel langs een longitudinale as die de uitgeklapte, vergrendelde geleidingshoes tot in de container verplaatst, het applicatorsamenstel werkzaam is om het sensorsamenstel los te maken en terug te brengen van de container, om het elektronicasamenstel te koppelen aan het
25 sensorsamenstel teneinde de on-body inrichting te vormen die losmaakbaar gehouden wordt binnen in het applicatorsamenstel, om de afdichtbare omhulling af te dichten met de steunstructuur en de geleidingshoes te ontgrendelen, en
30 waarin in antwoord op een tweede kracht op het applicatorsamenstel langs een longitudinale as met de uitgeklapte, ontgrendelde geleidingshoes tegen een gebruiker gehouden, het applicatorsamenstel werkzaam is om het de

uitgeklapte, ontgrendelde geleidingshoes mogelijk te maken om te transleren langs de longitudinale as tot in de teruggetrokken positie, om het scherpe element en de sensor van de on-body inrichting door de huid van de gebruiker in de richting langs de longitudinale as te verplaatsen, om de on-body inrichting los te maken van het applicatorsamenstel wanneer de geleidingshoes de teruggetrokken positie bereikt; om de on-body inrichting te hechten aan de huid van de gebruiker, en om het scherpe element terug te trekken tot in het applicatorsamenstel waarbij de sensor in de gebruiker achterblijft en de on-body inrichting afgedicht wordt tegen vocht.

34. On-body inrichting volgens conclusies 32 of 33, welke samenstelbaar is binnen een applicator in antwoord op een kracht die wordt uitgeoefend op de applicator en die aangebracht wordt op een gebruiker in antwoord op een volgende kracht die op de applicator wordt aangebracht.

35. Applicatorsamenstel volgens één van de conclusies 1-31, voor een on-body inrichting, bij voorkeur de on-body inrichting volgens één van de voorafgaande conclusies 32-42, waarbij de applicator omvat:

- een behuizing omvattende integraal gevormde greepfeatures;
- een verwijderbare kap die te koppelen is met de behuizing en werkzaam is om de applicator af te dichten;
- een elektronicasamenstelretentiesteun die is gekoppeld aan de behuizing en werkzaam is om op losmaakbare wijze een elektronicasamenstel te houden omvattende sensorelektronica, een geleidingshoes die vergrendelbaar is in een uitgeklapte positie deels binnen de behuizing en werkzaam is om langs een longitudinale as van de applicator

te transleren tot in een teruggetrokken positie wanneer dit ontgrendeld is, de geleidingshoes omvattende een elektronicasamenstelontkoppelfeature dat gerangschikt is om het elektronicasamenstel vrij los te maken van de applicator
5 wanneer de geleidingshoes zich in de teruggetrokken positie bevindt; en

- een scherp element terugtrekkingssamenstel binnen in de behuizing werkzaam om een scherp element te verwijderen van een sensorsamenstel wanneer de geleidingshoes de
10 teruggetrokken positie bereikt.

36. Applicatorsamenstel volgens conclusie 35, waarin de geleidingshoes omvat een proximaal en een distaal einde, waarbij het distale einde een eerste distaal vlak
15 definieert, waarin de elektronicasamenstelretentiesteun een tweede distaalvlak definieert en waarin het tweede distale vlak zich dichterbij het proximale einde van de geleidingshoes bevindt dan het eerste distale vlak wanneer de geleidingshoes zich in de uitgeklapte positie bevindt.

20
37. Applicatorsamenstel volgens conclusie 35 of 36, waarin in antwoord op een kracht die aangebracht wordt op de applicator langs de longitudinale as die de uitgeklapte, vergrendelde geleidingshoes verplaatst tot in een container die op oplosbare wijze het sensorsamenstel vasthoudt, de applicator werkzaam is om het sensorsamenstel los te maken en terug te brengen van de container, om het elektronicasamenstel te koppelen met het sensorsamenstel teneinde een on-body inrichting te vormen die losmaakbaar gehouden wordt
25 binnen de applicator, om de afdichtbare omhulling af te dichten met de steunstructuur en om de geleidingshoes te ontgrendelen door gebruik te maken van het
30

geleidingsshoesontgrendelfeature dat gerangschikt is in de container.

38. Applicatorsamenstel volgens conclusie 37, waarin in
5 antwoord op een opvolgende kracht die aangebracht wordt op
de applicator langs de longitudinale as met de uitgeklapte,
ontgrendelde geleidingsshoes die tegen een gebruiker gehouden
wordt, de applicator werkzaam is om het de geleidingsshoes
mogelijk te maken om te transleren langs de longitudinale as
10 tot in de teruggetrokken positie, om het scherpe element en
de sensor van de on-body inrichting door de huid van de
gebruiker in de richting langs de longitudinale as te
verplaatsen, de on-body inrichting los te maken van de
applicator wanneer de geleidingsshoes de teruggetrokken
15 positie bereikt, om de on-body inrichting te hechten aan de
huid van de gebruiker en om het scherpe element tot in de
applicator terug te trekken waarbij de sensor in de
gebruiker achterblijft en de on-body inrichting afgedicht
wordt van vocht.

20

39. Applicatorsamenstel volgens conclusie 38, waarin het
eerste distale vlak zich dichterbij het proximale einde van
de geleidingsshoes bevindt dan het tweede distale vlak
wanneer de geleidingsshoes zich in de teruggetrokken positie
25 bevindt.

40. Container volgens 1-31, waarbij de container omvat een
sensorsamenstel omvattende een sensor, geconfigureerd voor
gebruik met een applicator volgens één van de conclusies 35-
30 38.

41. Werkwijze voor het rangschikken van de sensor, zoals
een analytische sensor in een positie op een subject,

gebruikmakend van een toestel volgens één van de voorafgaande conclusies 1-31.

42. Werkwijze volgens conclusie 41, omvattende de stappen
5 van:

- het aanbrengen van een kracht op een applicatorsamenstelling langs een longitudinale as van het applicatorsamenstel teneinde een geleidingshoes van het applicatorsamenstel te verplaatsen tot in een
10 container die op losmaakbare wijze een sensorsamenstel vasthoudt, waarbij het sensorsamenstel omvat een sensor, een scherp element dat de sensor ondersteunt, een steunstructuur en een connector die gekoppeld is met de sensor, waarbij de steunstructuur de connector
15 en sensor ondersteunt en het scherpe element op losmaakbare wijze ondersteunt,
- het bevestigen van een platform dat het sensorsamenstel vasthoudt in de container met de geleidingshoes om het sensorsamenstel los te maken;
- 20 - het koppelen van een elektronicasamenstel dat losmaakbaar gehouden wordt binnen in het applicatorsamenstel aan het sensorsamenstel om een on-body inrichting te vormen;
- het afdichten van een omhulling die de sensor-
25 elektronica binnen in het elektronica samenstel omgeeft, met steunstructuur van het sensorsamenstel, waarbij de sensorelektronica een processor en een communicatiefaciliteit omvat;
- het ontgrendelen van de geleidingshoes van het
30 applicatorsamenstel gebruikmakend van een geleidingshoesontgrendelfeature gerangschikt binnen in de container teneinde het de geleidingshoes mogelijk te maken om getransleerd te worden langs de longitudinale

as van het applicatorsamenstel vanaf een uitgeklapte positie naar een teruggetrokken positie, waarbij de geleidingshoes een elektronicasamenstel ontkoppelfeature omvat gerangschikt om het

5 elektronicasamenstel van het applicatorsamenstel los te maken wanneer de geleidingshoes zich in de teruggetrokken positie bevindt;

- het verwijderen van het applicatorsamenstel omvattende de on-body inrichting van de container;

10 - het aanbrengen van een tweede kracht op het applicatorsamenstel langs de longitudinale as met de uitgeklapte, ontgrendelde geleidingshoes tegen een gebruiker gehouden;

15 - het dwingen van de uitgeklapte, onvergrendelde geleidingshoes om te transleren langs de longitudinale as naar de teruggetrokken positie;

- het verplaatsen van het scherpe element en de sensor van de on-body inrichting door de huid van de gebruiker in de richting langs de longitudinale as;

20 - het losmaken van de on-body inrichting van het applicatorsamenstel wanneer de geleidingshoes de teruggetrokken positie bereikt;

- het hechten van de on-body inrichting aan de huid van de gebruiker; en

25 - het terugtrekken van het scherpe element tot in het applicatorsamenstel waarbij de sensor in de gebruiker achterblijft en de on-body inrichting afgedicht wordt van vocht.

30 43. Werkwijze volgens conclusie 42, waarin het koppelen van het elektronicasamenstel binnen in het applicatorsamenstel aan het sensorsamenstel omvat het koppelen van de connector aan de sensorelektronica.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 2G

212 ↘





FIG. 3

206 ↘




FIG. 4




FIG. 5A

206 ↘




FIG. 5B





FIG. 6



600




FIG. 7

800 ↘




FIG. 8




FIG. 9A




FIG. 9B

206 ↘




FIG. 10A

212 ↘




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 10G




FIG. 10H




FIG. 10I




FIG. 10J




FIG. 10K




FIG. 10L




FIG. 10M




FIG. 10N




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14A




FIG. 14B




FIG. 15A






FIG. 15B




FIG. 15C





FIG. 15D




FIG. 15E




FIG. 15F




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19A




FIG. 19B




FIG. 20A




FIG. 20B




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 22




FIG. 23A




FIG. 23B




FIG. 24A




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28A



FIG. 28B




FIG. 28C




FIG. 28D




FIG. 28E




FIG. 28F




FIG. 29A




FIG. 29B




FIG. 29C




FIG. 29D




FIG. 30A




FIG. 30B




FIG. 30C




FIG. 31




FIG. 32A




FIG. 32B




FIG. 33A




FIG. 33B




FIG. 33C

FIG. 33D

FIG. 33E




FIG. 33F




FIG. 33G




FIG. 33H




FIG. 33I




FIG. 33J




FIG. 34A




FIG. 34B





FIG. 34C




FIG. 34D





FIG. 35A




FIG. 35B





FIG. 35D




FIG. 36




FIG. 37




FIG. 38




FIG. 39A




FIG. 39B




FIG. 40




FIG. 41A




FIG. 41B








FIG. 41C







FIG. 45A




FIG. 45B




FIG. 46A




FIG. 46B




FIG. 47A




FIG. 47B




FIG. 47C




FIG. 48A




FIG. 48B




FIG. 48C




FIG. 48D




FIG. 48E




FIG. 49A




FIG. 49B




FIG. 49C




FIG. 49D




FIG. 50A




FIG. 50B




FIG. 50C




FIG. 51A




FIG. 51B




FIG. 51C

SAMENWERKINGSVERDRAG (PCT)

RAPPORT BETREFFENDE NIEUWHEIDSONDERZOEK VAN INTERNATIONAAL TYPE

IDENTIFICATIE VAN DE NATIONALE AANVRAGE	KENMERK VAN DE AANVRAGER OF VAN DE GEMACHTIGDE	
	E/2NP13/CAR/26	
Nederlands aanvraag nr.	Indieningsdatum	
2009963	11-12-2012	
	Ingeroepen voorrangsdatum	
	11-12-2011	
Aanvrager (Naam)		
Abbott Diabetes Care Inc.		
Datum van het verzoek voor een onderzoek van internationaal type	Door de Instantie voor Internationaal Onderzoek aan het verzoek voor een onderzoek van internationaal type toegekend nr.	
23-03-2013	SN 59740	
I. CLASSIFICATIE VAN HET ONDERWERP (bij toepassing van verschillende classificaties, alle classificatiesymbolen opgeven)		
Volgens de internationale classificatie (IPC)		
A61B5/00	A61B5/155	A61B5/145
II. ONDERZOCHE GEBIEDEN VAN DE TECHNIEK		
Onderzochte minimumdocumentatie		
Classificatiesysteem	Classificatiesymbolen	
IPC	A61B	
Onderzochte andere documentatie dan de minimum documentatie, voor zover dergelijke documenten in de onderzochte gebieden zijn opgenomen		
III.	<input type="checkbox"/>	GEEN ONDERZOEK MOGELIJK VOOR BEPAALDE CONCLUSIES (opmerkingen op aanvullingsblad)
IV.	<input checked="" type="checkbox"/>	GEBREK AAN EENHEID VAN UITVINDING (opmerkingen op aanvullingsblad)

**ONDERZOEKSRAPPORT BETREFFENDE HET
RESULTAAT VAN HET ONDERZOEK NAAR DE STAND
VAN DE TECHNIEK VAN HET INTERNATIONALE TYPE**

Nummer van het verzoek om een onderzoek naar
de stand van de techniek
NL 2009963

<p>A. CLASSIFICATIE VAN HET ONDERWERP INV. A61B5/00 A61B5/155 A61B5/145 ADD.</p>	
<p>Volgens de Internationale Classificatie van octrooien (IPC) of zowel volgens de nationale classificatie als volgens de IPC.</p>	
<p>B. ONDERZOCHE GEBIEDEN VAN DE TECHNIEK</p>	
<p>Onderzochte minimum documentatie (classificatie gevolgd door classificatiesymbolen) A61B</p>	
<p>Onderzochte andere documentatie dan de minimum documentatie, voor dergelijke documenten, voor zover dergelijke documenten in de onderzochte gebieden zijn opgenomen</p>	
<p>Tijdens het onderzoek geraadpleegde elektronische gegevensbestanden (naam van de gegevensbestanden en, waar uitvoerbaar, gebruikte trefwoorden) EPO-Internal, BIOSIS, EMBASE, WPI Data</p>	
<p>C. VAN BELANG GEACHTE DOCUMENTEN</p>	
<p>Categorie °</p>	<p>Geciteerde documenten, eventueel met aanduiding van speciaal van belang zijnde passages</p>
<p>X</p>	<p>EENHEID VAN UITVINDING ONTBREEKT zie aanvullingsblad B ----- WO 2011/015659 A1 (UNOMEDICAL AS [DK]; GYRN STEFFEN [DK]) 10 februari 2011 (2011-02-10) * bladzijde 21; figuren 1A,3A,4A,4B * * bladzijde 15, laatste alinea *</p>
<p>A</p>	<p>WO 2008/014792 A1 (UNOMEDICAL AS [DK]; GYRN STEFFEN [DK]; MATHIASSEN ORLA [DK]) 7 februari 2008 (2008-02-07) * figuren 1,2 *</p>
	<p>----- -/--</p>
<p><input checked="" type="checkbox"/> Verdere documenten worden vermeld in het vervolg van vak C.</p>	<p><input checked="" type="checkbox"/> Leden van dezelfde octroofamilie zijn vermeld in een bijlage</p>
<p>° Speciale categorieën van aangehaalde documenten</p> <p>*A* niet tot de categorie X of Y behorende literatuur die de stand van de techniek beschrijft</p> <p>*D* in de octrooiaanvraag vermeld</p> <p>*E* eerdere octrooi(aanvraag), gepubliceerd op of na de indieningsdatum, waarin dezelfde uitvinding wordt beschreven</p> <p>*L* om andere redenen vermelde literatuur</p> <p>*O* niet-schriftelijke stand van de techniek</p> <p>*P* tussen de voorrangsdatum en de indieningsdatum gepubliceerde literatuur</p>	<p>*T* na de indieningsdatum of de voorrangsdatum gepubliceerde literatuur die niet bezwarend is voor de octrooiaanvraag, maar wordt vermeld ter verheldering van de theorie of het principe dat ten grondslag ligt aan de uitvinding</p> <p>*X* de conclusie wordt als niet nieuw of niet inventief beschouwd ten opzichte van deze literatuur</p> <p>*Y* de conclusie wordt als niet inventief beschouwd ten opzichte van de combinatie van deze literatuur met andere geciteerde literatuur van dezelfde categorie, waarbij de combinatie voor de vakman voor de hand liggend wordt geacht</p> <p>*&* lid van dezelfde octroofamilie of overeenkomstige octrooipublicatie</p>
<p>Datum waarop het onderzoek naar de stand van de techniek van internationaal type werd voltooid</p> <p>12 augustus 2013</p>	<p>Verzenddatum van het rapport van het onderzoek naar de stand van de techniek van internationaal type</p>
<p>Naam en adres van de instantie</p> <p>European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016</p>	<p>De bevoegde ambtenaar</p> <p>Clevorn, Jens</p>

**ONDERZOEKSRAPPORT BETREFFENDE HET
 RESULTAAT VAN HET ONDERZOEK NAAR DE STAND
 VAN DE TECHNIEK VAN HET INTERNATIONALE TYPE**

Nummer van het verzoek om een onderzoek naar
 de stand van de techniek
NL 2009963

C.(Vervolg). VAN BELANG GEACHTE DOCUMENTEN

Categorie °	Geciteerde documenten, eventueel met aanduiding van speciaal van belang zijnde passages	Van belang voor conclusie nr.
X	US 2008/064944 A1 (VANANTWERP NANNETTE M [US] ET AL) 13 maart 2008 (2008-03-13) * alineas [0036], [0037] * -----	1,2,4-9, 18,20, 30,32, 40,41
X	US 2010/022863 A1 (MOGENSEN LASSE W [DK] ET AL) 28 januari 2010 (2010-01-28) * figuren 21a-c, 22-27 * -----	1,2,4-9, 18,20, 30,32, 40,41
A	US 2011/290645 A1 (BRISTER MARK [US] ET AL) 1 december 2011 (2011-12-01) * alineas [0229] - [0230] * -----	1,2,4-9, 18,20, 30,32, 40,41

GEBREK AAN EENHEID VAN UITVINDING

Octrooiaanvraag Nr.:

SN 59740
NL 2009963

AANVULLINGSBLAD B

De Instantie belast met het uitvoeren van het onderzoek naar de stand van de techniek heeft vastgesteld dat deze aanvraag meerdere uitvindingen bevat, te weten:

1. conclusies: 1-9, 18-20, 23, 26-28, 30, 32, 33, 40-43

een container voor het tweede samenstel, waardoor de container losmaakbaar gekoppeld is aan het tweede samenstel

2. conclusies: 10-13, 15-17, 24, 31, 34-39

het inklappen van het applicatorsamenstel het losmaken van de on-body inrichting van het applicatorsamenstel mogelijk maakt

3. conclusies: 14, 21, 22, 25, 29

het eerste samenstel een elektronicasamenstel is met sensorelektronica en een de sensorelektronica omgevende omhulling, waarbij de sensorelektronica een processor en een communicatiefaciliteit omvat; en waarin het tweede samenstel de sensor, het scherpe element dat de sensor ondersteunt, een steunstructuur en een connector omvat, waarbij de connector gekoppeld is aan de sensor en koppelbaar is aan de sensorelektronica, waarbij de steunstructuur de connector en sensor ondersteunt en het scherpe element op losmaakbare wijze ondersteunt

Het vooronderzoek werd tot het eerste onderwerp beperkt.

**ONDERZOEKSRAPPORT BETREFFENDE HET
RESULTAAT VAN HET ONDERZOEK NAAR DE STAND
VAN DE TECHNIEK VAN HET INTERNATIONALE TYPE**

Informatie over leden van dezelfde octrooifamilie

Nummer van het verzoek om een onderzoek naar
de stand van de techniek

NL 2009963

In het rapport genoemd octrooigescrift	Datum van publicatie	Overeenkomend(e) geschrift(en)	Datum van publicatie
WO 2011015659	A1	10-02-2011	AU 2010280713 A1 02-02-2012
			CA 2766961 A1 10-02-2011
			CN 102548598 A 04-07-2012
			EP 2461853 A1 13-06-2012
			JP 2013500805 A 10-01-2013
			KR 20120047896 A 14-05-2012
			US 2012184909 A1 19-07-2012
			WO 2011015659 A1 10-02-2011

WO 2008014792	A1	07-02-2008	AU 2007280851 A1 07-02-2008
			CA 2659077 A1 07-02-2008
			CN 101500626 A 05-08-2009
			EP 2046420 A1 15-04-2009
			JP 2009545342 A 24-12-2009
			KR 20090037471 A 15-04-2009
			RU 2009107031 A 10-09-2010
			US 2010004597 A1 07-01-2010
			WO 2008014792 A1 07-02-2008

US 2008064944	A1	13-03-2008	CA 2291105 A1 17-12-1998
			DE 69837006 T2 22-11-2007
			DK 0987982 T3 04-06-2007
			EP 0987982 A1 29-03-2000
			JP 4065575 B2 26-03-2008
			JP 2002503988 A 05-02-2002
			US 5954643 A 21-09-1999
			US 6368141 B1 09-04-2002
			US 2002119711 A1 29-08-2002
			US 2004193025 A1 30-09-2004
			US 2008064944 A1 13-03-2008
WO 9856293 A1 17-12-1998			

US 2010022863	A1	28-01-2010	AU 2007256561 A1 13-12-2007
			CA 2653631 A1 13-12-2007
			EP 2023818 A2 18-02-2009
			JP 2009539438 A 19-11-2009
			KR 20090026760 A 13-03-2009
			US 2010022863 A1 28-01-2010
WO 2007140783 A2 13-12-2007			

US 2011290645	A1	01-12-2011	GEEN



File No. SN59740	Filing date (<i>day/month/year</i>) 11.12.2012	Priority date (<i>day/month/year</i>) 11.12.2011	Application No. NL2009963
International Patent Classification (IPC) INV. A61B5/00 A61B5/155 A61B5/145			
Applicant Abbott Diabetes Care, Inc.			

This opinion contains indications relating to the following items:

- Box No. I Basis of the opinion
- Box No. II Priority
- Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- Box No. IV Lack of unity of invention
- Box No. V Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- Box No. VI Certain documents cited
- Box No. VII Certain defects in the application
- Box No. VIII Certain observations on the application

	Examiner Clevorn, Jens
--	---------------------------

WRITTEN OPINION

Application number

NL2009963

Box No. I Basis of this opinion

1. This opinion has been established on the basis of the latest set of claims filed before the start of the search.
2. With regard to any **nucleotide and/or amino acid sequence** disclosed in the application and necessary to the claimed invention, this opinion has been established on the basis of:
 - a. type of material:
 - a sequence listing
 - table(s) related to the sequence listing
 - b. format of material:
 - on paper
 - in electronic form
 - c. time of filing/furnishing:
 - contained in the application as filed.
 - filed together with the application in electronic form.
 - furnished subsequently for the purposes of search.
3. In addition, in the case that more than one version or copy of a sequence listing and/or table relating thereto has been filed or furnished, the required statements that the information in the subsequent or additional copies is identical to that in the application as filed or does not go beyond the application as filed, as appropriate, were furnished.
4. Additional comments:

WRITTEN OPINION

Application number

NL2009963

Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability

The questions whether the claimed invention appears to be novel, to involve an inventive step, or to be industrially applicable have not been examined in respect of

- the entire application
- claims Nos. 10-17, 21, 22, 24, 25, 29, 31, 34-39

because:

- the said application, or the said claims Nos. relate to the following subject matter which does not require a search (*specify*):
- the description, claims or drawings (*indicate particular elements below*) or said claims Nos. are so unclear that no meaningful opinion could be formed (*specify*):
- the claims, or said claims Nos. are so inadequately supported by the description that no meaningful opinion could be formed (*specify*):
- no search report has been established for the whole application or for said claims Nos. 10-17, 21, 22, 24, 25, 29, 31, 34-39
- a meaningful opinion could not be formed as the sequence listing was either not available, or was not furnished in the international format (WIPO ST25).
- a meaningful opinion could not be formed without the tables related to the sequence listings; or such tables were not available in electronic form.
- See Supplemental Box for further details.

Box No. IV Lack of unity of invention

1. The requirement of unity of invention is not complied with for the following reasons:

see separate sheet

2. This report has been established in respect of the following parts of the application:

- all parts.
- the parts relating to claims Nos. (see Search Report)

WRITTEN OPINION

Application number

NL2009963

Box No. V Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty	Yes: Claims	3, 19, 23, 26-28, 33, 42, 43
	No: Claims	1, 2, 4-9, 18, 20, 30, 32, 40, 41
Inventive step	Yes: Claims	3, 19, 23, 26-28, 33, 42, 43
	No: Claims	1, 2, 4-9, 18, 20, 30, 32, 40, 41
Industrial applicability	Yes: Claims	1-9, 18-20, 23, 26-28, 30, 32, 33, 40-43
	No: Claims	

2. Citations and explanations

see separate sheet

Re Item IV

Lack of unity of invention

D1 (WO2011015659) discloses

Toestel voor het in positie rangschikken van een sensor voor een analyt, het toestel omvattende:

- een eerste (sensor 72) samenstel omvattende een eerste deel van een on-body inrichting;
- een tweede samenstel (base 1) omvattende een tweede deel van de on-body inrichting;
- een applicatorsamenstel (inserter 80) dat losmaakbaar gekoppeld is aan het eerste samenstel (step 2; page 21); waarin het toestel uitgevoerd is zodat bij het in positie rangschikken van de sensor de eerste en tweede delen met elkaar gekoppeld worden (before insertion, sensor 72 sensor must at least be slidable in opening 12C in figure 1A, since the sensor cannula, as shown in figure 3A, is inserted into the skin only after placement of the base on the skin. After insertion using the inserter, the sensor is coupled in position to the base 1, see also description of figures 4A-B).

Reference is also made to D2 (WO2008014792). This document discloses the inserter for the sensor used in D1 (see D1, page 15, last paragraph). D2 (e.g. figures 1, 2) discloses that a cannula holding part (5) is positioned within the inserters (1) and after deployment is positioned on the base plate (10).

The subject-matter of claim 1 is thus not novel and inventive and cannot be the basis for a common inventive concept.

The special technical feature of the first claimed invention (claims 1-9, 18-20, 23, 26-28, 30, 32-33, 40-43) is "een container voor het tweede samenstel, waardoor de container losmaakbaar gekoppeld is aan het tweede samenstel". The objective problem can thus be seen in avoiding contamination of the second part.

The special technical feature of the second claimed invention (claims 10-13, 15-17, 24, 31, 34-39) is that "het inklappen van het applicatorsamenstel het losmaken van de on-body inrichting van het applicatorsamenstel mogelijk maakt". The objective problem can thus be seen in providing the applicator with further functions during the insertion movement.

The special technical feature of the third claimed invention (claims 14, 21-22, 25, 29) is that "het eerste samenstel een elektronicasamenstel is met sensorelektronica en een de sensorelektronica omgevende omhulling, waarbij

de sensorelektronica een processor en een communicatiefaciliteit omvat; en waarin het tweede samenstel de sensor, het scherpe element dat de sensor ondersteunt, een steunstructuur en een connector omvat, waarbij de connector gekoppeld is aan de sensor en koppelbaar is aan de sensorelektronica, waarbij de steunstructuur de connector en sensor ondersteunt en het scherpe element op losmaakbare wijze ondersteunt". The objective problem can thus be seen in an alternative for distributing the sensor electronics on the different components.

In conclusion, the groups of claims are not linked by common or corresponding special technical features and define different inventions not linked by a single general inventive concept. The application, hence does not meet the requirements of unity of invention.

Re Item V

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

Reference is made to the following documents:

- D1 WO 2011/015659 A1 (UNOMEDICAL AS [DK]; GYRN STEFFEN [DK]) 10 februari 2011 (2011-02-10)
- D2 WO 2008/014792 A1 (UNOMEDICAL AS [DK]; GYRN STEFFEN [DK]; MATHIASSEN ORLA [DK]) 7 februari 2008 (2008-02-07)
- D3 US 2008/064944 A1 (VANANTWERP NANNETTE M [US] ET AL) 13 maart 2008 (2008-03-13)
- D4 US 2010/022863 A1 (MOGENSEN LASSE W [DK] ET AL) 28 januari 2010 (2010-01-28)
- D5 US 2011/290645 A1 (BRISTER MARK [US] ET AL) 1 december 2011 (2011-12-01)

- 1 The present application does not meet the criteria of patentability, because the subject-matter of claims 1, 32, 40 and 41 is not new.

(
1.1 D1 discloses the subject-matter of these claims, as discussed above.

1.2 D3 (US2008064944) discloses

Toestel voor het in positie rangschikken van een sensor voor een analyt, het toestel omvattende:

- een eerste (30) samenstel omvattende een eerste deel van een on-body inrichting;
- een tweede samenstel (20) omvattende een tweede deel van de on-body inrichting;
- een applicatorsamenstel (80, 14) dat losmaakbaar gekoppeld is aan het eerste samenstel (paragraph 37) ;waarin het toestel uitgevoerd is zodat bij het in positie rangschikken van de sensor de eerste en tweede delen met elkaar gekoppeld worden (paragraph 36; parts 20 and 30 are coupled and thus fixed in position relative to each other. This can be done holding the first part 30 with the applicator wings 82 and coupling it to the second part 20, see paragraph 37).

The subject-matter of claim 1 is thus not novel.

1.3 D4 (US2010022863) likewise discloses the subject-matter of claim 1 (embodiments of figures 21a-c and figures 22-27).

2 As to the dependent claims

2.1 Dependent claims 2, 4-9, 18, 20 and 30 do not appear to contain any additional features which meet the requirements of patentability with respect to novelty and/or inventive step.

A container as such to avoid contamination is a normal design option.