




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : H05B 6/80</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/22886</p> <p>(43) International Publication Date: 20 April 2000 (20.04.00)</p>
<p>(21) International Application Number: PCT/EP99/07661</p> <p>(22) International Filing Date: 12 October 1999 (12.10.99)</p> <p>(30) Priority Data: 9803512-4 15 October 1998 (15.10.98) SE</p> <p>(71) Applicant (for all designated States except US): WHIRLPOOL CORPORATION [US/US]; 2000 M 63, Benton Harbor, MI 49022 (US).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): NYRÉN, Gunnar [SE/SE]; Smedstugegatan 14, S-602 13 Norrköping (SE). BRAUNISCH, Eckart [SE/SE]; Kimstadsvägen 29, S-610 20 Kimstad (SE).</p> <p>(74) Agent: GUERCI, Alessandro; Whirlpool Europe s.r.l., V. le G. Borghi 27, I-21025 Comerio (IT).</p>		<p>(81) Designated States: AU, BR, CN, JP, KR, SK, TR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report.</i></p>

(54) Title: MICROWAVE OVEN WITH BROWNING DEVICE

(57) Abstract

A microwave oven for heating foodstuffs, comprising an oven cavity (4), a loading zone for the foodstuffs arranged in the oven cavity, a microwave unit for feeding microwaves to the oven cavity, and a browning device (13) having a radiation means (17) for generating infrared (IR) radiation. The browning device also comprises a reflector (16) adapted to reflect IR radiation essentially towards the loading zone. At least a surface layer of the reflector is made of a non-metallic, reflective and heat-resisting material.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MICROWAVE OVEN WITH BROWNING DEVICEField of the Invention

The present invention relates to a microwave oven for heating foodstuffs with a browning device according to the preamble to claim 1.

5 Background Art

Microwave ovens for heating foodstuffs which are provided with a browning device are already available. The browning device serves to give the foodstuffs a browned surface while the essential heating is achieved
10 by microwaves that are fed to the foodstuffs from a microwave unit. As a rule, the browning device consists of an omnidirectional radiation means which generates infrared (IR) radiation combined with a metal reflector for directing IR radiation towards the foodstuffs.

15 The grill element is conventionally arranged in a grill bulge outside the oven cavity to prevent the microwave pattern in the cavity from being interfered with. To permit the IR radiation to leave the grill bulge, an opening in the wall of the cavity must be arranged,
20 through which microwave radiation can unfortunately leak from the cavity.

Swedish patent application 9700280-2 discloses a device and a method for preventing microwave radiation from leaking through the grill bulge, by the grill bulge
25 and its connection opening being formed as a waveguide with such dimensions that its properties in respect of microwave propagation are such as to allow the space to be essentially free of microwaves.

Browning devices with reflectors are usually pro-
30 vided with a protection means protecting against fat splashing from the foodstuffs since fat deposited on the reflector essentially deteriorates its reflectance of IR radiation and a larger amount of IR radiation will be absorbed by the surface. The increased absorption results

in an increased temperature of the reflector, which in turn leads to a further deterioration of the reflectance. The protection means in front of the browning device is usually designed as a grating placed between the reflector and the oven cavity. The grating can be designed to absorb IR radiation from the grill element such that it obtains a high temperature. This results in the formation of a hot zone round the grating where the fat is burnt, thus avoiding that the fat deposits on the reflector and consequently deteriorates its reflectance.

A drawback of the grating is that an increased power of the browning device is required to compensate for the power drop in the protective grating. This increased power consumption should be added to the high consumption of power of the browning device as it is. Moreover, the ovens that are presently available frequently require two browning devices to obtain sufficient IR radiation efficiency.

Increased power of the browning device means that the power consumption of the oven increases and that the power supply need be reinforced and also that more power must be cooled away, which places greater demands on the cooling system. This results in the ovens becoming more expensive.

A further problem is the leaking of microwave radiation from the oven cavity to the grill bulge, which has not been completely eliminated by the prior art solutions.

One more problem is that the connection opening between the grill bulge and the oven cavity interferes with the field pattern of the oven cavity.

There is thus a need for providing a microwave oven with a grill element having a lower consumption of power, where the browning device is designed in such manner that its negative effect on the microwaves in the oven cavity is reduced and the heat loss is reduced.

Summary of the Invention

An object of the present invention is to provide a microwave oven with a grill element, whose negative effect on the function of the microwave oven is reduced.

5 A further object of the present invention is to provide a microwave oven with a reduced consumption of power, a reduced need for cooling, the leakage of microwave radiation from the cavity being reduced as well.

10 These objects are achieved by a device of the type mentioned by way of introduction, which has the features defined in claim 1. Further preferred features of the inventive device are recited in the dependent claims.

A basic idea of the invention is to use a heat-resisting material for the reflector.

15 By using a browning device with a reflector which has at least a surface layer of a non-metallic, heat-resisting, reflective material, the distance between the radiation means and the reflector can be made considerably smaller than in the case where metallic reflectors are used, and thus also the browning device can be made smaller. According to the invention use is preferably made of a material which retains its reflective properties at a temperature of typically at least 500°C, and preferably at least 800°C.

25 Moreover the reflector can be designed so as to achieve a generally improved directive efficiency. It can thus be avoided that direct radiation from the radiation means falls on the door of the microwave oven. Using a metal reflector, the necessarily great distance between the reflector and the radiation means would result in the browning device being huge to make the geometry such that the direct radiation from the radiation means does not fall on the door of the oven.

35 According to one aspect of the invention, a browning device is provided, which essentially illuminates the loading zone by the radiation means being placed in a reflector which is designed to screen off radiation from

the radiation means such that it does not fall on the door of the oven. The reflector has a concave surface with an opening. Radiation from the radiation means will be spread at an angle after having passed the opening.

5 The angle depends on the distance between the opening and the radiation means.

The reflector is designed with two preferably essentially parallel sides and a suitably rounded base. This design of the reflector is favourable from the viewpoint
10 of manufacture and results in relatively good reflective properties. By the reflector being made narrow and deep compared with today's reflectors, the possibilities of screening off direct radiation from the radiation means will be improved.

15 According to one aspect of the present invention, the browning device is arranged at the rear edge of the top of the oven cavity. This arrangement makes the browning device well protected from being mechanically affected in spite of a favourable IR radiation.

20 According to a further aspect of the present invention, an arrangement of the browning device at the rear edge of the top of the oven cavity, furthest away from the door, is combined with an arrangement of the food-stuffs on a rotary plate. Preferably, the reflector is
25 designed such that the maximum radiation intensity of the rotary plate is to be found outside the centre and preferably midway between the centre of the rotary plate and its rear edge. As the plate rotates, the average radiation intensity will essentially be uniform over the entire
30 surface of the rotary plate.

In case the radiation source is extended, only part of the radiation from the radiation source will be screened off in certain directions. The intensity of the direct radiation falling on the rotary plate depends on
35 the one hand on the distance to the radiation source and, on the other hand, on the amount of radiation that has been screened off. Preferably, the design and position of

the browning device is arranged such that the surface on which radiation from the entire radiation means falls is to be found in the rear part of the oven cavity. The surface on which direct radiation from the entire radiation means falls is also defined by the fact that there is a straight line that does not pass any obstacle from each point of the surface to each point of the radiation means.

Alternatively, the browning device can be arranged at the front edge of the top of the oven cavity closest to the door, in which case the surface on which direct radiation from the entire radiation means falls is positioned between the centre and the front edge of the rotary plate.

According to one more aspect of the invention, the browning device is arranged in a grill bulge with a connection opening to the oven cavity. By placing the reflector adjacent to the radiation means, its dimensions can be small. With small dimensions of the reflector, the connection opening can be narrow, which results in a reduced leakage of microwave radiation from the oven cavity to the grill bulge and further out of the oven.

The grill bulge is advantageously arranged above the top of the oven cavity at the rear edge thereof furthest away from the door.

If the entire reflector is made of a non-metallic material, the reflector can be placed in the oven cavity without the microwaves in the oven cavity being affected to a considerable extent.

According to a further aspect of the present invention, use is made of a material at least in a reflective surface layer such that it reflects at least 50% and preferably 70% of the incident radiation.

High reflectivity is achieved according to one aspect of the invention by at least a surface layer of the reflector being made of compacted fibres or grains, of a dielectric material having a high refractive index

for IR radiation. The refractive index of the dielectric material is at least 1.5 and preferably above 2 for IR radiation. The essential thing is that the reflector comprises a large number of surfaces in which refraction or reflection occurs. A similar result can be achieved by having a plurality of small particles having a high refractive index spread in a material having a lower refractive index, or small particles having a low refractive index in a material having a higher refractive index. Spreading in the small particles will then be achieved.

According to one aspect of the invention, at least a surface layer of the reflector is essentially made of calcium oxide, calcium sulphate, silica, barium sulphate, zirconium oxide or titanium oxide.

According to one aspect of the invention, the surface layer of the reflector is essentially made of a mixture of a selection of calcium oxide, calcium sulphate, silica, barium sulphate, zirconium oxide and titanium oxide.

In a mixture of a selection of calcium oxide, calcium sulphate, silica, barium sulphate and titanium oxide, it is possible that also some other substance is included to improve the mechanical properties of the surface layer.

By using, according to the invention, a radiation means having a temperature of between 1100°C and 1700°C and preferably between 1300°C and 1500°C, an increased radiation yield will be obtained compared with the case in which a lower temperature is used. By increasing the temperature from the normally employed temperature 800°C, it is thus possible to reduce the radiating surface of the radiation means with the radiated power retained. Consequently, the dimensions of the radiation means can be reduced, and moreover only one browning device is necessary to achieve sufficient power. Thus, an inventive device will have great advantages although the somewhat

shorter wavelength from a radiation means having a high temperature produces a somewhat poorer grilling result.

A high temperature of the filament is produced according to one aspect of the invention by using a
5 halogen bulb, a quartz tube or the like.

According to a further aspect of the invention, use is made of a material having a low thermal conductivity to reduce the thermal conduction to the casing. This reduces the cooling requirement and also gives the ad-
10 vantage that the temperature of the surface of the reflector can be kept high, which results in fat splashing onto the reflector being burnt off. This results in a self-cleaning function and no protective grating is required, which entails reduced power loss. The reflector
15 surface should have a temperature of at least 500°C for the self-cleaning effect to be optimal.

An unexpected and surprising advantage of having a reflector surface with poor thermal conductivity is that the reflector obtains a high temperature, which makes it
20 function as an IR radiator, which results in an increased radiation yield since the radiation absorbed in the reflector partially radiates back. The somewhat lower temperature of the reflector compared with the temperature of the radiation means results in the wavelength of
25 the radiation from the reflector being in a range which is favourable in terms of grilling.

The above aspects can, of course, be combined in the same embodiment.

In the following, detailed exemplifying embodiments
30 of the invention will be described with reference to the Figures.

Brief Description of the Drawings

Fig. 1 is a perspective view in cross-section of a
35 microwave oven comprising a browning device which has a ceramic reflector arranged in a grill bulge according to an embodiment of the present invention.

Fig. 2 is a detailed view of a reflector in accordance with an embodiment of the present invention.

Fig. 3 is a cross-sectional view of an oven cavity of a microwave oven comprising a browning device which has a ceramic reflector according to an embodiment of the present invention.

Description of Preferred Embodiments

Fig. 1 illustrates a microwave oven 1 according to a preferred embodiment of the present invention. The microwave oven has a casing 2, a control panel 3 and an oven cavity 4 arranged in the casing. A rotary plate 5 which is a loading zone is arranged on the base of the oven cavity. The plate is rotatable in the direction of arrow 6. One side of the oven cavity consists of a door 7, which closes the cavity during cooking. The microwave oven is also provided with a microwave source 8 for generating microwaves with a frequency of 2.45 GHz and microwave feed means 9 for feeding the microwaves into the oven cavity. By said feed means, the microwaves are fed through two feed openings 10 and 11 arranged in one side wall 12 of the cavity. A browning device 13 is arranged on the top 14 of the oven cavity at the rear wall 15 of the cavity. The browning device comprises a reflector 16 and a radiation means 17 which has a certain extent. The browning device 13 is arranged in a metallic grill bulge 18 on the top of the oven cavity. Between the grill bulge and the oven cavity there is a connection opening 19 (Fig. 2). The connection opening is of an elongate shape adapted to the browning device and has two parallel sides and is arranged with its long sides essentially in parallel with the door. The connection opening has a width which is smaller than half the wavelength of the microwaves. As a result, there will be essentially no leakage of microwave radiation from the oven cavity to the grill bulge. The browning device is arranged at the rear edge of the oven cavity, such that a rotating food-stuff placed on the plate should be uniformly illuminated

by the IR radiation and with a view to minimising the risk of a person unintentionally touching the browning device.

Fig. 2 is an enlarged view of how the browning device is arranged on the top of the oven cavity while Fig. 3 is a cross-sectional view of the browning device recessed in the top of the oven cavity. The reflector 16 is made of a ceramic material and is in the shape of a parallelepiped with a recess. The recess has an opening the shape of which essentially conforms to the shape of the connection opening. The depth of the recess is typically between 10 and 100 mm and preferably between 20 and 40 mm. The width of the recess is typically between 5 and 50 mm and preferably between 10 and 30 mm. The surface of the recess is the reflective surface of the reflector. A metallic reflector holder 21 encloses the reflector. The short sides 22 of the reflector holder are formed with apertures intended for electric contacts for the radiation means. The edges 23 of the connection opening are bent slightly upwards and adapted to cooperate with the edges of the recess of the reflector.

The reflective surface of the reflector has two essentially parallel walls 24. The reflector is arranged such that its parallel walls extend in parallel with the long sides of the connection opening. In the plane perpendicular to the long sides of the connection opening, the reflector has the form of two essentially parallel sides. The reflector is arranged such that the surface on which direct radiation from the entire radiation means falls is positioned between the centre of the rotary plate and the rear edge thereof. This is illustrated in Fig. 3 by the two lines 25 and 25', the intersection of which with the rotary plate defines the surface on which direct radiation from the entire radiation means falls. Since the radiation intensity depends on the distance from the source of radiation, the direct radiation intensity will be at its maximum adjacent to 25'.

The radiation means 17 is a cylindrical halogen bulb which consists of a filament enclosed by an inert gas in a transparent envelope which typically has a diameter of between 2 and 30 mm and preferably between 5 and 15 mm.

5 The filament is heated to between 1300°C and 1500°C by letting current pass through the filament. The higher temperature will result in an increased radiation yield. The material of the reflector consists of compacted fibres of a dielectric having a high refractive index.

10 Preferably the reflector consists essentially of fibres, consisting of calcium oxide, calcium sulphate, silica, barium sulphate, zirconium oxide or titanium oxide, which are compacted. The reflector surface will appear as an extended light source when illuminated by IR radiation.

15 The reflector reflects at least 70% of the incident radiation for wavelengths between 1 and 2 μm , where the radiation means has its maximum emission. The reflector also serves as a screen for preventing IR radiation directly from the lamp falling on the oven door or the

20 cavity walls. This is illustrated by the marginal rays 26 and 27. Fig. 3 illustrates that the direct radiation from the halogen bulb only falls on the loading zone which consists of the rotary plate. The halogen bulb is arranged relatively far into the reflector, and the reflector has a position and form as described above, such that

25 essentially all direct light from the halogen bulb falls either on the reflector or on the base of the oven cavity. The reflector concentrates the light that is reflected in the reflector essentially in the direction

30 of the loading zone.

The reflector material has low thermal conductivity and high temperature stability and withstands a temperature of 1000°C. The reflector resists heat in the respect that its mechanical strength is not reduced by intense

35 heat as well as in the respect that its reflective properties are retained at high temperatures. This entails that the bulb can be arranged close to the walls of the

reflector. The distance 28 between the halogen bulb and the reflector is typically smaller than 10 mm, preferably smaller than 5 mm and advantageously as small as 2 mm. By the recess being made deep and narrow, the opening 29 of the reflector can be made narrow, which permits a narrow connection opening, which results in a very small leakage of microwave radiation to the grill bulge. Moreover, the dimensions of the reflector can be small while at the same time direct radiation from the halogen bulb can be prevented from falling on the door of the oven. By the dimensions being small, there is no need for a large grill bulge.

In operation, the radiation of the bulb will be absorbed by the surface of the reflector. The surface will be heated until the temperature is so high that the energy absorbed via the radiation of the lamp is balanced by the energy radiated from the reflector and the significantly reduced energy which is conducted by means of the reflector out to the casing. The surface temperature of the reflector thus depends on the distance between the reflector and the bulb. The distance is selected such that the reflector obtains a surface temperature of at least 500°C, such that the temperature is sufficiently high for fat hitting the surface to be burnt off. IR radiation will then be emitted also from the reflector surface which acts as a black body radiator.

As mentioned above, the marginal rays 26, 27 define the area which is hit by direct light from the halogen bulb. If the marginal rays are extended backwards to the reflector, the marked area 30 between the intersection of the marginal rays 26, 27 with the reflector surface will define the area from which emitted IR radiation hits only the same area which is illuminated by direct light from the bulb. Parts of the IR radiation emitted from other parts of the reflector, outside the area 30, will hit also the door of the oven and the rear wall. However, the highest temperature of the reflector is to be found in

the inner part and, thus, also the radiation intensity is at its maximum in that part. The parts 31 of the reflector which have the maximum solid angle filled with the oven door or the rear wall are the coldest parts closest
5 to the opening.

The high temperature of the reflector results in the fat hitting the reflector surface in operation being automatically burnt off. Thus the reflector has a self-cleaning function and therefore does not need a protective grating between the browning device and the oven
10 cavity.

The grilling means can alternatively be arranged in connection with the top of the oven cavity inside the oven cavity. This is possible thanks to the reflector
15 being made of a non-metallic material. An advantage of having the grill element arranged inside the oven cavity is that there is no need for a connection opening through which microwave radiation can leak. This configuration, however, may place greater demands on the design of the
20 contacts of the bulb since these are exposed to a higher field.

In the above embodiments, the reflector has been described as a homogeneous ceramic reflector, but alternatively merely a surface layer is made of a reflective
25 heat-resisting material.

There are several materials that are suitable as reflector materials. The demands placed on a suitable reflector material are that it should withstand a high temperature, have heat-insulating properties and reflect
30 IR radiation. A plurality of ceramic materials satisfying these demands are available. A person skilled in the art realises that several materials satisfy the demands.

A person skilled in the art realises that there are many possibilities of variations of the above embodiments
35 within the scope of the invention.

CLAIMS

1. A microwave oven (1) for heating foodstuffs, comprising
5 an oven cavity (4),
a loading zone for the foodstuffs arranged in the oven cavity,
a microwave unit (8) for feeding microwaves to the
10 oven cavity, and
a browning device (13) having a radiation means (17) for generating infrared (IR) radiation and a reflector (16),
c h a r a c t e r i s e d in that at least a surface
15 layer of the reflector is made of a non-metallic, reflective and heat-resisting material.
2. A microwave oven as claimed in claim 1, c h a r a c t e r i s e d in that the reflector has essentially retained reflection properties for temperatures of at
20 least 500°C and preferably at least 800°C.
3. A microwave oven as claimed in claim 1 or 2, c h a r a c t e r i s e d in
that the reflector has the form of a recess with two parallel sides and a base, and
25 that the radiation means has such a position inside the reflector and the reflector such a position in relation to the loading zone that essentially only the loading zone is hit by direct radiation from the radiation means.
- 30 4. A microwave oven as claimed in any one of the preceding claims, c h a r a c t e r i s e d in that the reflector reflects at least 70% of the incident IR radiation for wavelengths between 1 and 2 micrometer.
- 35 5. A microwave oven as claimed in any one of the preceding claims, c h a r a c t e r i s e d in that the radiation means consists of a filament surrounded by a

transparent cylindrical envelope which is filled with an inert gas.

6. A microwave oven as claimed in claim 5, characterised in that the distance between the envelope and the reflector is typically smaller than 10 mm, preferably smaller than 5 mm and advantageously smaller than 2 mm.

7. A microwave oven as claimed in any one of the preceding claims, characterised in that the radiation means has a temperature of between 1300°C and 1500°C.

8. A microwave oven as claimed in claim 3, characterised in that it also comprises means (18) which define a cavity outside the actual oven cavity, which cavity has a connection opening (19) to the oven cavity and in which cavity the browning device is arranged, the connection opening being adapted to the width of the recess and the connection opening having an elongate shape of a width which is less than half the wavelength of the microwaves.

9. A microwave oven as claimed in any one of the preceding claims, characterised in that the non-metallic material is a ceramic material.




10. A microwave oven as claimed in any one of claims 1-8, characterised in that the non-metallic material consists of compacted grains of a dielectric material having a refractive index above 1.5.

11. A microwave oven as claimed in any one of claims 1-8, characterised in that at least a surface layer of the reflector is essentially made of one of the materials calcium oxide, calcium sulphate, silica, barium sulphate, zirconium oxide or titanium oxide.

12. A microwave oven as claimed in any one of the preceding claims, characterised in that it also comprises a rotary plate and that the reflector is partly arranged between a part of the radiation means and the centre of the rotary plate

such that part of the direct radiation from the radiation means is thus prevented from hitting the centre of the rotary plate.

5 13. Use of a radiation means having a temperature of between 1300°C and 1500°C, and a reflector made of a non-metallic, reflective and heat-resisting material, as grill element in a microwave oven.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/07661

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H05B6/80

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 771 154 A (BELL) 13 September 1988 (1988-09-13) abstract	1,5,9
Y	column 2, line 8 - line 27	3
A	column 2, line 43 - line 46 ---	13
X	US 4 803 324 A (FUJI) 7 February 1989 (1989-02-07)	1
Y	column 4, line 7 - line 37	3
A	column 5, line 64 - column 6, line 66 ---	13
X	US 3 783 220 A (TANIZAKI) 1 January 1974 (1974-01-01)	1,11
A	abstract column 3, line 31 - line 42 -----	13

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

14 January 2000

Date of mailing of the international search report

21/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Taccoen, J-F

INTERNATIONAL SEARCH REPORT

...ormation on patent family members

International Application No

PCT/EP 99/07661

Patent document cited in search report	A	Publication date	Patent family member(s)	Publication date	Publication date
US 4771154	A	13-09-1988	CA 1262264 A EP 0226407 A	10-10-1989 24-06-1987	
US 4803324	A	07-02-1989	CA 1289627 A US 4870255 A	24-09-1991 26-09-1989	
US 3783220	A	01-01-1974	DE 2132369 A NL 7108793 A	13-01-1972 10-01-1972	