

# Authoring experience

Alex Jitianu  
[alex\\_jitianu@oxygenxml.com](mailto:alex_jitianu@oxygenxml.com)



# Agenda

- Document templates customization
- Custom form controls (Javascript)
- Changing the document through Javascript & XQuery Update actions

# Guided authoring

- Focus on fixing
  - Schematron business rules
  - Schematron Quick Fixes (SQF)
- Focus on preventing
  - Inline actions
  - Contextual hints

# Templates



"Moderate"  
business letter



"Modern"  
business letter



mediawiki



CV



Resume



Businesscard-  
with-logo

# Templates and Hints (1)

- Hints can be specified in the CSS


```
title {  
    -oxy-placeholder-content:"The title is very important!";  
}
```

# Templates and Hints (1)

- Hints can be specified in the CSS

```
shortdesc {  
    -oxy-placeholder-content:"A short overview of the topic.";  
}
```

- Disadvantages
  - An additional CSS is required together with the template
  - Can be difficult to specify context sensitive messages



# Templates and Hints (2)

- Hints specified as Processing Instructions

```
<section>
    <title><?oxy-placeholder content="First title"?></title>
    <p><?oxy-placeholder content="First section's content"?></p>
</section>
<section>
    <title><?oxy-placeholder content="Second title"?></title>
    <p><?oxy-placeholder content="Second section's content"?></p>
</section>
```

# Templates and Hints (2)

- Hints specified as Processing Instructions

```
<section>
    <title><?oxy-placeholder content="First title"?></title>
    <p><?oxy-placeholder content="First section's content"?></p>
</section>
<section>
    <title><?oxy-placeholder content="Second title"?></title>
    <p><?oxy-placeholder content="Second section's content"?></p>
</section>
```

- Controlling the hints' styling

```
p:oxy-placeholder:empty {
    color: rgb(0, 50, 255);
}
```

# Form controls

- Built-in form controls
  - Text field
  - Combo boxes
  - etc.
- Custom ones (Java-based API)
  - HTML + Javascript (JavaFX Web Browser)

```
elementName {  
    content: oxy_combobox(  
        edit, '@attribute',  
        values, 'one, two, three')
```

# Google maps form control (1)

- A Java part
  - a JavaFx Web Browser
  - Oxygen's form controls API
  - Javascript → Java bridge
- An HTML part
- A Javascript part
  - It can update the document through the Javascript→Java bridge

# Google maps form control (1)

- A Java part
  - a JavaFx Web Browser
  - Oxygen's form controls API
  - Javascript → Java bridge
- An HTML part
- A Javascript part
  - It can update the document through the Javascript→Java bridge

<https://github.com/AlexJitianu/oXygen-XML-map-form-control>

# Google maps form control (2)

- It is bound from the CSS:

```
address:-oxy-edit-gps:before(4) {  
    content: oxy_editor(  
        saHeavyFormControlClassName ,  
        "com.oxygenxml.samples.jfx.GoogleMapFormControl");  
}
```

[https://raw.githubusercontent.com/AlexJitianu/oxygen-XML-map-form-control/master/build/update\\_site.xml](https://raw.githubusercontent.com/AlexJitianu/oxygen-XML-map-form-control/master/build/update_site.xml)

# XQuery Update author action

- The challenge:
  - Set an attribute on multiple elements
- Why is it a challenge?
  - *ChangeAttributeOperation* operates on a single element

# Javascript author action

- The challenge: Copy an address

```
<address  
lat="36.46017824849352"  
lng="25.372959673404694"> Nik. Nomikou, Oía 847 02, Greece</address>
```

Address: Nik. Nomikou, Oía 847 02, Greece

Latitude: 36.46017824849352

Longitude: 25.372959673404694

# Thank you!

Questions?

Alex Jitianu  
[alex\\_jitianu@oxygenxml.com](mailto:alex_jitianu@oxygenxml.com)  
@AlexJitianu